



Personal Systems Reference
IBM ThinkPad R Series
2001 to 2005 - withdrawn

May 2005 - Version 291



Type-model	Processor	Speed	Memory	Screen	Disk	Optical	Mini PCI Communications Bay	CDC Modem	Ethernet on planar	Preload	Workhorse or Global model	Avail date
2656-2BU	Celeron™	900	64MB ¹¹	13.3" XGA	10GB CD-ROM	802.11b/modem			10/100	Windows® 98 SE		Oct 2001
2656-22U	Celeron	900	64MB	13.3" XGA	10GB CD-ROM	Open		Modem	10/100	Windows 98 SE		Oct 2001
2656-32U	Pentium® III	1.0	128MB	13.3" XGA	15GB CD-ROM	Open		Modem	10/100	Windows 98 SE		Oct 2001
2656-5BU	Pentium III	1.0	128MB	13.3" XGA	15GB CD-RW	802.11b/modem			10/100	Windows 98 SE		Oct 2001
2656-62U	Pentium III	1.0	128MB	14.1" XGA	30GB DVD-ROM	Open		Modem	10/100	Windows 98 SE	Workhorse/Global	Oct 2001
2656-7BU	Pentium III	1.0	128MB	14.1" XGA	30GB CD-RW	802.11b/modem			10/100	Windows 98 SE		Oct 2001
2656-82U**	Pentium III	1.0	256MB	14.1" XGA	30GB DVD-ROM	Open		Modem	10/100	Windows 98 SE	Workhorse/Global	Dec 2001

Positioning Processor	<i>Best blend of portability and essential features; two-spindle system</i>		<p align="center">SOFTWARE¹⁴</p> <p>Windows 98 models</p> <ul style="list-style-type: none"> - Microsoft® Windows® 98 Second Edition ◇ Disk-to-Disk Recovery (in hidden Service Partition) <p>INCLUDED SOFTWARE¹⁴ (all)</p> <p>Preloaded</p> <ul style="list-style-type: none"> • Access ThinkPad • Adobe® Acrobat • ConfigSafe® • Mediamatics™ DVD (DVD models) • MusicMatch Jukebox • PC-Doctor™ • ThinkPad Assistant™ • ThinkPad Utilities • IBM Update Connector™.15 • Veritas RecordNOW (CD-RW mod) <p>Downloadable</p> <ul style="list-style-type: none"> • IBM Rapid Restore PC • IBM Data Transfer • Universal Manageability Services™ <p>License</p> <ul style="list-style-type: none"> - Lotus® SmartSuite® Millennium 		
L2 cache	Celeron: 128KB / onboard (at processor speed) / ECC Pentium III: 256KB / onboard (at processor speed) / ECC				
Memory	64MB, 128MB or 256MB ⁹ standard / 1GB maximum / SDRAM / non-parity / 100MHz (chipset limits to 100MHz although 133MHz SO-DIMMs used) / PC 133 / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available				
Diskette drive CD-ROM CD-RW DVD-ROM Ultrabay 2000 Disk	None standard / use optional Ultrabay™-based or USB-based diskette drive <i>Some:</i> CD-ROM / 24X-10X ¹⁰ speed / bootable / removable from Ultrabay™ Plus <i>Some:</i> CD-RW / 8X/4X/24X ¹⁰ Max / removable from Ultrabay Plus <i>Some:</i> DVD-ROM / 8X-3.3X ¹⁰ speed / removable from Ultrabay Plus One modular bay for interchangeable devices (right side) / Ultrabay Plus-compatible 10, 15, or 30GB⁸ (4200 rpm) / upgradeable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay				
Display	<i>Some:</i> 13.3" (337.8mm) XGA (1024x768) TFT color / Active Matrix <i>Some:</i> 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix <i>All:</i> Easy-open cover to unlatch and open with one hand				
Graphics controller	Trident® CyberBLADE™ Aladdin1 2X AGP 3D / 8MB ¹¹ SDRAM / Unified Memory Architecture / controller in M1632M Northbridge				
Graphics - external	External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200				
Keyboard	87-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar / pitch: 19mm; stroke: 2.7mm				
ThinkLight™ UltraPort™	Illuminates the keyboard to improve visibility in low-light conditions None				
Dimensions ¹⁴	12.3" x 10.0" x 1.42"				
Approximate weight ²	with optical drive and battery: <i>CD-ROM models:</i> 5.7 lbs; <i>DVD models:</i> 5.8 lbs; <i>CD-RW models:</i> 5.9 lbs				
Case material	<i>Color:</i> black; <i>All:</i> ABS plastic				
Battery - type	Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus				
Battery - life ¹³	2.5 hrs to 3.0 hrs depending on model				
Architecture	ALI chipset / M1632M Northbridge (memory, graphics, PCI, Mini PCI) / M1535 Southbridge (IDE, USB, parallel, audio, power management) / PCI 2.1, 32-bit 33MHz / O2® Micro OZ6912 for CardBus				
Port Replicator	Optional ThinkPad Port Replicator (no ThinkPad Dock support)				
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video				
Ports	Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port				
Video out	S-video out / one industry standard connector				
Mini PCI	One Mini PCI IIIb slot (Communications Bay) / not customer upgradeable				
CDC	One Communications Daughter Card (CDC) socket (open or modem) / not accessible				
Modem	<i>Some:</i> 56K ⁹ V.90 (V.92-capable ²⁹) CDC modem card / Lucent® chip set				
802.11b/modem	<i>Some:</i> Mini PCI 802.11b wireless ⁴ , Intersil® Prism 2.5 chipset, antennas in side of display and base, Wi-Fi-certified / 56K ¹² V.90 ²⁹ modem combo, Lucent® chipset				
Ethernet	10/100 ethernet on planar / Intel® 82550GY chipset				
Audio support	Soft audio / SoundBlaster-compatible / Realtek® ALC200 AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm)				
Security	Power-on password / hard disk password / supervisor password / security keyhole				
Limited warranty* ²²	1 year - EasyServ™.25 onsite pickup and delivery / warranty service upgrades ²¹				
64 MB SO DIMM	133MHz NP SDRAM	19K4650	USB Portable Diskette Drive	05K9276	<p>Universal 72 watt AC adapter</p> <p>PC 2001-compliant</p> <p>CIM and DMI 2.0-compliant</p> <p>Wired for Management 2.0</p> <p>IBM ImageUltra Services available</p> <p>IBM Rapid Restore PC available to protect software image and data</p> <p>Personalized Web-based support²³</p> <p>Setup Guide, Service and Troubleshooting Guide, Windows manual</p> <p>International Warranty Service²⁴</p> <p>24 hour x 7 day¹ toll-free hardware support during the warranty</p>
128 MB SO DIMM	133MHz NP SDRAM	19K4652	ThinkPad Removable Diskette Drive	08K9603	
256 MB SO DIMM	133MHz NP SDRAM	19K4654	ThinkPad R30 Series Li-Ion Battery	02K6821	
512 MB SO DIMM	133MHz NP SDRAM	19K4656	ThinkPad 72W AC Adapter	02K6699	
SuperDisk (LS-240)	UltraBay 2000	08K9616	ThinkPad 72W DC Auto Adapter	10K3820	
Zip 250MB	Ultrabay 2000 Drive	00N8253	ThinkPad Port Replicator	02K8667	
24X-10X CD-ROM	Ultrabay 2000 Drive	05K9233	Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)	19K4480	
8X/4X/24X Max CD-RW	Ultrabay 2000	08K9569	15GB Hard Disk Drive	08K9588	
8X-3X DVD	Ultrabay 2000 Drive	27L3448	30GB Hard Disk Drive	08K9593	
CD-RW/DVD Combo	Ultrabay 2000	08K9572	48GB Hard Disk Drive	08K9600	
Travel Bezel for	Ultrabay 2000	08K6070	ServicePac®.21 1yr IOR 9x5 NBD	30L9188	
Second HDD Adapter for	Ultrabay 2000	08K6068	ServicePac 2yr IOR 9x5 NBD	30L9189	
IBM ThinkPad	Ultrabay Plus Carrier	22P5737	ServicePac 3yr IOR 9x5 NBD	30L9195	
IBM ThinkPad	Ultrabay Plus c500 Cradle	22P5738	ServicePac 2yr P&L P/U Depot	30L9191	
ThinkPad	Ultrabay Plus Numeric Keypad	22P7330	ServicePac 3yr P&L P/U Depot	30L9192	

* For a copy of IBM's Statement of Limited Warranty, call 1-800-772-2227

** Special ordering only

US models announced October 9 or November 27, 2001

US models withdrawn effective April 2002

No warranties are expressed or implied in this summary
(R3098) © IBM Corp. April 2002

Type-model	Processor	Speed	Memory ¹¹	Screen	Disk GB ⁸	Optical	Mini PCI Comm Bay wireless/modem	CDC modem	Ethernet on planar	Security Chip Preload	Small business software	Workhorse (W) or Global (G) model	Avail date
2656-25U	Celeron™	1.06	128MB	13.3" XGA	20G	CD-ROM	Open	Modem	10/100	XP Home			Feb 2002
2656-A5U	Celeron	1.06	128MB	13.3" XGA	20G	CD-ROM	Open	Modem	10/100	XP Pro			Feb 2002
2656-AFU	Celeron	1.06	128MB	13.3" XGA	20G	CD-ROM	Wi-Fi ³² /mod	None	10/100	XP Pro			Feb 2002
2656-AKU	Celeron	1.06	128MB	13.3" XGA	20G	CD-ROM	Open	Modem	10/100	XP Pro	Office XP SB ¹⁸		Feb 2002
2656-AGU	Celeron	1.06	128MB	14.1" XGA	20G	CD-ROM	Wi-Fi/mod	None	10/100	XP Pro			Aug 2002
2656-HHU	Pentium® III-M	1.00	128MB	14.1" XGA	20G	DVD-ROM	Open	Modem	10/100	XP Pro		G	Mar 2002
2656-3FU	Pentium III-M	1.13	128MB	13.3" XGA	20G	CD-RW	Wi-Fi/mod	None	10/100	XP Home			Feb 2002
2656-BFU	Pentium III-M	1.13	128MB	13.3" XGA	20G	CD-RW	Wi-Fi/mod	None	10/100	XP Pro			Feb 2002
2656-E5U	Pentium III-M	1.13	128MB	14.1" XGA	30G	DVD-ROM	Open	Modem	10/100	XP Pro		W G	Feb 2002
2656-E6U	Pentium III-M	1.13	128MB	14.1" XGA	30G	CD-RW	Open	Modem	10/100	Yes	XP Pro		Feb 2002
2656-EFU	Pentium III-M	1.13	128MB	14.1" XGA	30G	DVD-ROM	Wi-Fi/mod	None	10/100	XP Pro		W G	Feb 2002
2656-HFU	Pentium III-M	1.13	128MB	14.1" XGA	40G	DVD/CD-RW	Wi-Fi/mod	None	10/100	Yes	XP Pro		Feb 2002
2656-EHU	Pentium III-M	1.13	128MB	14.1" XGA	30G	DVD-ROM	Wi-Fi/mod	None	10/100	XP Pro	Office XP SB		Feb 2002
2656-HGU	Pentium III-M	1.13	128MB	14.1" XGA	40G	DVD/CD-RW	Wi-Fi/mod	None	10/100	Yes	XP Pro	Office XP SB	Feb 2002
Positioning Processor	Best blend of portability and essential features; two-spindle system												
L2 cache	Intel® Mobile Celeron™ 1.06GHz with 133MHz frontside bus or Intel Mobile Pentium® III-M 1.0 or 1.13GHz with Speedstep™ technology ¹ with 133MHz frontside bus												
Memory	Celeron: 256KB / at processor speed; Pentium III: 512 KB / at processor speed 128MB standard / 1GB max ⁷ / SDRAM / non-parity / 133MHz / PC133 / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available												
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive												
CD-ROM	Some: CD-ROM / 24X-10X ⁹ speed / bootable / removable												
CD-RW	Some: CD-RW / 8X/4X/24X Max ⁹ / removable												
DVD-ROM	Some: DVD-ROM / 8X-3.3X ⁹ speed / removable												
DVD-ROM/CD-RW	Some: DVD-ROM/CD-RW combo / 8X/8X/24X/8X ²¹ speed / removable												
Ultrabay 2000	One modular bay for interchangeable devices (right side) / Ultrabay™ Plus-compatible												
Disk	20, 30, or 40GB ⁸ (4200 rpm) / upgradable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay												
Display	Some: 13.3" (337.8mm) XGA (1024x768) TFT color / Active Matrix Some: 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix												
Graphics controller	Intel 830MG Integrated Direct AGP 3D / Unified Memory Architecture / in GMCH / controller dynamically allocates 8 to 32MB ¹¹ of system memory for graphics												
Graphics - external	External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200												
Keyboard	87-key / ThinkPad Button / palm rest / TrackPoint™, "Press-to-Select," Internet Scroll Bar ¹³ / pitch: 19mm; stroke: 2.7mm												
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions / no UltraPort™												
Dimensions ³	12.3" x 10.0" x 1.42" / 313mm x 254mm x 36mm												
Approximate weight ²	w/ battery and: CD-ROM: 5.8 lbs; DVD: 5.8 lbs; CD-RW: 6.1 lbs; DVD/CD-RW: 6.1 lbs												
Case material	Color: Black; All: ABS plastic												
Battery - type	Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus												
Battery - life ¹⁰	Celeron models: 2.4 to 2.6 hrs; Pentium III models: 2.9 to 3.1 hrs												
Architecture	Intel 830MG chipset / 82830MG Graphics Memory Controller Hub (GMCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100/66 EIDE, PCI bus, USB, Low Pin Count bus, ethernet, AC-Link) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus, Mini PCI) / Firmware Hub / LPC bus 33MHz (NS PC87392VJG Super I/O for parallel, infrared)												
Port Replicator	Optional ThinkPad Port Replicator (no ThinkPad Dock support)												
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door												
Ports	Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port												
Video out	S-video out port (TV out) / one industry standard connector												
Mini PCI	One Mini PCI type III slot (Communications Bay) / not customer upgradable												
Wi-Fi ³² /modem	Some: Mini PCI Wi-Fi ³² wireless ⁴ , Intel® PrISM 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K ⁶ V.90 (V.92-designed ²⁹) modem combo, Lucent® chipset												
CDC	One Communications Daughter Card (CDC) socket (open or modem) / not accessible												
Modem	Some: 56K ⁶ V.90 (V.92-designed ²⁹) CDC modem card / Lucent® chip set												
Ethernet	10/100 ethernet on planar / Intel® 82562ET chipset												
Audio support	Soft audio / SoundBlaster-compatible / Analog Devices AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm)												
Security	Power-on password / hard disk password / supervisor password / security keyhole Some: IBM Embedded Security Subsystem ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶												
Limited warranty ¹²	1 year - EasyServ™.19 onsite pickup and delivery / service upgrades ²² available												
64 MB SO DIMM	133MHz NP SDRAM	19K4650	USB Portable Diskette Drive	05K9276									
128 MB SO DIMM	133MHz NP SDRAM	19K4652	ThinkPad R30/R31 Li-Ion Battery	02K6821									
256 MB SO DIMM	133MHz NP SDRAM	19K4654	ThinkPad 72W AC Adapter	02K6699									
512 MB SO DIMM	133MHz NP SDRAM	19K4656	ThinkPad Port Replicator	02K8667									
SuperDisk (LS-240)	Ultrabay 2000	08K9616	Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)	19K4480									
Zip 250MB	Ultrabay 2000 Drive	00N8253	20GB Hard Disk 9.5mm (4200 rpm)	08K9686									
24X-10X CD-ROM	Ultrabay 2000 Drive	05K9233	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816									
8X/4X/24X Max CD-RW	Ultrabay 2000	22P9101	IBM Optical 3-Button Travel Wheel Mouse	31P7410									
Ultralight 8X	Max DVD Ultrabay 2000	22P9102	ServicePac ²² 1yr IOR 9x5 NBD	30L9188									
CD-RW/DVD Combo III	Ultrabay 2000	22P6980	ServicePac 2yr IOR 9x5 NBD	30L9189									
Second HDD Adapter for Ultrabay 2000		08K6068	ServicePac 3yr IOR 9x5 NBD	30L9195									
IBM ThinkPad Ultrabay Plus Carrier		22P5737	ServicePac 2yr P&L P/U Depot	30L9191									
IBM ThinkPad Ultrabay Plus c500 Cradle		22P5738	ServicePac 3yr P&L P/U Depot	30L9192									
ThinkPad Ultrabay Plus Numeric Keypad		22P7330											

SOFTWARE¹⁴

Windows XP Home models

- Microsoft® Windows® XP Home²⁰
- ↳ Disk-to-Disk Recovery (in hidden Service Partition)

Windows XP Pro models

- Microsoft® Windows® XP Professional²⁰
- ↳ Disk-to-Disk Recovery (in hidden Service Partition)

INCLUDED SOFTWARE¹⁴ (all)

Preloaded

- Access ThinkPad
- Access Connections
- Access Help
- Access Support
- Adobe® Acrobat
- InterVideo WinDVD (DVD models)
- Norton AntiVirus
- PC-Doctor™
- ThinkPad Utilities
- IBM Update Connector™.15
- Veritas RecordNOW (CD-RW mod)

Downloadable

- IBM Rapid Restore™ PC
- IBM Data Transfer
- Veritas RecordNOW (CD-RW mod)

License

- Lotus® SmartSuite® Millennium and Lotus Notes® Client 5.0

Microsoft Office XP Small Business²⁸ Models

- Microsoft Office XP Small Business¹⁸ (Word, Excel, Outlook, Publisher, Small Business Tools)
- ↳ Office XP Small Business CD

Ultrabay Plus integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series

Other options at ibm.com/pc/us/accessories

Universal 72 watt AC adapter
PC 2001-compliant
CIM and DMI 2.0-compliant
IBM ImageUltra™ Services available
IBM Rapid Restore PC available to protect software image and data
Setup Guide, Service and Troubleshooting Guide, Windows manual
International Warranty Service¹⁷
24 hour x 7 day¹⁸ toll-free hardware support during the warranty¹²

See footnotes for important warranty information
US models announced January 22, March 19, or August 13, 2002
US models withdrawn effective July 2002, January 2003, or July 2003

Type-model	Processor	Speed	Memory ¹¹	Screen	Disk GB ⁸	Optical	Mini PCI Comm Bay wireless/modem	CDC modem	Ethernet on planar	Security Chip	Preload	Small business software	Workhorse (W) or Global (G) model	Avail date
2656-F5U	Pentium® III-M	1.13	128MB	14.1" XGA	30G	DVD-ROM	Open	Modem	10/100		XP Pro			Apr 2002
2656-H4U	Pentium III-M	1.13	128MB	14.1" XGA	30G	CD-RW	Open	Modem	10/100	Yes	XP Pro			Apr 2002
2656-H8U	Pentium III-M	1.13	128MB	14.1" XGA	40G	DVD/CD-RW	Wi-Fi ³² /mod	None	10/100	Yes	XP Pro			Apr 2002
2656-FGU	Pentium III-M	1.13	256MB	14.1" XGA	30G	DVD-ROM	Open	Modem	10/100		XP Pro			Apr 2002
2656-M4U	Pentium III-M	1.0	128MB	14.1" XGA	20G	DVD-ROM	Open	Modem	10/100		XP Pro			Apr 2002
2656-H6U	Pentium III-M	1.13	128MB	14.1" XGA	30G	DVD-ROM	Wi-Fi/mod	None	10/100		XP Pro	Office XP SB ¹⁸		Apr 2002
2656-H9U	Pentium III-M	1.13	128MB	14.1" XGA	40G	DVD/CD-RW	Wi-Fi/mod	None	10/100	Yes	XP Pro	Office XP SB		Apr 2002
2656-H5U	Pentium III-M	1.13	128MB	14.1" XGA	30G	CD-RW	Open	Modem	10/100	Yes	Windows 2000			Apr 2002
2656-H7U	Pentium III-M	1.13	128MB	14.1" XGA	40G	DVD/CD-RW	Wi-Fi/mod	None	10/100	Yes	Windows 2000			Apr 2002
2656-F4U	Pentium III-M	1.13	128MB	14.1" XGA	30G	DVD-ROM	Open	Modem	10/100		Windows 2000			Apr 2002
2656-FEU	Pentium III-M	1.13	256MB	14.1" XGA	30G	DVD-ROM	Open	Modem	10/100		Windows 2000			Apr 2002
2656-L4U	Pentium III-M	1.0	128MB	14.1" XGA	20G	DVD-ROM	Open	Modem	10/100		Windows 2000			Apr 2002

Positioning	<i>Best blend of portability and essential features; two-spindle system</i>										
TAA-compliant Processor	Trade Act Agreement-compliant Intel® Mobile Pentium® III-M 1.0 or 1.13GHz with Speedstep™ technology ¹ with 133MHz Front Side Bus										
L2 cache	512 KB / at processor speed / ECC										
Memory	128 or 256MB standard / 1GB max ⁷ / SDRAM / non-parity / 133MHz / PC133 / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available										
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive										
CD-RW	<i>Some:</i> CD-RW / 8X/4X/24X Max ⁹ / removable										
DVD-ROM	<i>Some:</i> DVD-ROM / 8X-3.3X speed / removable										
DVD-ROM/CD-RW	<i>Some:</i> DVD-ROM/CD-RW combo / 8X/8X/24X/8X ²¹ speed / removable										
Ultrabay 2000	One modular bay for interchangeable devices (right side) / Ultrabay™ Plus -compatible										
Disk	20, 30, or 40GB⁸ (4200 rpm) / upgradeable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay										
Display	14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix										
Graphics controller	Intel 830MG Integrated Direct AGP 3D / Unified Memory Architecture / in GMCH / controller dynamically allocates 8 to 32MB ¹¹ of system memory for graphics										
Graphics - external	External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200										
Keyboard	87-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar ¹³ / pitch: 19mm; stroke: 2.7mm										
ThinkLight™ UltraPort™	Illuminates the keyboard to improve visibility in low-light conditions None										
Dimensions ³	12.3" x 10.0" x 1.42" / 313mm x 254mm x 36mm										
Approximate weight ²	w/ battery and: <i>DVD-ROM</i> : 5.8 lbs; <i>CD-RW</i> : 6.1 lbs; <i>DVD/CD-RW</i> : 6.1 lbs										
Case material	Color: black; All: ABS plastic										
Battery - type	Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus										
Battery - life ¹⁰	<i>802.11b models</i> : 2.9 hrs; <i>Others</i> : 3.1 hrs										
Architecture	Intel 830MG chipset / 82830MG Graphics Memory Controller Hub (GMCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100/66 EIDE, PCI bus, USB, Low Pin Count bus, ethernet, AC-Link) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus, Mini PCI) / Firmware Hub / LPC bus 33MHz (NS PC87392VJG Super I/O for parallel, infrared)										
Port Replicator	Optional ThinkPad Port Replicator (no ThinkPad Dock support)										
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video										
Ports	Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port										
Video out	S-video out port (TV out) / one industry standard connector										
Mini PCI	One Mini PCI type III slot (Communications Bay) / not customer upgradeable										
Wi-Fi ³² /modem	<i>Some:</i> Mini PCI Wi-Fi ³² wireless ⁴ , Intersil® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K ⁶ V.90 (V.92-designed ²⁹) modem combo, Lucent® chipset										
CDC	One Communications Daughter Card (CDC) socket (open or modem) / not accessible										
Modem	<i>Some:</i> 56K ⁶ V.90 (V.92-designed ²⁹) CDC modem card / Lucent® chip set										
Ethernet	10/100 ethernet on planar / Intel® 82562ET chipset										
Audio support	Soft audio / SoundBlaster-compatible / Analog Devices AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm)										
Security	Power-on password / hard disk password / supervisor password / security keyhole <i>Some:</i> IBM Embedded Security Subsystem³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶										
Limited warranty ¹²	1 year - EasyServ™ ¹⁹ onsite pickup and delivery / warranty service upgrades ²²										

SOFTWARE¹⁴

Windows XP Pro models

- Microsoft® Windows® XP Professional²⁰
- ↳ Disk-to-Disk Recovery (in hidden Service Partition)

Windows 2000 models

- Microsoft Windows 2000 Professional²⁰
- ConfigSafe®
- ↳ Disk-to-Disk Recovery (in hidden Service Partition)

INCLUDED SOFTWARE¹⁴ (all)

Preloaded

- Access ThinkPad
- Access Connections
- Access Help
- Access Support
- Adobe® Acrobat
- InterVideo WinDVD (DVD models)
- Norton AntiVirus
- PC-Doctor™
- ThinkPad Utilities
- IBM Update Connector™¹⁵
- Veritas RecordNOW (CD-RW mod)

Downloadable

- IBM Rapid Restore™ PC
- IBM Data Transfer
- IBM Director Agent
- IBM Client Security Software (for security chip)

License

- Lotus® SmartSuite® Millennium and Lotus Notes® Client 5.0

Microsoft Office XP Small Business¹⁸ Models (H6U and H9U)

- Microsoft Office XP Small Business²⁸ (Word, Excel, Outlook, Publisher, Small Business Tools)
- ↳ Office XP Small Business CD

Ultrabay Plus integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series

64 MB SO DIMM	133MHz NP SDRAM	19K4650	USB Portable Diskette Drive	05K9276
128 MB SO DIMM	133MHz NP SDRAM	19K4652	ThinkPad R30/R31 Li-Ion Battery	02K6821
256 MB SO DIMM	133MHz NP SDRAM	19K4654	ThinkPad 72W AC Adapter	02K6699
512 MB SO DIMM	133MHz NP SDRAM	19K4656	ThinkPad Port Replicator	02K8667
SuperDisk (LS-240)	UltraBay 2000	08K9616	Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)	19K4480
Zip 250MB	Ultrabay 2000 Drive	00N8253	20GB HDD	08K9686
24X-10X CD-ROM	Ultrabay 2000 Drive	05K9233	40GB HDD	08K9687
8X/4X/24X Max CD-RW	Ultrabay 2000	22P9101	60GB HS Hard Disk 9.5mm (5400 rpm)	08K9688
Ultralight 8X Max DVD	Ultrabay 2000	22P9102	ServicePac ²² 1yr IOR 9x5 NBD	30L9188
CD-RW/DVD Combo II	Ultrabay 2000	08K9701	ServicePac 2yr IOR 9x5 NBD	30L9189
Second HDD Adapter for	Ultrabay 2000	08K6068	ServicePac 3yr IOR 9x5 NBD	30L9195
IBM ThinkPad Ultrabay Plus Carrier		22P5737	ServicePac 2yr P&L P/U Depot	30L9191
IBM ThinkPad Ultrabay Plus c500 Cradle		22P5738	ServicePac 3yr P&L P/U Depot	30L9192
ThinkPad Ultrabay Plus Numeric Keypad		22P7330		

See footnotes for important warranty information
US models announced April 2, 2002
US models withdrawn effective October 2002

Type-model	Processor	GHz	Memory ¹	Screen	Disk	Optical	Mini PCI Comm Bay	CDC Modem	Ethernet on planar	Security Chip	Preload	Workhorse (W) or Global (G) model	Avail date
2657-F4U	Pentium® III-M	1.13	128MB	14.1" XGA	30GB ⁸	DVD-ROM	Open	Modem	10/100	No	Windows® 2000		Apr 2002
2657-FEU	Pentium III-M	1.13	256MB	14.1" XGA	30GB	DVD-ROM	Open	Modem	10/100	No	Windows 2000		Apr 2002
2657-F5U	Pentium III-M	1.13	128MB	14.1" XGA	30GB	DVD-ROM	Open	Modem	10/100	No	Windows XP Pro		Apr 2002
2657-FGU	Pentium III-M	1.13	256MB	14.1" XGA	30GB	DVD-ROM	Open	Modem	10/100	No	Windows XP Pro		Apr 2002

• 2657 models have a 3 year limited warranty (other 2656 ThinkPad R31 systems have a 1 year limited warranty)
• Trade Act Agreement (TAA)-compliant models

Positioning	Best blend of portability and essential features; two-spindle system												
TAA-compliant	Trade Act Agreement-compliant												
Processor	Intel® Mobile Pentium® III Processor-M 1.13GHz with Speedstep™ technology ¹ with 133MHz Front Side Bus												
L2 cache	512 KB / at processor speed												
Memory	128MB or 256MB standard / 1GB maximum ⁷ / SDRAM / non-parity / 133MHz / PC133 / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available												
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive												
CD-RW	DVD-ROM / 8X-3.3X ⁹ speed / removable												
Ultrabay 2000	One modular bay for interchangeable devices (right side) / Ultrabay™ Plus-compatible												
Disk	30GB ⁸ (4200 rpm) / upgradeable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay												
Display	14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix												
Graphics controller	Intel 830MG Integrated Direct AGP 3D / Unified Memory Architecture / in GMCH / controller dynamically allocates 8 to 32MB ¹¹ of system memory for graphics												
Graphics - external	External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200												
Keyboard	87-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar ¹³ / pitch: 19mm; stroke: 2.7mm												
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions												
UltraPort™	None												
Dimensions ³	12.3" x 10.0" x 1.42" / 313mm x 254mm x 36mm												
Approximate weight ²	w/ battery and DVD: 5.8 lbs (2.6 kg)												
Case material	Color: black; All: ABS plastic												
Battery - type	Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus												
Battery - life ¹⁰	2.5 to 3.1 hrs												
Architecture	Intel 830MG chipset / 82830MG Graphics Memory Controller Hub (GMCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100/66 EIDE, PCI bus, USB, Low Pin Count bus, ethernet, AC-Link) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus, Mini PCI) / Firmware Hub / LPC bus 33MHz (NS PC87392VJG Super I/O for parallel, infrared)												
Port Replicator	Optional ThinkPad Port Replicator (no ThinkPad Dock support)												
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video												
Ports	Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port												
Video out	S-video out port (TV out) / one industry standard connector												
Mini PCI	One Mini PCI type III slot (Communications Bay) / not customer upgradeable												
Wi-Fi ³² wireless	None												
CDC	One Communications Daughter Card (CDC) socket / not accessible												
Modem	56K ⁶ V.90 (V.92-designed ²⁹) CDC modem card / Lucent® chip set												
Bluetooth™	None												
Ethernet	10/100 ethernet on planar / Intel® 82562ET chipset												
Audio support	Soft audio / SoundBlaster-compatible / Analog Devices AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm)												
Security	Power-on password / hard disk password / supervisor password / security keyhole												
Limited warranty ¹²	3 years/1 year battery - EasyServ™-19 onsite pickup and delivery / warranty service upgrades ²²												
SOFTWARE¹⁴													
Windows XP Pro models													
- Microsoft® Windows® XP Professional ²⁰													
✦ Disk-to-Disk Recovery (in hidden Service Partition)													
Windows 2000 models													
- Microsoft Windows 2000 Professional ²⁰													
- ConfigSafe®													
✦ Disk-to-Disk Recovery (in hidden Service Partition)													
INCLUDED SOFTWARE¹⁴ (all)													
Preloaded													
• Access ThinkPad													
- Access Connections													
- Access Help													
- Access Support													
• Adobe® Acrobat													
• InterVideo WinDVD (DVD models)													
• Norton AntiVirus													
• PC-Doctor™													
• ThinkPad Utilities													
• IBM Update Connector™-15													
Downloadable													
• IBM Rapid Restore™ PC													
• IBM Data Transfer													
• IBM Director Agent													
• IBM Client Security Software (for security chip)													
License													
- Lotus® SmartSuite® Millennium and Lotus Notes® Client 5.0													
Ultrabay Plus integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series													
Other options at ibm.com/pc/us/accessories													
64 MB SO DIMM	133MHz NP SDRAM	19K4650	USB Portable Diskette Drive	05K9276	Universal 72 watt AC adapter								
128 MB SO DIMM	133MHz NP SDRAM	19K4652	ThinkPad Removable Diskette Drive	08K9603	PC 2001-compliant								
256 MB SO DIMM	133MHz NP SDRAM	19K4654	ThinkPad R30/R31 Li-Ion Battery	02K6821	CIM and DMI 2.0-compliant								
512 MB SO DIMM	133MHz NP SDRAM	19K4656	ThinkPad 72W AC Adapter	02K6699	IBM ImageUltra Services available								
IBM 32MB USB Memory Key		22P5296	ThinkPad Port Replicator	02K8667	IBM Rapid Restore PC available to protect software image and data								
SuperDisk (LS-240) UltraBay 2000		08K9616	Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)	19K4480	Personalized Web-based support ³¹								
Zip 250MB Ultrabay 2000 Drive		00N8253	20GB HDD	08K9686	Setup Guide, Service and Troubleshooting Guide, Windows manual								
24X-10X CD-ROM Ultrabay 2000 Drive		05K9233	40GB HDD	08K9687	International Warranty Service ¹⁷								
8X/4X/24X Max CD-RW Ultrabay 2000		22P9101	60GB HS Hard Disk 9.5mm (5400 rpm)	08K9688	24 hour x 7 day ¹⁸ toll-free hardware support during the warranty ¹²								
Ultralight 8X Max DVD Ultrabay 2000		22P9102	IBM USB 2.0 Portable CD-RW Drive	22P5297									
CD-RW/DVD Combo II Ultrabay 2000		08K9701	ThinkPad Portable 20GB Hard Disk Drive	10K0177									
Second HDD Adapter for Ultrabay 2000		08K6068	IBM 1GB Microdrive	07N5574									
IBM ThinkPad Ultrabay Plus Carrier		22P5737	IBM USB Mobile Mouse	33L3243									
IBM ThinkPad Ultrabay Plus c500 Cradle		22P5738	ServicePac®, 22 2yr IOR 9x5 NBD	30L9190									
ThinkPad Ultrabay Plus Numeric Keypad		22P7330	ServicePac 3yr IOR 9x5 NBD	30L9197									
Other options at ibm.com/pc/us/accessories													

See footnotes for important warranty information
US models announced April 2, 2002
US models withdrawn effective October 2002

Type-model	Processor	GHz	Memory ¹¹	Screen	Disk	Optical	Mini PCI Comm Bay wireless/modem	CDC Modem	Ethernet on planar	Security Chip	Preload	Workhorse (W) or Global (G) model	Avail date
2656-A4U	Celeron™	1.06	128MB	13.3" XGA	20GB ⁸	CD-ROM	Open	Modem	10/100		Windows® 2000		Feb 2002
2656-AEU	Celeron	1.06	128MB	13.3" XGA	20GB	CD-ROM	Wi-Fi ³² /mod	None	10/100		Windows 2000		Feb 2002
2656-FFU	Pentium® III-M	1.00	128MB	14.1" XGA	20GB	DVD-ROM	Open	Modem	10/100		Windows 2000	G	Mar 2002
2656-BEU	Pentium III-M	1.13	128MB	13.3" XGA	20GB	CD-RW	Wi-Fi/modem	None	10/100		Windows 2000		Feb 2002
2656-EEU	Pentium III-M	1.13	128MB	14.1" XGA	30GB	DVD-ROM	Wi-Fi/modem	None	10/100		Windows 2000	W G	Feb 2002
2656-E4U	Pentium III-M	1.13	128MB	14.1" XGA	30GB	DVD-ROM	Open	Modem	10/100		Windows 2000	W G	Feb 2002
2656-E7U	Pentium III-M	1.13	128MB	14.1" XGA	30GB	CD-RW	Open	Modem	10/100	Yes	Windows 2000		Feb 2002
2656-HEU	Pentium III-M	1.13	128MB	14.1" XGA	40GB	DVD/CD-RW	Wi-Fi/modem	None	10/100	Yes	Windows 2000		Feb 2002
Positioning Processor	Best blend of portability and essential features; two-spindle system												
L2 cache	Intel® Mobile Celeron™ 1.06GHz with 133MHz Front Side Bus or Intel Mobile Pentium® III-M 1.0 or 1.13GHz with Speedstep™ technology ¹ with 133MHz Front Side Bus												
Memory	Celeron: 256KB / at processor speed; Pentium III: 512 KB / at processor speed 128MB ⁹ standard / 1GB maximum / SDRAM / non-parity / 133MHz / PC133 / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available												
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive												
CD-ROM	Some: CD-ROM / 24X-10X ⁹ speed / bootable / removable												
CD-RW	Some: CD-RW / 8X/4X/24X Max ⁹ / removable												
DVD-ROM	Some: DVD-ROM / 8X-3.3X ⁹ speed / removable												
DVD-ROM/CD-RW	Some: DVD-ROM/CD-RW combo / 8X/8X/24X/8X ²¹ speed / removable												
Ultrabay 2000	One modular bay for interchangeable devices (right side) / Ultrabay™ Plus-compatible												
Disk	20, 30, or 40GB ⁸ (4200 rpm) / upgradeable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay												
Display	Some: 13.3" (337.8mm) XGA (1024x768) TFT color / Active Matrix Some: 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix												
Graphics controller	Intel 830MG Integrated Direct AGP 3D / Unified Memory Architecture / in GMCH / controller dynamically allocates 8 to 32MB ¹¹ of system memory for graphics												
Graphics - external	External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200												
Keyboard	87-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar ¹³ / pitch: 19mm; stroke: 2.7mm												
ThinkLight™ UltraPort™	Illuminates the keyboard to improve visibility in low-light conditions None												
Dimensions ³	12.3" x 10.0" x 1.42" / 313mm x 254mm x 36mm												
Approximate weight ²	w/ battery and: CD-ROM: 5.8 lbs; DVD: 5.8 lbs; CD-RW with 13.3": 6.0 lbs; CD-RW with 14.1": 6.1 lbs; DVD/CD-RW: 6.1 lbs												
Case material	Color: black; All: ABS plastic												
Battery - type	Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus												
Battery - life ¹⁰	Celeron models: 2.4 to 2.6 hrs; Pentium III models: 2.9 to 3.1 hrs												
Architecture	Intel 830MG chipset / 82830MG Graphics Memory Controller Hub (GMCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100/66 EIDE, PCI bus, USB, Low Pin Count bus, ethernet, AC-Link) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus, Mini PCI) / Firmware Hub / LPC bus 33MHz (NS PC87392VJG Super I/O for parallel, infrared)												
Port Replicator	Optional ThinkPad Port Replicator (no ThinkPad Dock support)												
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video												
Ports	Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port												
Video out	S-video out port (TV out) / one industry standard connector												
Mini PCI	One Mini PCI type III slot (Communications Bay) / not customer upgradeable												
Wi-Fi ³² /modem	Some: Mini PCI Wi-Fi ³² wireless ⁴ , Intersil® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K ⁶ V.90 (V.92-designed ²⁹) modem combo, Lucent® chipset												
CDC Modem	One Communications Daughter Card (CDC) socket (open or modem) / not accessible Some: 56K ⁶ V.90 (V.92-designed ²⁹) CDC modem card / Lucent® chip set												
Bluetooth™	None												
Ethernet	10/100 ethernet on planar / Intel® 82562ET chipset												
Audio support	Soft audio / SoundBlaster-compatible / Analog Devices AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm)												
Security	Power-on password / hard disk password / supervisor password / security keyhole Some: IBM Embedded Security Subsystem ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶												
Limited warranty ¹²	1 year - EasyServ™.19 onsite pickup and delivery / service upgrades ²² available												
64 MB SO DIMM	133MHz NP SDRAM	19K4650	USB Portable Diskette Drive	05K9276	Universal 72 watt AC adapter								
128 MB SO DIMM	133MHz NP SDRAM	19K4652	ThinkPad Removable Diskette Drive	08K9603	PC 2001-compliant								
256 MB SO DIMM	133MHz NP SDRAM	19K4654	ThinkPad R30/R31 Li-Ion Battery	02K6821	CIM and DMI 2.0-compliant								
512 MB SO DIMM	133MHz NP SDRAM	19K4656	ThinkPad 72W AC Adapter	02K6699	IBM ImageUltra Services available								
IBM 32MB USB Memory Key		22P5296	ThinkPad Port Replicator	02K8667	IBM Rapid Restore PC available to protect software image and data								
SuperDisk (LS-240) UltraBay 2000		08K9616	Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)	19K4480	Personalized Web-based support ³¹								
Zip 250MB Ultrabay 2000 Drive		00N8253	20GB Hard Disk 9.5mm (4200 rpm)	08K9686	Setup Guide, Service and Troubleshooting Guide, Windows manual								
24X-10X CD-ROM Ultrabay 2000 Drive		05K9233	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816	International Warranty Service ¹⁷								
8X/4X/24X Max CD-RW Ultrabay 2000		22P9101	60GB HS Hard Disk 12.5mm (5400 rpm)	08K9688	24 hour x 7 day ¹⁸ toll-free hardware support during the warranty ¹²								
Ultralight 8X Max DVD Ultrabay 2000		22P9102	ServicePac ²¹ 1yr IOR 9x5 NBD	30L9188									
CD-RW/DVD Combo III Ultrabay 2000		22P6980	ServicePac 2yr IOR 9x5 NBD	30L9189									
Second HDD Adapter for Ultrabay 2000		08K6068	ServicePac 3yr IOR 9x5 NBD	30L9195									
IBM ThinkPad Ultrabay Plus Carrier		22P5737	ServicePac 2yr P&L P/U Depot	30L9191									
IBM ThinkPad Ultrabay Plus c500 Cradle		22P5738	ServicePac 3yr P&L P/U Dmpot	30L9192									
ThinkPad Ultrabay Plus Numeric Keypad		22P7330											
Other options at ibm.com/pc/us/accessories													

See footnotes for important warranty information
US models announced January 22 or March 19, 2002
US models withdrawn effective July 2002 or January 2003

Type-model	Processor	Speed	Memory ¹¹	Screen	Disk	Optical	Mini PCI Comm Bay	Ethernet on planar	Security Chip	Preload	Limited warranty	Avail date
2656-99U	Pentium® III-M	1.06	128MB	13.3" XGA	20GB ⁸ CD-RW	CD-RW	Wi-Fi ³² /modem	None	10/100	No	Windows® XP Pro	1 yr Apr 2002
2656-88U	Pentium III-M	1.06	128MB	14.1" XGA	30GB DVD/CD-RW	CD-RW	Wi-Fi/modem	None	10/100	No	Windows XP Pro	1 yr Apr 2002
2656-77U	Pentium III-M	1.06	128MB	14.1" XGA	20GB CD-RW	CD-RW	Wi-Fi/modem	None	10/100	No	Windows XP Pro	1 yr Aug 2002
2657-99U	Pentium III-M	1.06	128MB	13.3" XGA	20GB CD-RW	CD-RW	Wi-Fi/modem	None	10/100	No	Windows XP Pro	3 yr Apr 2002
2657-88U	Pentium III-M	1.06	128MB	14.1" XGA	30GB DVD/CD-RW	CD-RW	Wi-Fi/modem	None	10/100	No	Windows XP Pro	3 yr Apr 2002
2657-77U	Pentium III-M	1.06	128MB	14.1" XGA	20GB CD-RW	CD-RW	Wi-Fi/modem	None	10/100	No	Windows XP Pro	3 yr Aug 2002

These educational models of the ThinkPad R31 notebook must be sold only to qualified education customers. Qualified institution/customer is a public or private K-12 (or higher) accredited school organized and operated exclusively for educational purposes for use by Qualified Students and/or Qualified Teachers.

This model for education is for sale direct from IBM or through an Authorized Education Reseller. The model or models for education are not available for resale to any other organization or individual.

Positioning Processor	<i>Best blend of portability and essential features; two-spindle system</i> Intel® Mobile Pentium® III-M 1.06GHz with Speedstep™ technology ¹ with 133MHz frontside bus							SOFTWARE¹⁴				
L2 cache	512 KB / at processor speed / ECC							Windows XP Pro models				
Memory	128MB standard / 1GB max ⁷ / SDRAM / non-parity / 133MHz / PC133-compliant / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available							- Microsoft® Windows® XP Professional ²⁰ ↔ Disk-to-Disk Recovery (in hidden Service Partition)				
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive							INCLUDED SOFTWARE¹⁴ (all)				
CD-RW	<i>Some:</i> CD-RW / 8X/4X/24X Max ⁹ / removable							Preloaded				
DVD-ROM/CD-RW	<i>Some:</i> DVD-ROM/CD-RW combo / 8X/8X/24X/8X ²¹ speed / removable							• Access ThinkPad				
Ultrabay 2000	One modular bay for interchangeable devices (right side) / Ultrabay™ Plus -compatible							- Access Connections				
Disk	20 or 30GB⁸ (4200 rpm) / upgradeable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay							- Access Help				
Display	<i>Some:</i> 13.3" (337.8mm) XGA (1024x768) TFT color / Active Matrix							- Access Support				
	<i>Some:</i> 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix							• Adobe® Acrobat				
Graphics controller	Intel 830MG Integrated Direct AGP 3D / Unified Memory Architecture / in GMCH / controller dynamically allocates 8 to 32MB ¹¹ of system memory for graphics							• InterVideo WinDVD (DVD models)				
Graphics - external	External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200							• Norton AntiVirus				
Keyboard	87-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar ¹³ / pitch: 19mm; stroke: 2.7mm							• PC-Doctor™				
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions							• ThinkPad Utilities				
UltraPort™	None							• IBM Update Connector™ ¹⁵				
Dimensions ³	12.3" x 10.0" x 1.42" / 313mm x 254mm x 36mm							• Veritas RecordNOW				
Approximate weight ²	w/ battery and: 13.3" TFT: 6.0 lbs (2.7kg); 14.1" TFT: 6.1 lbs (2.7kg)							Downloadable				
Case material	<i>Color:</i> black; <i>All:</i> ABS plastic							• IBM Rapid Restore™ PC				
Battery - type	Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus							• IBM Data Transfer				
Battery - life ¹⁰	2.9 hrs							• IBM Director Agen				
Architecture	Intel 830MG chipset / 82830MG Graphics Memory Controller Hub (GMCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100/66 EIDE, PCI bus, USB, Low Pin Count bus, ethernet, AC-Link) / PCI bus 2.2 32-bit, 33MHz (TI® PCI11410A CardBus, Mini PCI) / Firmware Hub / LPC bus 33MHz (NS PC87392VJG Super I/O for parallel, infrared)							License				
Port Replicator	Optional ThinkPad Port Replicator (no ThinkPad Dock support)							- Lotus® SmartSuite® Millennium and Lotus Notes® Client 5.0				
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video											
Ports	Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port											
Video out	S-video out port (TV out) / one industry standard connector											
Mini PCI	One Mini PCI type III slot (Communications Bay) / not customer upgradeable											
Wi-Fi ³² /modem	Mini PCI Wi-Fi ³² wireless ⁴ , Intersil® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K ⁶ V.90 (V.92-designed ²⁹) modem combo, Lucent® chipset											
CDC	One Communications Daughter Card (CDC) socket / not accessible											
Open	One Communications Daughter Card (CDC) socket open											
Ethernet	10/100 ethernet on planar / Intel® 82562ET chipset (physical layer)							Ultrabay Plus integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad™ c500 Series				
Audio support	Soft audio / SoundBlaster-compatible / Analog Devices AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm)											
Security	Power-on password / hard disk password / supervisor password / security keyhole											
Limited warranty ¹²	2656: 1 year - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² available 2657: 3 years /1 year battery - EasyServ onsite pickup and delivery / service upgrades available											
64 MB SO DIMM	133MHz NP SDRAM	19K4650	USB Portable Diskette Drive	05K9276								
128 MB SO DIMM	133MHz NP SDRAM	19K4652	ThinkPad R30/R31 Li-Ion Battery	02K6821								
256 MB SO DIMM	133MHz NP SDRAM	19K4654	ThinkPad 72W AC Adapter	02K6699								
512 MB SO DIMM	133MHz NP SDRAM	19K4656	ThinkPad Port Replicator	02K8667								
SuperDisk (LS-240)	UltraBay 2000	08K9616	Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)	19K4480								
Zip 250MB	Ultrabay 2000 Drive	00N8253	20GB Hard Disk 9.5mm (4200 rpm)	08K9686								
24X-10X CD-ROM	Ultrabay 2000 Drive	05K9233	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816								
8X/4X/24X Max CD-RW	Ultrabay 2000	22P9101	60GB HS Hard Disk 12.5mm (5400 rpm)	08K9688								
Ultralight 8X Max DVD	Ultrabay 2000	22P9102	2656: ServicePac ²² 1yr IOR 9x5 NBD	30L9188								
CD-RW/DVD Combo III	Ultrabay 2000	22P6980	2656: ServicePac 2yr IOR 9x5 NBD	30L9189								
Second HDD Adapter for Ultrabay 2000		08K6068	2656: ServicePac 3yr IOR 9x5 NBD	30L9195								
IBM ThinkPad Ultrabay Plus Carrier		22P5737	2656: ServicePac 2yr P&L P/U Depot	30L9191								
IBM ThinkPad Ultrabay Plus c500 Cradle		22P5738	2656: ServicePac 3yr P&L P/U Depot	30L9192								
ThinkPad Ultrabay Plus Numeric Keypad		22P7330	2657: ServicePac 2yr IOR 9x5 NBD	30L9190								
Other options at ibm.com/pc/us/accessories			2657: ServicePac 3yr IOR 9x5 NBD	30L9197								

See footnotes for important warranty information
US models announced April 30 or August 13, 2002
US models withdrawn from marketing effective October 2002 or January 2003

Type-model	Processor	Speed GHz	Memory ¹¹	Screen	Disk GB ⁶	Optical	Mini PCI Comm Bay wireless/modem	CDC modem	Ethernet on planar	IEEE 1394	Preload	Workhorse (W) or Global (G) model	Avail date
2656-2GU	Celeron®	1.13	128MB	13.3" XGA	20GB	CD-ROM	Open	Modem	10/100		Windows® XP Pro	No	Jun 2002
2656-1CU	Celeron	1.13	128MB	14.1" XGA	20GB	CD-ROM	Open	Modem	10/100		Windows XP Pro	No	Jun 2002
2656-2VU	Celeron	1.13	128MB	13.3" XGA	20GB	CD-ROM	Wi-Fi ³² /modem	Open	10/100	1394	Windows XP Pro	No	Jun 2002
2656-1FU	Celeron	1.13	128MB	14.1" XGA	20GB	CD-RW	Open	Modem	10/100		Windows XP Pro	No	Jun 2002
2656-1GU	Celeron	1.13	128MB	14.1" XGA	20GB	DVD	Open	Modem	10/100		Windows XP Home	No	Jun 2002
2656-2HU	Celeron	1.13	128MB	13.3" XGA	20GB	CD-ROM	Open	Modem	10/100		Windows XP Home	No	Jun 2002
2656-1BU	Celeron	1.13	128MB	14.1" XGA	20GB	CD-ROM	Open	Modem	10/100		Windows XP Home	No	Aug 2002

Positioning	<i>Best blend of portability and essential features; two-spindle system</i>										SOFTWARE¹⁴		
Processor	Intel® Mobile Celeron® 1.13GHz with 133MHz frontside bus										Windows XP Home models		
L2 cache	256KB / at processor speed / ECC										- Microsoft® Windows® XP Home ²⁰		
Memory	128MB standard / 1GB max⁷ / SDRAM / non-parity / 133MHz / PC133 / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available										↳ Disk-to-Disk Recovery (in hidden Service Partition)		
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive										Windows XP Pro models		
CD-ROM	<i>Some: CD-ROM / 24X-10X⁹ speed / removable from Ultrabay 2000</i>										- Microsoft® Windows® XP Professional ²⁰		
CD-RW	<i>Some: CD-RW / 8X/4X/24X Max⁹ / removable from Ultrabay 2000</i>										↳ Disk-to-Disk Recovery (in hidden Service Partition)		
DVD-ROM	<i>Some: DVD-ROM / 8X-3.3X Max⁹ / removable from Ultrabay 2000</i>												
Ultrabay 2000	One modular bay for interchangeable devices (right side) / Ultrabay™ Plus-compatible												
Disk	20GB⁹ (4200 rpm) / upgradeable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay												
Display	<i>Some: 13.3" (337.8mm) XGA (1024x768) TFT color / Active Matrix</i> <i>Some: 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix</i>										INCLUDED SOFTWARE¹⁴ (all)		
Graphics controller	Intel 830MG Integrated Direct AGP 3D / Unified Memory Architecture / in GMCH / controller dynamically allocates 8 to 32MB¹¹ of system memory for graphics										Preloaded		
Graphics - external	External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200										• Access ThinkPad		
Keyboard	87-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar ¹³ / pitch: 19mm; stroke: 2.7mm										- Access Connections		
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions										- Access Help		
UltraPort™	None										- Access Support		
Dimensions ³	12.3" x 10.0" x 1.42" / 313mm x 254mm x 36mm										• Adobe® Acrobat Reader		
Approximate weight ²	w/ battery and: <i>CD-ROM: 5.8lb (2.62kg); DVD: 5.75lb (2.61kg); CD-RW: 6.05lb (2.73kg)</i>										• InterVideo WinDVD (DVD models)		
Case material	<i>Color: black; All: ABS plastic</i>										• Norton AntiVirus		
Battery - type	Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus										• PC-Doctor™		
Battery - life ¹⁰	<i>2VU: 2.4 hrs; Others: 2.6 hrs</i>										• ThinkPad Utilities		
Architecture	Intel 830MG chipset / 82830MG Graphics Memory Controller Hub (GMCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100/66 EIDE, PCI bus, USB, Low Pin Count bus, ethernet, AC-Link) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus, Mini PCI, TI TSB43AB22 IEEE 1394) / Firmware Hub / LPC bus 33MHz (NS PC87392VJG Super I/O for parallel, infrared)										• IBM Update Connector™ ¹⁵		
Port Replicator	Optional ThinkPad Port Replicator (no ThinkPad Dock support)										• Veritas RecordNOW (CD-RW mod)		
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video										Downloadable		
Ports	Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / IEEE 1394 (4-pin) / no keyboard or mouse or serial port										• IBM Rapid Restore™ PC		
Video out	S-video out port (TV out) / one industry standard connector										• IBM Data Transfer		
IEEE 1394 (FireWire)	<i>Some: IEEE 1394 (FireWire) Port (4-pin)</i>										• IBM Director Agent		
Mini PCI	One Mini PCI type III slot (Communications Bay) / not customer upgradeable										License (CD not included)		
Wi-Fi ³² /modem	<i>Some: Mini PCI Wi-Fi³² wireless⁴, Intersil® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K⁶ V.90 (V.92-designed²⁹) modem combo, Lucent® chipset</i>										- Lotus® SmartSuite® Millennium and Lotus Notes® Stand Alone Client		
CDC Modem	One Communications Daughter Card (CDC) socket (open or modem) / not accessible										Ultrabay Plus integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series		
Ethernet	<i>Some: 56K⁶ V.90 (V.92-designed²⁹) CDC modem card / Lucent® chip set</i>												
Audio support	Soft audio / SoundBlaster-compatible / Analog Devices AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm)												
Security	Power-on password / hard disk password / supervisor password / security keyhole												
Limited warranty ¹²	1 year - EasyServ™¹⁹ onsite pickup and delivery / service upgrades²² available												
64 MB SO DIMM	133MHz NP SDRAM	19K4650	IBM USB Portable Diskette Drive						05K9276				
128 MB SO DIMM	133MHz NP SDRAM	19K4652	IBM 128MB USB 2.0 Memory Key						22P8998				
256 MB SO DIMM	133MHz NP SDRAM	19K4654	TrackPoint Cap Collection						73P2698				
512 MB SO DIMM	133MHz NP SDRAM	19K4656	IBM USB 2.0 Portable CD-RW Drive						22P5297				
SuperDisk (LS-240)	UltraBay 2000	08K9616	IBM ThinkPad USB 2.0 CardBus Adapter						33L3245				
Zip 250MB	Ultrabay 2000 Drive	00N8253	IBM USB Serial Parallel Adapter						22P5298				
24X-10X CD-ROM	Ultrabay 2000 Drive	05K9233	ThinkPad R30 Series Li-Ion Battery						02K6821				
8X/4X/24X Max CD-RW	Ultrabay 2000	22P9101	ThinkPad T2W AC Adapter						02K6699				
Ultralight 8X Max DVD	Ultrabay 2000	22P9102	20GB Hard Disk 9.5mm (4200 rpm)						08K9686				
CD-RW/DVD Combo III	Ultrabay 2000	22P6980	40GB HS Hard Disk 9.5mm (5400 rpm)						08K9816				
Second HDD Adapter for Ultrabay 2000		08K6068	60GB HS Hard Disk 12.5mm (5400 rpm)						08K9688				
IBM ThinkPad Ultrabay Plus Carrier		22P5737	ServicePac® ²² 1yr IOR 9x5 NBD						30L9188				
IBM ThinkPad Ultrabay Plus c500 Cradle		22P5738	ServicePac 2yr IOR 9x5 NBD						30L9189				
ThinkPad Ultrabay Plus Numeric Keypad		22P7330	ServicePac 3yr IOR 9x5 NBD						30L9195				
Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)		19K4480	ServicePac 2yr P&L P/U Depot						30L9191				
ThinkPad Port Replicator		02K8667	ServicePac 3yr P&L P/U Depot						30L9192				
			Other options at ibm.com/pc/us/accessories										

See footnotes for important warranty information
US models announced June 4 or August 13, 2002
US models withdrawn from marketing effective October 2002 or January 2003

Type-model	Processor	GHz	Memory ¹¹	Screen	Disk	Optical	Mini PCI Comm Bay	CDC Modem	Ethernet on planar	Security Chip	Preload	Workhorse (W) or Global (G) model	Avail date
2657-LLU	Pentium® III-M	1.00	128MB	14.1" XGA	20GB ⁸ DVD-ROM	DVD-ROM	Open	Modem	10/100	No	Windows® 2000		Mar 2002
2657-MMU	Pentium III-M	1.00	128MB	14.1" XGA	20GB DVD-ROM	DVD-ROM	Open	Modem	10/100	No	Windows XP Pro		Mar 2002
2657-E4U	Pentium III-M	1.13	128MB	14.1" XGA	30GB DVD-ROM	DVD-ROM	Open	Modem	10/100	No	Windows 2000	W G	Mar 2002
2657-J1U	Pentium III-M	1.13	256MB	14.1" XGA	30GB DVD-ROM	DVD-ROM	Open	Modem	10/100	No	Windows 2000	W G	Mar 2002
2657-E5U	Pentium III-M	1.13	128MB	14.1" XGA	30GB DVD-ROM	DVD-ROM	Open	Modem	10/100	No	Windows XP Pro	W G	Mar 2002
2657-J2U	Pentium III-M	1.13	256MB	14.1" XGA	30GB DVD-ROM	DVD-ROM	Open	Modem	10/100	No	Windows XP Pro	W G	Mar 2002

2657 models have a 3 year limited warranty (other 2656 ThinkPad R31 systems have a 1 year limited warranty)

Positioning Processor	Best blend of portability and essential features; two-spindle system Intel® Mobile Pentium® III Processor-M 1.0 or 1.13GHz with Speedstep™ technology ¹ with 133MHz Front Side Bus										SOFTWARE¹⁴		
L2 cache	512 KB / at processor speed										Windows XP Pro models		
Memory	128MB or 256MB standard / 1GB maximum ⁷ / SDRAM / non-parity / 133MHz / PC133 / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available										- Microsoft® Windows® XP Professional ²⁰ ◆ Disk-to-Disk Recovery (in hidden Service Partition)		
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive										Windows 2000 models		
DVD-ROM	DVD-ROM / 8X-3.3X ⁹ speed / removable										- Windows Windows 2000 Professional ²⁰		
Ultrabay 2000	One modular bay for interchangeable devices (right side) / Ultrabay™ Plus -compatible										- ConfigSafe®		
Disk	20, 30, or 40GB ⁸ (4200 rpm) / upgradable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay										◆ Disk-to-Disk Recovery (in hidden Service Partition)		
Display	14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix										INCLUDED SOFTWARE¹⁴ (all)		
Graphics controller	Intel 830MG Integrated Direct AGP 3D / Unified Memory Architecture / in GMCH / controller dynamically allocates 8 to 32MB ¹¹ of system memory for graphics										Preloaded		
Graphics - external	External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200										• Access ThinkPad		
Keyboard	87-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar ¹³ / pitch: 19mm; stroke: 2.7mm										- Access Connections		
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions										- Access Help		
UltraPort™	None										- Access Support		
Dimensions ³	12.3" x 10.0" x 1.42" / 313mm x 254mm x 36mm										• Adobe® Acrobat		
Approximate weight ²	w/ battery and DVD: 5.8 lbs (2.6 kg)										• InterVideo WinDVD (DVD models)		
Case material	Color: black; All: ABS plastic										• Norton AntiVirus		
Battery - type	Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus										• PC-Doctor™		
Battery - life ¹⁰	3.1 hrs										• ThinkPad Utilities		
Architecture	Intel 830MG chipset / 82830MG Graphics Memory Controller Hub (GMCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100/66 EIDE, PCI bus, USB, Low Pin Count bus, ethernet, AC-Link) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus, Mini PCI) / Firmware Hub / LPC bus 33MHz (NS PC87392VJG Super I/O for parallel, infrared)										• IBM Update Connector™ ¹⁵		
Port Replicator	Optional ThinkPad Port Replicator (no ThinkPad Dock support)										• Veritas RecordNOW (CD-RW mod)		
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1										Downloadable		
Ports	Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port										• IBM Rapid Restore™ PC		
Video out	S-video out port (TV out) / one industry standard connector										• IBM Data Transfer		
Mini PCI	One Mini PCI type III slot (Communications Bay) / not customer upgradable										• IBM Director Agent		
Wi-Fi ²² wireless	None										• IBM Client Security Software (for security chip)		
CDC	One Communications Daughter Card (CDC) socket / not accessible										License		
Modem	56K ⁶ V.90 (V.92-designed ²⁹) CDC modem card / Lucent® chip set										- Lotus® SmartSuite® Millennium and Lotus Notes® Client 5.0		
Bluetooth™	None										Ultrabay Plus integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series		
Ethernet	10/100 ethernet on planar / Intel® 82562ET chipset												
Audio support	Soft audio / SoundBlaster-compatible / Analog Devices AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm)												
Security	Power-on password / hard disk password / supervisor password / security keyhole												
Limited warranty ¹²	3 years/1 year battery - EasyServ™ ¹⁹ onsite pickup and delivery												
Service options	Service upgrades ²² provide up to five years of onsite or depot repair service coverage from date of ThinkPad purchase (including warranty period)												

64 MB SO DIMM	133MHz NP SDRAM	19K4650	USB Portable Diskette Drive	05K9276	Universal 72 watt AC adapter
128 MB SO DIMM	133MHz NP SDRAM	19K4652	ThinkPad Removable Diskette Drive	08K9603	PC 2001-compliant
256 MB SO DIMM	133MHz NP SDRAM	19K4654	ThinkPad R30/R31 Li-Ion Battery	02K6821	CIM and DMI 2.0-compliant
512 MB SO DIMM	133MHz NP SDRAM	19K4656	ThinkPad 72W AC Adapter	02K6699	IBM ImageUltra™ Services available
IBM 32MB USB Memory Key		22P5296	ThinkPad Port Replicator	02K8667	IBM Rapid Restore PC available to protect software image and data
SuperDisk (LS-240) UltraBay 2000		08K9616	Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)	19K4480	Personalized Web-based support ³¹
Zip 250MB Ultrabay 2000 Drive		00N8253	20GB Hard Disk 9.5mm (4200 rpm)	08K9686	Setup Guide, Service and Troubleshooting Guide, Windows manual
24X-10X CD-ROM Ultrabay 2000 Drive		05K9233	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816	International Warranty Service ¹⁷
8X/4X/24X Max CD-RW Ultrabay 2000		22P9101	60GB HS Hard Disk 12.5mm (5400 rpm)	08K9688	24 hour x 7 day ¹⁸ toll-free hardware support during the warranty ¹²
Ultralight 8X Max DVD Ultrabay 2000		22P9102	IBM USB 2.0 Portable CD-RW Drive	22P5297	
CD-RW/DVD Combo III Ultrabay 2000		22P6980	ThinkPad Portable 20GB Hard Disk Drive	10K0177	
Second HDD Adapter for Ultrabay 2000		08K6068	IBM 1GB Microdrive	07N5574	
IBM ThinkPad Ultrabay Plus Carrier		22P5737	IBM Optical 3-Button Travel Wheel Mouse	31P7410	
IBM ThinkPad Ultrabay Plus c500 Cradle		22P5738	ServicePac®, 22 2yr IOR 9x5 NBD	30L9190	
ThinkPad Ultrabay Plus Numeric Keypad		22P7330	ServicePac 3yr IOR 9x5 NBD	30L9197	
Other options at ibm.com/pc/us/accessories					

See footnotes for important warranty information
US models announced March 5 or 19, 2002
US models withdrawn effective January 2003 or April 2003

Type-model	Processor	Speed GHz	Memory ¹¹	Screen	Disk GB ⁹	Optical in Ultrabay 2000	Mini PCI Comm Bay wireless/modem	CDC modem	Ethernet on planar	IEEE 1394	Preload	Workhorse (W) or Global (G) model	Avail date
2656-L2U	Celeron®	1.2	128MB	13.3" XGA	20GB	CD-ROM	Open	Modem	10/100	1394	Windows® XP Pro	No	Sep 2002
2656-L6U	Celeron	1.2	128MB	13.3" XGA	20GB	CD-ROM	Wi-Fi ³² /modem	Modem	10/100		Windows XP Pro	No	Sep 2002
2656-M2U	Celeron	1.2	128MB	14.1" XGA	20GB	CD-ROM	Open	Modem	10/100		Windows XP Pro	No	Sep 2002
2656-NYU	Celeron	1.2	128MB	14.1" XGA	20GB	Combo III	Open	Modem	10/100		Windows XP Pro	No	Sep 2002
2656-L1U	Celeron	1.2	128MB	13.3" XGA	20GB	CD-ROM	Open	Modem	10/100		Windows XP Home	No	Sep 2002
2656-LBU	Celeron	1.2	256MB	14.1" XGA	30GB	None (open)	Open	Modem	10/100		Windows XP Home	No	Sep 2002
2656-NAU	Celeron	1.2	128MB	14.1" XGA	20GB	DVD	Open	Modem	10/100		Windows XP Home	No	Sep 2002
Positioning Processor	<i>Best blend of portability and essential features; two-spindle system</i>												
L2 cache	Intel® Mobile Celeron® 1.20GHz with 133MHz frontside bus												
Memory	256KB / at processor speed / ECC 128MB or 256MB standard / 1GB max ⁷ / SDRAM / non-parity / 133MHz / PC133 / 3.3v / two 144-pin SO-DIMM sockets / std mem in one socket / one socket available												
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive												
CD-ROM	<i>Some:</i> CD-ROM / 24X-10X ⁹ speed / removable from Ultrabay 2000												
Combo	<i>Some:</i> DVD-ROM/CD-RW Combo III / 16X/10X/24X/8X ²¹ / removable from Ultrabay 2000												
DVD-ROM	<i>Some:</i> DVD-ROM / 8X-3.3X Max ⁹ / removable from Ultrabay 2000												
Ultrabay 2000	One modular bay for interchangeable devices (right side) / Ultrabay™ Plus -compatible												
Disk	20GB⁸ (4200 rpm) or 30GB (4200 rpm) / upgradable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay												
Display	<i>Some:</i> 13.3" (337.8mm) XGA (1024x768) TFT color / Active Matrix <i>Some:</i> 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix												
Graphics controller	Intel 830MG Integrated Direct AGP 3D / Unified Memory Architecture / in GMCH / controller dynamically allocates 8 to 32MB ¹¹ of system memory for graphics												
Graphics - external	External SVGA to various modes such as 16.7 million colors, 85Hz, or 1600x1200												
Keyboard	87-key / ThinkPad Button / palm rest / TrackPoint®, "Press-to-Select," Internet Scroll Bar ¹³ / pitch: 19mm; stroke: 2.7mm												
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions / no UltraPort™												
Dimensions ³	12.3" x 10.0" x 1.42" / 313mm x 254mm x 36mm												
Approximate weight ² w/ battery and:	<i>CD-ROM:</i> 5.8 lb (2.62kg); <i>DVD:</i> 5.75 lb (2.61kg); <i>Combo:</i> 6.05 lb (2.73kg); <i>Open LBU:</i> 5.3 lb (2.41kg)												
Case material	<i>Color:</i> black; <i>All:</i> ABS plastic												
Battery - type	Lithium Ion 6-cell / intelligent / no second battery in Ultrabay Plus												
Battery - life ¹⁰	<i>Wireless L6U:</i> 2.4 hrs; <i>Others:</i> 2.6 hrs												
Architecture	Intel 830MG chipset / 82830MG Graphics Memory Controller Hub (GMCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100/66 EIDE, PCI bus, USB, Low Pin Count bus, ethernet, AC-Link) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus, Mini PCI, TI TSB43AB22 IEEE 1394) / Firmware Hub / LPC bus 33MHz (NS PC87392VJG Super I/O for parallel, infrared)												
Port Replicator	Optional ThinkPad Port Replicator (no ThinkPad Dock support)												
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1												
Ports	Two USB (Version 1.1) / parallel / external DB-15 monitor / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / IEEE 1394 (4-pin) / no keyboard or mouse or serial port												
Video out IEEE 1394	S-video out port (TV out) / one industry standard connector <i>Some:</i> IEEE 1394 (FireWire) Port (4-pin)												
Mini PCI	One Mini PCI type III slot (Communications Bay) / not customer upgradable												
Wi-Fi ³² /modem	<i>Some:</i> Mini PCI Wi-Fi ³² wireless ⁴ , Intersil® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K ⁶ V.90 (V.92-designed ²⁹) modem combo, Lucent® chipset												
CDC Modem	One Communications Daughter Card (CDC) socket (open or modem) / not accessible <i>Some:</i> 56K ⁶ V.90 (V.92-designed ²⁹) CDC modem card / Lucent® chip set												
Ethernet	10/100 ethernet on planar / Intel® 82562ET chipset												
Audio support	Soft audio / SoundBlaster-compatible / Analog Devices AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm)												
Security	Power-on password / hard disk password / supervisor password / security keyhole												
Limited warranty ¹²	1 year - EasyServ™-19 onsite pickup and delivery / service upgrades ²² available												
64 MB SO DIMM	133MHz NP SDRAM	19K4650	IBM 128MB USB 2.0 Memory Key	22P8998									
128 MB SO DIMM	133MHz NP SDRAM	19K4652	IBM USB 2.0 Portable CD-RW Drive	22P5297									
256 MB SO DIMM	133MHz NP SDRAM	19K4654	IBM ThinkPad USB 2.0 CardBus Adapter	33L3245									
512 MB SO DIMM	133MHz NP SDRAM	19K4656	IBM USB Serial Parallel Adapter	22P5298									
ThinkPad Removable Diskette Drive		08K9603	ThinkPad R30 Series Li-Ion Battery	02K6821									
Zip 250MB Ultrabay 2000 Drive		00N8253	ThinkPad 72W AC Adapter	02K6699									
24X-10X CD-ROM Ultrabay 2000 Drive		05K9233	20GB Hard Disk Drive	08K9686									
Ultralight 8X Max DVD Ultrabay 2000		22P9102	40GB Hard Disk Drive	08K9687									
CD-RW/DVD Combo III Ultrabay 2000		22P6980	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816									
Second HDD Adapter for Ultrabay 2000		08K6068	60GB HS Hard Disk 12.5mm (5400 rpm)*	08K9688									
IBM ThinkPad Ultrabay Plus Carrier		22P5737	ServicePac®.22 1yr IOR 9x5 NBD	30L9188									
IBM ThinkPad Ultrabay Plus c500 Cradle		22P5738	ServicePac 2yr IOR 9x5 NBD	30L9189									
ThinkPad Ultrabay Plus Numeric Keypad		22P7330	ServicePac 3yr IOR 9x5 NBD	30L9195									
Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)		19K4480	ServicePac 4yr IOR 9x5 NBD	69P9194									
ThinkPad Port Replicator		02K8667	ServicePac 5yr IOR 9x5 NBD	69P9196									
IBM High Rate Wireless LAN PC Card 128		09N9904	ServicePac 2yr P&L P/U Depot	30L9191									
IBM USB Portable Diskette Drive		05K9276	ServicePac 3yr P&L P/U Depot	30L9192									
Other options at ibm.com/pc/us/accessories			ServicePac 4yr P&L P/U Depot	69P9195									
			ServicePac 5yr P&L P/U Depot	69P9197									
SOFTWARE¹⁴													
Windows XP Home models													
- Microsoft® Windows® XP Home ²⁰													
↳ Disk-to-Disk Recovery (in hidden Service Partition)													
Windows XP Pro models													
- Microsoft® Windows® XP Professional ²⁰													
↳ Disk-to-Disk Recovery (in hidden Service Partition)													
INCLUDED SOFTWARE¹⁴ (all)													
Preloaded													
• Access ThinkPad													
- Access Connections													
- Access Help													
- Access Support													
• Adobe® Acrobat Reader													
• InterVideo WinDVD (DVD models)													
• Norton AntiVirus (OEM Edition)													
• PC-Doctor™													
• ThinkPad Utilities													
• IBM Update Connector™.15													
• IBM RecordNOW and DLA by Veritas® (combo models)													
• IBM Rapid Restore™ PC													
Downloadable													
• IBM Director Agent													
• Software Delivery Assistant													
• System Migration Assistant													
License (CD not included)													
- Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client													
Ultrabay Plus integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series													
Universal 72 watt AC adapter													
PC 2001-compliant													
CIM and DMI 2.0-compliant													
ACPI 1.0b and 2.0-compliant													
IBM ImageUltra™ Services available													
IBM Rapid Restore PC available to protect software image and data													
Personalized Web-based support ³¹													
Proactive e-mail updates ³¹													
Setup Guide, Service and Troubleshooting Guide, Windows manual													
International Warranty Service ¹⁷													
24x7 ¹⁸ toll-free support for warranty-related issues during the warranty period ¹²													

See footnotes for important warranty information
US models announced September 17, 2002
US models withdrawn effective April 2003

Type-model	Processor	Speed GHz	Memory	Screen	Disk GB ⁸	Optical	Mini PCI Comm Bay wireless/modem	CDC modem	Ethernet on planar	IEEE 1394 port	Security Chip	Preload software	Small business or Global (G) model	Workhorse (W) or Avail date	
2658-ACU	Pentium® 4-M	1.6	128MB	14.1" XGA	20GB	CD-ROM	Open	Modem	10/100			XP Pro	No	Jun 2002	
2658-ADU	Pentium 4-M	1.6	128MB	14.1" XGA	20GB	CD-RW	Open	Modem	10/100	1394		XP Pro	No	Jun 2002	
2658-AEU	Pentium 4-M	1.6	128MB	14.1" XGA	30GB	Combo	Wi-Fi ³² /modem	None	10/100	1394	Yes	XP Pro	No	Jun 2002	
2658-AFU	Pentium 4-M	1.6	128MB	14.1" XGA	30GB	Combo	Open	Modem	10/100			XP Pro	No	Jun 2002	
2658-CZU	Pentium 4-M	1.8	256MB	14.1" XGA	40GB	Combo	Open	Modem	10/100	1394	Yes	XP Pro	No	Jun 2002	
2658-AGU	Pentium 4-M	1.6	128MB	14.1" XGA	20GB	CD-ROM	Open	Modem	10/100			XP Pro	Office ¹⁸	No	Jun 2002
2658-DAU	Pentium 4-M	1.6	256MB	14.1" XGA	20GB	DVD	Wi-Fi/modem	None	10/100			XP Pro	Office	No	Jun 2002

• Trade Act Agreement (TAA)-compliant models

Positioning TAA-compliant Processor	<i>Best blend of portability and essential features; two-spindle system</i> Trade Act Agreement-compliant Mobile Intel® Pentium® 4 Processor-M 1.6 or 1.8GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz frontside bus										SOFTWARE¹⁴ Windows XP Pro models - Microsoft® Windows® XP Professional ²⁰ ◇ Disk-to-Disk Recovery (in hidden Service Partition)			
L2 cache Memory	512KB / on die (at processor speed) / ECC 128 or 256MB std / 1GB max ⁷ / PC2100 266MHz DDR-SDRAM / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available										Windows 2000 models - Microsoft Windows 2000 Professional ²⁰ - ConfigSafe® ◇ Disk-to-Disk Recovery (in hidden Service Partition)			
Diskette drive CD-ROM CD-RW DVD Combo Ultrabay 2000 Disk	None standard / use optional Ultrabay™-based or USB-based diskette drive <i>Some:</i> CD-ROM / 24X-10X ⁹ speed / bootable / removable from Ultrabay 2000 <i>Some:</i> CD-RW / 8X/4X/24X Max ⁹ / bootable / removable from Ultrabay 2000 <i>Some:</i> DVD-ROM / 8X-3.3X ⁹ speed / bootable / removable from Ultrabay 2000 <i>Some:</i> DVD-ROM/CD-RW / 8X/8X/24X/8X ²¹ speed / removable from Ultrabay 2000 One modular bay for interchangeable devices (right side) / Ultrabay Plus -compatible 20GB⁸, 30GB, or 40GB / 4200 rpm / upgradeable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay 2000										INCLUDED SOFTWARE¹⁴ (all) Preloaded • Access ThinkPad - Access Connections - Access Help - Access Support • Adobe Acrobat Reader • InterVideo WinDVD (DVD models) • Norton AntiVirus (OEM edition) • PC-Doctor™ • ThinkPad Utilities • Veritas RecordNOW (CD-RW mod) • IBM Update Connector™. ¹⁵			
Display	14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits / Easy-open cover to unlatch and open with one hand										Downloadable • IBM Rapid Restore™ PC • IBM Data Transfer • IBM Director Agent • Client Security Software (security chip models) License (CD not included) - Lotus® SmartSuite® Millennium and Lotus Notes® Stand Alone Client			
Graphics controller Graphics - external	ATI® Mobility™ Radeon™ 7000 / AGP 4X / 16MB DDR-SDRAM External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B										Office XP Small Business model only (2658-AGU/DAU) - Microsoft Office XP Small Business ²⁸ (Word, Excel, Outlook, Publisher, Small Business Tools) ◇ Office XP Small Business CD			
Keyboard TrackPoint® ThinkLight™	87-key / ThinkPad Button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys) TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass Illuminates the keyboard to improve visibility in low-light conditions / no UltraPort™													
Dimensions ³ Approximate weight ² Case material Battery - type Battery - life ¹⁰	12.3" x 10.0" x 1.5"; 313mm x 254mm x 38mm with optical drive and battery: 5.9 to 6.2 lbs (2.6 to 2.7 kg) depending on model <i>Color:</i> black; <i>All:</i> ABS plastic Lithium Ion 8-cell / intelligent / supports unique 2nd battery in Ultrabay 2000 <i>Wireless models:</i> 3.0 hrs; <i>Others:</i> 3.1 hrs													
Architecture	Intel 845MP chipset / 82845MP Memory Controller Hub (MCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB, Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (TI®) PCI1410A CardBus controller, TSB43AB21 1394 (some), Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared)													
Port Replicator PC Card Std slots Ports	Optional ThinkPad Port Replicator (no ThinkPad Dock support) One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / no Zoomed Video Two USB (Version 1.1) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port													
Video out IEEE 1394 (FireWire) Mini PCI Wi-Fi ³² /modem	S-video out port (TV out) / one industry standard connector <i>Some:</i> IEEE 1394 (FireWire) port / 4-pin connector One Mini PCI type III slot (Communications Bay) / customer upgradeable ^{4,36} <i>Some:</i> Mini PCI Wi-Fi ³² wireless ⁴ , Intersil® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K ⁶ V.90 (V.92-designed ²⁹) modem combo, Agere® chipset													
CDC Modem Ethernet Audio support	One Communications Daughter Card (CDC) socket (open or modem) / not accessible <i>Some:</i> 56K ⁶ V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset 10/100 ethernet on motherboard / Intel 82562ET chipset (physical layer) Soft audio / ICH AC97 controller / SoundBlaster Pro™-compatible / AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal mic / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack													
Security	Power-on password / hard disk password / supervisor password / security keyhole <i>Some:</i> IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCPA-compliant													
Limited warranty ¹²	1 year - EasyServ™. ¹⁹ onsite pickup and delivery / service upgrades ²² available													
128 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028	ThinkPad Port Replicator	02K8667											
256 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030	Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)	19K4480											
512 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032	ThinkPad R32 Series Li-Ion Battery	02K7052											
IBM ThinkPad Ultrabay Plus Carrier	22P5737	Ultrabay 2000 Li-Ion battery	02K6646											
IBM ThinkPad Ultrabay Plus c500 Cradle	22P5738	ThinkPad 72W AC Adapter	02K6699											
ThinkPad Ultrabay Plus Numeric Keypad	22P7330	ThinkPad 72W DC Auto Adapter	10K3820											
Travel Bezel for Ultrabay 2000	08K6070	Multiple Li-Ion/NiMH Battery Charger	02K6719											
Zip 250MB Ultrabay 2000 Drive	00N8253	20GB Hard Disk 9.5mm (4200 rpm)	08K9686											
24X-10X CD-ROM Ultrabay 2000 Drive	05K9233	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816											
Ultralight 8X Max DVD Ultrabay 2000	22P9102	60GB HS Hard Disk 12.5mm (5400 rpm)	08K9688											
CD-RW/DVD Combo III Ultrabay 2000	22P6980	IBM 128MB USB 2.0 Memory Key	22P8998											
Second HDD Adapter for Ultrabay 2000	08K6068	TrackPoint Cap Collection	73P2698											
ThinkPad Removable Diskette Drive	08K9603	IBM USB 2.0 Portable CD-RW	22P5297											
ThinkPad Monitor Stand 2001	22P5265	IBM USB 2.0 PC Card	33L3245											
IBM 802.11a PC Card	22P7501	Other options at ibm.com/pc/us/accessories												
													ServicePac®. ²² 1yr IOR 9x5 NBD	30L9188
													ServicePac 2yr IOR 9x5 NBD	30L9189
													ServicePac 3yr IOR 9x5 NBD	30L9195
													ServicePac 2yr P&L P/U Depot	30L9191
													ServicePac 3yr P&L P/U Depot	30L9192

See footnotes for important warranty information
US models announced June 4, 2002
US models withdrawn effective January 2003

Type-model	Processor	Speed GHz	Memory	Screen	Disk GB ⁸	Optical	Mini PCI Comm Bay wireless/modem	CDC modem	Ethernet on planar	IEEE 1394 port	Security Chip	Preload business or software	Small Workhorse (W) or Global (G) model	Avail date
2658-A5U	Pentium® 4-M	1.6	128MB	14.1" XGA	20GB	CD-ROM	Open	Modem	10/100		XP Pro		Jun 2002	
2658-A6U	Pentium 4-M	1.6	128MB	14.1" XGA	20GB	CD-RW	Open	Modem	10/100	1394	XP Pro		Jun 2002	
2658-A7U	Pentium 4-M	1.6	128MB	14.1" XGA	30GB	Combo	11b Wi-Fi ³² /mod	None	10/100	1394	Yes	XP Pro	Jun 2002	
2658-A8U	Pentium 4-M	1.6	128MB	14.1" XGA	30GB	Combo	Open	Modem	10/100		XP Pro		Jun 2002	
2658-CSU	Pentium 4-M	1.8	256MB	14.1" XGA	40GB	Combo	Open	Modem	10/100	1394	Yes	XP Pro	Jun 2002	
2658-A9U	Pentium 4-M	1.6	128MB	14.1" XGA	20GB	CD-ROM	Open	Modem	10/100		XP Pro	Office ¹⁸	Jun 2002	
2658-BKU	Pentium 4-M	1.6	256MB	14.1" XGA	20GB	DVD	Open	Modem	10/100		XP Pro	Office	Jun 2002	
2658-BPU	Pentium 4-M	1.6	256MB	14.1" XGA	20GB	DVD	Open	Modem	10/100		XP Pro		W G Jun 2002	
2658-BQU	Pentium 4-M	1.6	256MB	14.1" XGA	20GB	DVD	11b Wi-Fi/mod	None	10/100		Yes	XP Pro	W G Jun 2002	
2658-CFU	Pentium 4-M	1.8	256MB	14.1" XGA	30GB	DVD	Open	Modem	10/100		XP Pro		W G Jun 2002	
2658-CGU	Pentium 4-M	1.8	256MB	14.1" XGA	30GB	DVD	11b Wi-Fi/mod	None	10/100		Yes	XP Pro	W G Jun 2002	
2658-BMU	Pentium 4-M	1.6	256MB	14.1" XGA	20GB	DVD	Open	Modem	10/100		2000		W G Jun 2002	
2658-BNU	Pentium 4-M	1.6	256MB	14.1" XGA	20GB	DVD	11b Wi-Fi/mod	None	10/100		Yes	2000	W G Jun 2002	
Positioning Processor	<i>Best blend of portability and essential features; two-spindle system</i>													
L2 cache	Mobile Intel® Pentium® 4 Processor-M 1.6 or 1.8GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz frontside bus													
Memory	512KB / on die (at processor speed) / ECC 128 or 256MB std / 1GB max ⁷ / PC2100 266MHz DDR-SDRAM / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available											SOFTWARE¹⁴ Windows XP Pro models - Microsoft® Windows® XP Professional ²⁰ ↳ Disk-to-Disk Recovery (in hidden Service Partition) Windows 2000 models - Microsoft Windows 2000 Professional ²⁰ - ConfigSafe® ↳ Disk-to-Disk Recovery (in hidden Service Partition)		
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive													
CD-ROM	<i>Some:</i> CD-ROM / 24X-10X ⁹ speed / bootable / removable from Ultrabay 2000													
CD-RW	<i>Some:</i> CD-RW / 8X/4X/24X Max ⁹ / bootable / removable from Ultrabay 2000													
DVD	<i>Some:</i> DVD-ROM / 8X-3.3X ⁹ speed / bootable / removable from Ultrabay 2000													
Combo	<i>Some:</i> DVD-ROM/CD-RW / 8X/8X/24X/8X ²¹ speed / removable from Ultrabay 2000													
Ultrabay 2000	One modular bay for interchangeable devices (right side) / Ultrabay Plus -compatible													
Disk	20GB⁸, 30GB, or 40GB / 4200 rpm / upgradable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay 2000											INCLUDED SOFTWARE¹⁴ (all) Preloaded • Access ThinkPad - Access Connections - Access Support • Adobe Acrobat Reader • InterVideo WinDVD (DVD models) • Norton AntiVirus (OEM edition) • PC-Doctor™ • ThinkPad Utilities • Veritas RecordNOW (CD-RW mod) • IBM Update Connector™ ¹⁵ Downloadable • IBM Rapid Restore™ PC • IBM Data Transfer • IBM Director Agent • Client Security Software (models with security chip) License (CD not included) - Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client Office XP Small Business model only (2658-A9U/BKU) - Microsoft Office XP Small Business ²⁸ (Word, Excel, Outlook, Publisher, Small Business Tools) ↳ Office XP Small Business CD		
Display	14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits / Easy-open cover to unlatch and open with one hand													
Graphics controller	ATI® Mobility™ RADEON™ 7000 / AGP 4X / 16MB DDR-SDRAM													
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B													
Keyboard	87-key / ThinkPad Button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)													
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass													
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions / no UltraPort™													
Dimensions ³	12.3" x 10.0" x 1.5"; 313mm x 254mm x 38mm													
Approximate weight ²	with optical drive and battery: 5.9 to 6.2 lbs (2.6 to 2.7 kg) depending on model													
Case material	<i>Color:</i> black; <i>All:</i> ABS plastic													
Battery - type	Lithium Ion 8-cell / intelligent / supports unique 2nd battery in Ultrabay 2000													
Battery - life ¹⁰	<i>Wireless models:</i> 3.0 hrs; <i>Others:</i> 3.1 hrs													
Architecture	Intel 845MP chipset / 82845MP Memory Controller Hub (MCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB, Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (TI®) PCI1410A CardBus controller, TSB43AB21 1394 (some), Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared)													
Port Replicator	Optional ThinkPad Port Replicator (no ThinkPad Dock support)													
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1													
Ports	Two USB (Version 1.1) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port													
Video out	S-video out port (TV out) / one industry standard connector													
IEEE 1394 (FireWire)	<i>Some:</i> IEEE 1394 (FireWire) port / 4-pin connector													
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable ^{4,36}													
11b Wi-Fi ³² /mod	<i>Some:</i> Mini PCI 11b Wi-Fi ³² wireless ⁴ , Intersil® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K ⁶ V.90 (V.92-designed ²⁹) modem combo, Agere® chipset													
CDC	One Communications Daughter Card (CDC) socket (open or modem) / not accessible													
Modem	<i>Some:</i> 56K ⁶ V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset													
Ethernet	10/100 ethernet on motherboard / Intel 82562ET chipset (physical layer)													
Audio support	Soft audio / ICH AC97 controller / SoundBlaster Pro™-compatible / AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal mic / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack													
Security	Power-on password / hard disk password / supervisor password / security keyhole <i>Some:</i> IBM Embedded Security Subsystem 2.0³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCPA-compliant													
Limited warranty ¹²	1 year - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² available													
128 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028	ThinkPad Port Replicator	02K8667											
256 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030	Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)	19K4480											
512 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032	ThinkPad R32/R40 Li-Ion Battery	02K7052											
IBM ThinkPad Ultrabay Plus Carrier	22P5737	Ultrabay 2000 Li-Ion battery	02K6646											
IBM ThinkPad Ultrabay Plus c500 Cradle	22P5738	ThinkPad 72W AC Adapter	02K6699											
ThinkPad Ultrabay Plus Numeric Keypad	22P7330	ThinkPad 72W DC Auto Adapter	10K3820											
Travel Bezel for Ultrabay 2000	08K6070	Multiple Li-Ion/NiMH Battery Charger	02K6719											
Zip 250MB Ultrabay 2000 Drive	00N8253	20GB Hard Disk 9.5mm	08K9686											
24X-10X CD-ROM Ultrabay 2000 Drive	05K9233	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816											
Ultralight 8X Max DVD Ultrabay 2000	22P9102	60GB HS Hard Disk 12.5mm (5400 rpm)	08K9688											
CD-RW/DVD Combo III Ultrabay 2000	22P6980	TrackPoint Cap Collection	73P2698											
Second HDD Adapter for Ultrabay 2000	08K6068	Other options at ibm.com/pc/us/accessories												
ThinkPad Removable Diskette Drive	08K9603													

See footnotes for important warranty information
US models announced June 4, 2002
US models withdrawn effective January 2003 or April 2003

Type-model	Processor	Speed GHz	Memory	Screen	Disk GB ⁵	Optical	Mini PCI Comm Bay wireless/modem	CDC modem	Ethernet on planar	IEEE 1394 port	Security Chip	Preload	Workhorse (W) Limited or Global (G) Avail date
2659-BPU	Pentium® 4-M	1.6	256MB	14.1" XGA	20GB	DVD	Open	Modem	10/100	No	No	XP Pro	3 yr W G Jun 2002
2659-BQU	Pentium 4-M	1.6	256MB	14.1" XGA	20GB	DVD	11b Wi-Fi ³² /mod	None	10/100	No	Yes	XP Pro	3 yr W G Jun 2002
2659-CFU	Pentium 4-M	1.8	256MB	14.1" XGA	30GB	DVD	Open	Modem	10/100	No	No	XP Pro	3 yr W G Jun 2002
2659-CGU	Pentium 4-M	1.8	256MB	14.1" XGA	30GB	DVD	11b Wi-Fi/mod	None	10/100	No	Yes	XP Pro	3 yr W G Jun 2002
2659-BMU	Pentium 4-M	1.6	256MB	14.1" XGA	20GB	DVD	Open	Modem	10/100	No	No	2000	3 yr W G Jun 2002
2659-BNU	Pentium 4-M	1.6	256MB	14.1" XGA	20GB	DVD	11b Wi-Fi/mod	None	10/100	No	Yes	2000	3 yr W G Jun 2002

2659 models have a 3 year limited warranty (other 2658 ThinkPad R32 systems have a 1 year limited warranty)

Positioning Processor	Best blend of portability and essential features; two-spindle system Mobile Intel® Pentium® 4 Processor-M 1.6 or 1.8GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz frontside bus										SOFTWARE¹⁴		
L2 cache	512KB / on die (at processor speed) / ECC										Windows XP Pro models		
Memory	128 or 256MB std / 1GB max ⁷ / PC2100 266MHz DDR-SDRAM / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available										- Microsoft® Windows® XP Professional ²⁰ ↔ Disk-to-Disk Recovery (in hidden Service Partition)		
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive										Windows 2000 models		
DVD	DVD-ROM / 8X-3.3X ⁹ speed / bootable / removable from Ultrabay 2000										- Microsoft Windows 2000 Professional ²⁰		
Ultrabay 2000 Disk	One modular bay for interchangeable devices (right side) / Ultrabay Plus -compatible 20GB ⁸ or 30GB / 4200 rpm / upgradable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay 2000										- ConfigSafe® ↔ Disk-to-Disk Recovery (in hidden Service Partition)		
Display	14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits / Easy-open cover to unlatch and open with one hand										INCLUDED SOFTWARE¹⁴ (all)		
Graphics controller	ATI® Mobility™ RADEON™ 7000 / AGP 4X / 16MB DDR-SDRAM										Preloaded		
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B										• Access ThinkPad • Access Connections • Access Help • Access Support		
Keyboard	87-key / ThinkPad Button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)										• Adobe Acrobat Reader		
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass										• InterVideo WinDVD (DVD models)		
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions / no UltraPort™										• Norton AntiVirus (OEM edition)		
Dimensions ³	12.3" x 10.0" x 1.5"; 313mm x 254mm x 38mm										• PC-Doctor™		
Approximate weight ²	with optical drive and battery: 5.9 lbs (2.6kg)										• ThinkPad Utilities		
Case material	Color: black; All: ABS plastic										• Veritas RecordNOW (CD-RW mod)		
Battery - type	Lithium Ion 8-cell / intelligent / supports unique 2nd battery in Ultrabay 2000										• IBM Update Connector™ ¹⁵		
Battery - life ¹⁰	Wireless models: 3.0 hrs; Others: 3.1 hrs										Downloadable		
Architecture	Intel 845MP chipset / 82845MP Memory Controller Hub (MCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB, Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (TI® PCI11410A CardBus controller, Mini PCI, external expansion) / LPC bus 33MHz (security chip (some); PC87392 Super I/O for diskette, parallel, infrared)										• IBM Rapid Restore™ PC		
Port Replicator	Optional ThinkPad Port Replicator (no ThinkPad Dock support)										• IBM Data Transfer		
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1										• IBM Director Agent		
Ports	Two USB (Version 1.1) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port										• Client Security Software (models with security chip)		
Video out	S-video out port (TV out) / one industry standard connector										License (CD not included)		
IEEE 1394	None										- Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client		
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable ^{4,36}										Universal 72 watt AC adapter		
11b Wi-Fi ³² /mod	Some: Mini PCI 11b Wi-Fi ³² wireless ⁴ , Intersil® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K ⁶ V.90 (V.92-designed ²⁹) modem combo, Agere® chipset										Asset ID (system-specific info in chip accessed over network)		
CDC	One Communications Daughter Card (CDC) socket (open or modem) / not accessible										PC 2001-compliant		
Modem	Some: 56K ⁶ V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset										ACPI 1.0b and 2.0-compliant		
Ethernet	10/100 ethernet on motherboard / Intel 82562E Chipset (physical layer)										CIM and DMI 2.0-compliant		
Audio support	Soft audio / ICH AC97 controller / SoundBlaster Pro™-compatible / AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal mic / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack										PXE 2.0-compliant		
Security	Power-on password / hard disk password / supervisor password / security keyhole Some: IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCPA-compliant										IBM ImageUltra™ Services available		
Limited warranty ¹²	3 years/1 year battery - EasyServ™ ¹⁹ onsite pickup and delivery										IBM Rapid Restore PC available to protect software image and data		
Service options	Service upgrades ²² provide up to five years of onsite or depot repair service coverage from date of ThinkPad purchase (including warranty period)										International Warranty Service ¹⁷		
128 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028	ThinkPad Port Replicator	02K8667	256 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030	Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)	19K4480	512 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032	ThinkPad R32/R40 Li-Ion Battery	02K7052	ServicePac®.22 2yr IOR 9x5 NBD	30L9190
IBM ThinkPad Ultrabay Plus Carrier	22P5737	ThinkPad 72W AC Adapter	02K6646	IBM ThinkPad Ultrabay Plus c500 Cradle	22P5738	ThinkPad 72W DC Auto Adapter	10K3820	ThinkPad Ultrabay Plus Numeric Keypad	22P7330	Multiple Li-Ion/NiMH Battery Charger	02K6719	ServicePac 3yr IOR 9x5 NBD	30L9197
Travel Bezel for Ultrabay 2000	08K6070	20GB Hard Disk 9.5mm (4200 rpm)	08K9686	Zip 250MB Ultrabay 2000 Drive	00N8253	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816	24X-10X CD-ROM Ultrabay 2000 Drive	05K9233	60GB HS Hard Disk 12.5mm (5400 rpm)	08K9688		
Ultralight 8X Max DVD Ultrabay 2000	22P9102	IBM 128MB USB 2.0 Memory Key	22P8998	CD-RW/DVD Combo III Ultrabay 2000	22P6980	TrackPoint Cap Collection	73P2698	Second HDD Adapter for Ultrabay 2000	08K6068	Other options at ibm.com/pc/us/accessories			
ThinkPad Removable Diskette Drive	08K9603												

See footnotes for important warranty information

US models announced June 4, 2002

US models withdrawn effective January 2003 or April 2003

(R323) © IBM Corp. March 2003

Type-model	Processor	Speed GHz	Memory	Screen	Disk GB ⁵	Optical	Mini PCI Comm Bay wireless/modem	CDC modem	Ethernet on planar	IEEE 1394 port	Security Chip	Preload	Workhorse (W) Limited or Global (G) Avail date
2659-DPU	Pentium® 4-M	1.6	256MB	14.1" XGA	20GB	DVD	Open	Modem	10/100	No	Yes	XP Pro	3 yr W Jun 2002
2659-DQU	Pentium 4-M	1.6	256MB	14.1" XGA	20GB	DVD	11b Wi-Fi ³² /mod	None	10/100	No	Yes	XP Pro	3 yr W Jun 2002
2659-EFU	Pentium 4-M	1.8	256MB	14.1" XGA	30GB	DVD	Open	Modem	10/100	No	Yes	XP Pro	3 yr W Jun 2002
2659-EGU	Pentium 4-M	1.8	256MB	14.1" XGA	30GB	DVD	11b Wi-Fi/mod	None	10/100	No	Yes	XP Pro	3 yr W Jun 2002
2659-DMU	Pentium 4-M	1.6	256MB	14.1" XGA	20GB	DVD	Open	Modem	10/100	No	Yes	2000	3 yr W Jun 2002
2659-DNU	Pentium 4-M	1.6	256MB	14.1" XGA	20GB	DVD	11b Wi-Fi/mod	None	10/100	No	Yes	2000	3 yr W Jun 2002

- 2659 models have a 3 year limited warranty (other 2658 ThinkPad R32 systems have a 1 year limited warranty)
- Trade Act Agreement (TAA)-compliant models

Positioning TAA-compliant Processor	Best blend of portability and essential features; two-spindle system Trade Act Agreement-compliant Mobile Intel® Pentium® 4 Processor-M 1.6 or 1.8GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz frontside bus		SOFTWARE¹⁴ Windows XP Pro models - Microsoft® Windows® XP Professional ²⁰ ↳ Disk-to-Disk Recovery (in hidden Service Partition)	
L2 cache Memory	512KB / on die (at processor speed) / ECC 128 or 256MB std / 1GB max ⁷ / PC2100 266MHz DDR-SDRAM / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available		Windows 2000 models - Microsoft Windows 2000 Professional ²⁰ - ConfigSafe® ↳ Disk-to-Disk Recovery (in hidden Service Partition)	
Diskette drive DVD Ultrabay 2000 Disk	None standard / use optional Ultrabay™-based or USB-based diskette drive DVD-ROM / 8X-3.3X ⁹ speed / bootable / removable from Ultrabay 2000 One modular bay for interchangeable devices (right side) / Ultrabay Plus-compatible 20GB⁸ or 30GB / 4200 rpm / upgradable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay 2000		INCLUDED SOFTWARE¹⁴ (all) Preloaded • Access ThinkPad - Access Connections - Access Help - Access Support • Adobe Acrobat Reader • InterVideo WinDVD (DVD models) • Norton AntiVirus (OEM edition) • PC-Doctor™ • ThinkPad Utilities • Veritas RecordNOW (CD-RW mod) • IBM Update Connector™ ¹⁵	
Display	14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits / Easy-open cover to unlatch and open with one hand		Downloadable • IBM Rapid Restore™ PC • IBM Data Transfer • IBM Director Agent • Client Security Software (models with security chip)	
Graphics controller Graphics - external	ATI® Mobility™ RADEON™ 7000 / AGP 4X / 16MB DDR-SDRAM External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B		License (CD not included) - Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client	
Keyboard TrackPoint® ThinkLight™	87-key / ThinkPad Button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys) TrackPoint® pointing device; "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass Illuminates the keyboard to improve visibility in low-light conditions / no UltraPort™		Universal 72 watt AC adapter Asset ID (system-specific info in chip accessed over network) PC 2001-compliant ACPI 1.0b and 2.0-compliant CIM and DMI 2.0-compliant PXE 2.0-compliant IBM ImageUltra™ Services available IBM Rapid Restore PC available to protect software image and data International Warranty Service ¹⁷ Personalized Web-based support ³¹ Proactive e-mail updates ³¹ 24x7 ¹⁸ toll-free support for warranty-related issues during the warranty period ¹²	
Dimensions ³ Approximate weight ² Case material Battery - type Battery - life ¹⁰	12.3" x 10.0" x 1.5"; 313mm x 254mm x 38mm with optical drive and battery: 5.9 lbs (2.6kg) depending on model Color: black; All: ABS plastic Lithium Ion 8-cell / intelligent / supports unique 2nd battery in Ultrabay 2000 Wireless models: 3.0 hrs; Others: 3.1 hrs			
Architecture	Intel 845MP chipset / 82845MP Memory Controller Hub (MCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB, Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus controller, Mini PCI, external expansion) / LPC bus 33MHz (security chip (some); PC87392 Super I/O for diskette, parallel, infrared) Optional ThinkPad Port Replicator (no ThinkPad Dock support)			
Port Replicator PC Card Std slots Ports	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 Two USB (Version 1.1) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port			
Video out IEEE 1394 Mini PCI 11b Wi-Fi ³² /mod	S-video out port (TV out) / one industry standard connector None One Mini PCI type III slot (Communications Bay) / customer upgradable ^{4,36} Some: Mini PCI 11b Wi-Fi ³² wireless ⁴ , Intersil® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K ⁶ V.90 (V.92-designed ²⁹) modem combo, Agere® chipset			
CDC Modem Ethernet Audio support	One Communications Daughter Card (CDC) socket (open or modem) / not accessible Some: 56K ⁶ V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset 10/100 ethernet on motherboard / Intel 82562E Tchipset (physical layer) Soft audio / ICH AC97 controller / SoundBlaster Pro™-compatible / AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal mic / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack			
Security	Power-on password / hard disk password / supervisor password / security keyhole Some: IBM Embedded Security Subsystem 2.0³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCPA-compliant			
Limited warranty ¹²	3 years/1 year battery - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² available			
128 MB PC2100 DDR-SDRAM CL2.5 SOD 256 MB PC2100 DDR-SDRAM CL2.5 SOD 512 MB PC2100 DDR-SDRAM CL2.5 SOD IBM ThinkPad Ultrabay Plus Carrier IBM ThinkPad Ultrabay Plus c500 Cradle ThinkPad Ultrabay Plus Numeric Keypad Travel Bezel for Ultrabay 2000 Zip 250MB Ultrabay 2000 Drive 24X-10X CD-ROM Ultrabay 2000 Drive Ultralight 8X Max DVD Ultrabay 2000 CD-RW/DVD Combo III Ultrabay 2000 Second HDD Adapter for Ultrabay 2000 ThinkPad Removable Diskette Drive ThinkPad Monitor Stand 2001 IBM 802.11a PC Card	10K0028 10K0030 10K0032 22P5737 22P5738 22P7330 08K6070 00N8253 05K9233 22P9102 22P6980 08K6068 08K9603 22P5265 22P7501	ThinkPad Port Replicator Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices) ThinkPad R32/R40 Li-Ion Battery Ultrabay 2000 Li-Ion battery ThinkPad 72W AC Adapter ThinkPad 72W DC Auto Adapter Multiple Li-Ion/NiMH Battery Charger 20GB Hard Disk 9.5mm (4200 rpm) 40GB HS Hard Disk 9.5mm (5400 rpm) 60GB HS Hard Disk 12.5mm (5400 rpm) IBM 128MB USB 2.0 Memory Key TrackPoint Cap Collection IBM USB 2.0 Portable CD-RW IBM USB 2.0 PC Card Other options at ibm.com/pc/us/accessories	02K8667 19K4480 02K7052 02K6646 02K6699 10K3820 02K6719 08K9686 08K9816 08K9688 22P8998 73P2698 22P5297 33L3245	ServicePac®. 22 2yr IOR 9x5 NBD 30L9190 ServicePac 3yr IOR 9x5 NBD 30L9197

See footnotes for important warranty information
US models announced June 4, 2002
US models withdrawn effective January 2003 or April 2003

Type-model	Processor	Speed GHz	Memory	Screen	Disk GB ⁸	Optical	Mini PCI Comm Bay wireless/modem	CDC modem	Ethernet on planar	Security Chip	Preload	Workhorse (W) Limited or Global (G) warranty	Avail date
2658-BZU	Pentium® 4-M	1.6	256MB	14.1" XGA	20GB	DVD	Open (wireless upg ³⁶)	Modem	10/100		XP Pro	1 year	W G Jul 2002
2658-CHU	Pentium 4-M	1.8	256MB	14.1" XGA	30GB	DVD	Cisco 802.11b	Modem	10/100	Yes	XP Pro	1 year	W Jul 2002
Positioning Processor	<i>Best blend of portability and essential features; two-spindle system</i>												
L2 cache	Mobile Intel® Pentium® 4 Processor-M 1.6 or 1.8GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz frontside bus												
Memory	512KB / on die (at processor speed) / ECC 256MB std / 1GB max ⁷ / PC2100 266MHz DDR-SDRAM / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available												
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive												
DVD	<i>Some:</i> DVD-ROM / 8X-3.3X ⁹ speed / bootable / removable from Ultrabay 2000												
Ultrabay 2000	One modular bay for interchangeable devices (right side) / Ultrabay Plus -compatible												
Disk	20GB⁸ or 30GB / 4200 rpm / upgradable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay 2000												
Display	14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits / easy-open cover to unlatch and open with one hand (two latches)												
Graphics controller	ATI® Mobility™ RADEON™ 7000 / AGP 4X / 16MB DDR-SDRAM												
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B												
Keyboard	87-key / ThinkPad Button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)												
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass												
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions / no UltraPort™												
Dimensions ³	12.3" x 10.0" x 1.5"; 313mm x 254mm x 38mm												
Approximate weight ²	with optical drive and battery: 5.9 lbs (2.7 kg)												
Case material	<i>Color:</i> Black; <i>All:</i> ABS plastic												
Battery - type	Lithium Ion 8-cell / intelligent / supports unique 2nd battery in Ultrabay 2000												
Battery - life ¹⁰	<i>Wireless CHU model:</i> 3.0 hrs; <i>BZU:</i> 3.1 hrs												
Architecture	Intel 845MP chipset / 82845MP Memory Controller Hub (MCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB, Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus controller, TSB43AB21 1394 (some), Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared)												
Port Replicator	Optional ThinkPad Port Replicator (no ThinkPad Dock support)												
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door												
Ports	Two USB (Version 1.1) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port												
Video out	S-video out port (TV out) / one industry standard connector												
IEEE 1394	None												
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable												
802.11b	<i>CHU:</i> Mini PCI 802.11b wireless ⁴ , Cisco® Aironet® Wireless 802.11b, Prism 2.0 chipset, dual antennas (in side of display and in base), Wi-Fi-certified												
Wireless up-gradable	<i>BZU:</i> Dual antennas (in side of display and in base) for wireless connectivity / IBM intends to announce Mini PCI Wi-Fi wireless communication options												
CDC	One Communications Daughter Card (CDC) socket (open or modem) / not accessible												
Modem	<i>All:</i> 56K ⁶ V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset												
Ethernet	10/100 ethernet on motherboard / Intel 82562ET chipset (physical layer)												
Audio support	Soft audio / ICH AC97 controller / SoundBlaster Pro™-compatible / AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal mic / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack												
Security	<i>All:</i> Power-on password / hard disk password / supervisor password / security keyhole <i>CHU:</i> IBM Embedded Security Subsystem 2.0³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCPA-compliant												
Limited warranty ¹²	1 year - EasyServ™ ¹⁹ onsite pickup and delivery												
Service options	Service upgrades ²² provide up to five years of onsite or depot repair service coverage from date of ThinkPad purchase (including warranty period)												
128 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028	ThinkPad Port Replicator	02K8667										
256 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030	Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)	19K4480										
512 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032	ThinkPad R32/R40 Li-Ion Battery	02K7052										
IBM ThinkPad Ultrabay Plus Carrier	22P5737	Ultrabay 2000 Li-Ion battery	02K6646										
IBM ThinkPad Ultrabay Plus c500 Cradle	22P5738	ThinkPad 72W AC Adapter	02K6699										
ThinkPad Ultrabay Plus Numeric Keypad	22P7330	ThinkPad 72W DC Auto Adapter	10K3820										
Travel Bezel for Ultrabay 2000	08K6070	Multiple Li-Ion/NiMH Battery Charger	02K6719										
Zip 250MB Ultrabay 2000 Drive	00N8253	20GB Hard Disk 9.5mm (4200 rpm)	08K9686										
24X-10X CD-ROM Ultrabay 2000 Drive	05K9233	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816										
Ultralight 8X Max DVD Ultrabay 2000	22P9102	Optical 3-Button Travel Wheel Mouse	08K9869										
CD-RW/DVD Combo III Ultrabay 2000	22P6980	IBM 128MB USB 2.0 Memory Key	22P8998										
Second HDD Adapter for Ultrabay 2000	08K6068	TrackPoint Cap Collection	73P2698										
ThinkPad Removable Diskette Drive	08K9603	IBM USB 2.0 Portable CD-RW Drive	22P5297										
IBM High Rate Wireless LAN Mini PCI	22P7701	IBM 1GB Microdrive™ with PC Card	07N5574										
Cisco Aironet Wireless 802.11b Mini PCI	31P8301	Other options at ibm.com/pc/us/accessories											
IBM High Rate Wireless LAN PC Card 128	09N9904												

SOFTWARE¹⁴

Windows XP Pro models

- Microsoft® Windows® XP Professional²⁰
- ✦ Disk-to-Disk Recovery (in hidden Service Partition)

INCLUDED SOFTWARE¹⁴ (all)

Preloaded

- Access ThinkPad
- Access Connections
- Access Help
- Access Support
- Adobe Acrobat Reader
- InterVideo WinDVD (DVD models)
- Norton AntiVirus (OEM edition)
- PC-Doctor™
- ThinkPad Utilities
- IBM Update Connector™¹⁵

Downloadable

- IBM Rapid Restore™ PC
- IBM Data Transfer
- IBM Director Agent
- Client Security Software (models with security chip)

License (CD not included)

- Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client

Ultrabay Plus integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series

Universal 72 watt AC adapter
Asset ID (system-specific info in chip accessed over network)
PC 2001-compliant
ACPI 1.0b and 2.0-compliant
CIM and DMI 2.0-compliant
PXE 2.0-compliant
IBM ImageUltra™ Services available
IBM Rapid Restore PC available to protect software image and data
International Warranty Service¹⁷
24 hour x 7 day¹⁸ toll-free hardware support during the warranty¹²

ServicePac ²² 1yr IOR 9x5 NBD	30L9188
ServicePac 2yr IOR 9x5 NBD	30L9189
ServicePac 3yr IOR 9x5 NBD	30L9195
ServicePac 4yr IOR 9x5 NBD	69P9194
ServicePac 5yr IOR 9x5 NBD	69P9196
ServicePac 2yr P&L P/U Depot	30L9191
ServicePac 3yr P&L P/U Depot	30L9192
ServicePac 4yr P&L P/U Depot	69P9195
ServicePac 5yr P&L P/U Depot	69P9197

See footnotes for important warranty information
US models announced July 16, 2002
US models withdrawn effective April or July 2003

Type-model	Processor	Speed GHz	Memory	Screen	Disk GB ⁸	Optical	Mini PCI Comm Bay wireless/modem	CDC modem	Ethernet on planar	Security Chip	Preload	Limited warranty	Workhorse (W) or Global (G) model	Avail date																																																											
2659-BZU	Pentium® 4-M 1.6	256MB	14.1" XGA	20GB	DVD	Open (wireless upg ³⁶)	Modem 10/100	Modem 10/100	Yes	XP Pro	3 years	W G	Jul 2002																																																												
2659-CHU	Pentium 4-M 1.8	256MB	14.1" XGA	30GB	DVD	Cisco 802.11b	Modem 10/100	Modem 10/100	Yes	XP Pro	3 years	W	Jul 2002																																																												
2659 models have a 3 year limited warranty (other 2658 ThinkPad R32 systems have a 1 year limited warranty)																																																																									
Positioning Processor	<i>Best blend of portability and essential features; two-spindle system</i> Mobile Intel® Pentium® 4 Processor-M 1.6 or 1.8GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz frontside bus											SOFTWARE¹⁴																																																													
L2 cache Memory	512KB / on die (at processor speed) / ECC 256MB std / 1GB max ⁷ / PC2100 266MHz DDR-SDRAM / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available											Windows XP Pro models - Microsoft® Windows® XP Professional ²⁰ ◇ Disk-to-Disk Recovery (in hidden Service Partition)																																																													
Diskette drive DVD Ultrabay 2000 Disk	None standard / use optional Ultrabay™-based or USB-based diskette drive <i>Some:</i> DVD-ROM / 8X-3.3X ⁹ speed / bootable / removable from Ultrabay 2000 One modular bay for interchangeable devices (right side) / Ultrabay Plus -compatible 20GB⁸ or 30GB / 4200 rpm / upgradable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay 2000											INCLUDED SOFTWARE¹⁴ (all)																																																													
Display	14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits / easy-open cover to unlatch and open with one hand (two latches)											Preloaded • Access ThinkPad - Access Connections - Access Help - Access Support • Adobe Acrobat Reader • InterVideo WinDVD (DVD models) • Norton AntiVirus (OEM edition) • PC-Doctor™ • ThinkPad Utilities • IBM Update Connector™ ¹⁵																																																													
Graphics controller Graphics - external	ATI® Mobility™ RADEON™ 7000 / AGP 4X / 16MB DDR-SDRAM External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B											Downloadable • IBM Rapid Restore™ PC • IBM Data Transfer • IBM Director Agent • Client Security Software (models with security chip)																																																													
Keyboard TrackPoint® ThinkLight™	87-key / ThinkPad Button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys) TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass Illuminates the keyboard to improve visibility in low-light conditions / no UltraPort™											License (CD not included) - Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client																																																													
Dimensions ³ Approximate weight ² Case material Battery - type Battery - life ¹⁰	12.3" x 10.0" x 1.5"; 313mm x 254mm x 38mm with optical drive and battery: 5.9 lbs (2.7 kg) <i>Color:</i> Black; <i>All:</i> ABS plastic Lithium Ion 8-cell / intelligent / supports unique 2nd battery in Ultrabay 2000 <i>Wireless CHU model:</i> 3.0 hrs; <i>BZU:</i> 3.1 hrs																																																																								
Architecture	Intel 845MP chipset / 82845MP Memory Controller Hub (MCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB, Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus controller, TSB43AB21 1394 (some), Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared) Optional ThinkPad Port Replicator (no ThinkPad Dock support)																																																																								
Port Replicator PC Card Std slots Ports	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door Two USB (Version 1.1) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port																																																																								
Video out IEEE 1394 Mini PCI 802.11b	S-video out port (TV out) / one industry standard connector None One Mini PCI type III slot (Communications Bay) / customer upgradable <i>CHU:</i> Mini PCI 802.11b wireless ⁴ , Cisco® Aironet® Wireless 802.11b, Prism 2.0 chipset, dual antennas (in side of display and in base), Wi-Fi-certified											Ultrabay Plus integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series																																																													
Wireless up-gradable CDC Modem Ethernet Audio support	<i>BZU:</i> Dual antennas (in side of display and in base) for wireless connectivity / IBM intends to announce Mini PCI Wi-Fi wireless communication options One Communications Daughter Card (CDC) socket (open or modem) / not accessible <i>All:</i> 56K ⁶ V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset 10/100 ethernet on motherboard / Intel 82562ET chipset (physical layer) Soft audio / ICH AC97 controller / SoundBlaster Pro™-compatible / AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal mic / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack <i>All:</i> Power-on password / hard disk password / supervisor password / security keyhole <i>CHU:</i> IBM Embedded Security Subsystem 2.0³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCPA-compliant																																																																								
Security												Universal 72 watt AC adapter Asset ID (system-specific info in chip accessed over network) PC 2001-compliant ACPI 1.0b and 2.0-compliant CIM and DMI 2.0-compliant PXE 2.0-compliant IBM ImageUltra™ Services available IBM Rapid Restore PC available to protect software image and data International Warranty Service ¹⁷ 24 hour x 7 day ¹⁸ toll-free hardware support during the warranty ¹²																																																													
Limited warranty ¹² Service options	3 years /1 year battery - EasyServ™ ¹⁹ onsite pickup and delivery Service upgrades ²² provide up to five years of onsite or depot repair service coverage from date of ThinkPad purchase (including warranty period)																																																																								
128 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028	ThinkPad Port Replicator	02K8667	256 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030	Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)	19K4480	512 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032	ThinkPad R32/R40 Li-Ion Battery	02K7052	IBM ThinkPad Ultrabay Plus Carrier	22P5737	IBM ThinkPad Ultrabay Plus c500 Cradle	22P5738	Ultrabay 2000 Li-Ion battery	02K6646	ThinkPad Ultrabay Plus Numeric Keypad	22P7330	ThinkPad 72W AC Adapter	02K6699	Travel Bezel for Ultrabay 2000	08K6070	ThinkPad 72W DC Auto Adapter	10K3820	Zip 250MB Ultrabay 2000 Drive	00N8253	Multiple Li-Ion/NiMH Battery Charger	02K6719	24X-10X CD-ROM Ultrabay 2000 Drive	05K9233	20GB Hard Disk 9.5mm (4200 rpm)	08K9686	Ultralight 8X Max DVD Ultrabay 2000	22P9102	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816	CD-RW/DVD Combo III Ultrabay 2000	22P6980	Optical 3-Button Travel Wheel Mouse	31P7410	Second HDD Adapter for Ultrabay 2000	08K6068	IBM 128MB USB 2.0 Memory Key	22P8998	ThinkPad Removable Diskette Drive	08K9603	TrackPoint Cap Collection	73P2698	IBM High Rate Wireless LAN Mini PCI	22P7701	IBM USB 2.0 Portable CD-RW Drive	22P5297	IBM High Rate Wireless LAN Mini PCI	31P8301	IBM 1GB Microdrive™ with PC Card	07N5574	Cisco Aironet Wireless 802.11b Mini PCI	09N9904	Other options at ibm.com/pc/us/accessories		ServicePac®. ²² 2yr IOR 9x5 NBD	30L9190	ServicePac 3yr IOR 9x5 NBD	30L9197	ServicePac 4yr IOR 9x5 NBD	69P9198	ServicePac 5yr IOR 9x5 NBD	69P9200	ServicePac 4yr P&L P/U Depot	69P9199	ServicePac 5yr P&L P/U Depot	69P9201

See footnotes for important warranty information
US models announced July 16, 2002
US models withdrawn effective April or July 2003

Type-model	Processor	Speed GHz	Memory	Screen	Disk GB ⁸	Optical	Mini PCI Comm Bay wireless/modem	Ethernet IEEE on 1394 Security Chip	Preload business or software	Small Global (G)	Workhorse (W) model	Avail date
2658-H3U	Celeron®	1.5	128MB	14.1" XGA	20G	CD	Open	Modem 10/100	XP Pro			Sep 2002
2658-J3U	Pentium® 4-M	1.8	256MB	14.1" XGA	20G	DVD	Open; wireless upg ³⁶	Modem 10/100	XP Pro		W G	Sep 2002
2658-N3U	Pentium 4-M	2.0	256MB	14.1" XGA	30G	DVD	Open; wireless upg ³⁶	Modem 10/100	XP Pro		W G	Sep 2002
2658-N4U	Pentium 4-M	2.0	256MB	14.1" XGA	30G	DVD	11b Wi-Fi ³² /modem	Open 10/100	Yes XP Pro		W G	Sep 2002
2658-N5U	Pentium 4-M	2.0	256MB	14.1" XGA	30G	DVD	Cisco® 802.11b	Modem 10/100	Yes XP Pro		W	Sep 2002
2658-K7U	Pentium 4-M	1.7	128MB	14.1" XGA	20G	DVD	Open	Modem 10/100	1394 XP Pro			Sep 2002
2658-KAU	Pentium 4-M	1.7	128MB	14.1" XGA	20G	CD	Open	Modem 10/100	XP Pro			Sep 2002
2658-KGU	Pentium 4-M	1.7	128MB	14.1" XGA	30G	Combo	Open	Modem 10/100	XP Pro			Sep 2002
2658-KHU	Pentium 4-M	1.7	128MB	14.1" XGA	30G	Combo	11b Wi-Fi/modem	None 10/100	1394 Yes XP Pro			Sep 2002
2658-KJU	Pentium 4-M	1.7	128MB	14.1" XGA	40G	Combo	Open	Modem 10/100	1394 XP Pro			Sep 2002
2658-LSU	Pentium 4-M	1.7	256MB	14.1" XGA	20G	Combo	Open	Modem 10/100	1394 XP Pro			Sep 2002
2658-NWU	Pentium 4-M	2.0	256MB	14.1" XGA	40G	Combo	Open	Modem 10/100	1394 Yes XP Pro			Sep 2002
2658-K4U	Pentium 4-M	1.7	128MB	14.1" XGA	20G	CD	Open	Modem 10/100	XP Home			Sep 2002
2658-K8U	Pentium 4-M	1.7	128MB	14.1" XGA	20G	DVD	11b Wi-Fi/modem	None 10/100	XP Pro	Office XP SB ¹⁸		Sep 2002
2658-KCU	Pentium 4-M	1.7	128MB	14.1" XGA	20G	CD	Open	Modem 10/100	XP Pro	Office XP SB		Sep 2002
2658-LHU	Pentium 4-M	1.7	256MB	14.1" XGA	20G	DVD	Open	Modem 10/100	XP Pro	Office XP SB		Sep 2002
Positioning Processor	<i>Best blend of portability and essential features; two-spindle system</i> Mobile Intel® Celeron 1.5GHz with 400MHz frontside bus or Mobile Intel Pentium 4 Processor-M 1.7, 1.8, or 2.0GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz frontside bus								SOFTWARE¹⁴			
L2 cache	Celeron: 256KB ; Pentium 4-M: 512KB ; All: on die (at processor speed) / ECC								Windows XP Pro models			
Memory	128 or 256MB std / 1GB max ⁷ / PC2100 266MHz DDR-SDRAM / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available								- Microsoft® Windows® XP Professional ²⁰ ◆ Disk-to-Disk Recovery (in hidden Service Partition)			
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive								Windows XP Home models			
CD	<i>Some:</i> CD-ROM / 24X-10X ⁹ speed / bootable / removable from Ultrabay 2000								- Microsoft Windows XP Home ²⁰			
DVD	<i>Some:</i> DVD-ROM / 8X-3.3X ⁹ speed / bootable / removable from Ultrabay 2000								◆ Disk-to-Disk Recovery (in hidden Service Partition)			
Combo	<i>Some:</i> DVD-ROM/CD-RW / 8X/8X/24X/8X ²¹ speed / removable from Ultrabay 2000								INCLUDED SOFTWARE¹⁴ (all)			
Ultrabay 2000	One modular bay for interchangeable devices / Ultrabay Plus -compatible								Preloaded			
Disk	20GB⁸, 30GB, or 40GB / 4200 rpm / upgradable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay 2000								• Access ThinkPad			
Display	14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits / easy-open cover to unlatch and open with one hand (two latches)								- Access Connections			
Graphics controller	ATI® Mobility™ RADEON™ 7000 / AGP 4X / 16MB DDR-SDRAM								- Access Help			
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B								- Access Support			
Keyboard	87-key / ThinkPad Button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)								• Adobe Acrobat Reader			
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass								• InterVideo WinDVD (DVD models)			
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions / no UltraPort™								• Norton AntiVirus (OEM edition)			
Dimensions ³	12.3" x 10.0" x 1.5"; 313mm x 254mm x 38mm								• PC-Doctor™			
Approximate weight ²	with optical drive and battery: 5.9 to 6.2 lbs (2.6 to 2.7 kg) depending on model								• ThinkPad Utilities			
Case material	<i>Color:</i> Black; <i>All:</i> ABS plastic								• IBM RecordNOW and DLA by Veritas (combo models)			
Battery - type	Lithium Ion 8-cell / intelligent / supports unique 2nd battery in Ultrabay 2000								• IBM Update Connector™.15			
Battery - life ¹⁰	<i>Celeron model:</i> 3.1 hrs; <i>wireless models:</i> 3.2 hrs; <i>Pentium 4 non-wireless:</i> 3.3 hrs								• IBM Rapid Restore™ PC			
Architecture	Intel 845MP chipset / 82845MP Memory Controller Hub (MCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB, Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus controller, TSB43AB21 1394 (some), Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared)								Downloadable			
Port Replicator	Optional ThinkPad Port Replicator (no ThinkPad Dock support)								• IBM Director Agent			
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door								• Software Delivery Assistant			
Ports	Two USB (Version 1.1) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port								• System Migration Assistant			
Video out	S-video out port (TV out) / one industry standard connector								• Client Security Software (models with security chip)			
IEEE 1394 (FireWire)	<i>Some:</i> IEEE 1394 (FireWire) port / 4-pin connector								License (CD not included)			
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradeable								- Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client			
11b Wi-Fi ³² /mod	<i>Some:</i> Mini PCI 11b Wi-Fi ³² wireless ⁴ , Intersil® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K ⁶ V.90 (V.92-designed ²⁹) modem combo, Agere® chipset								Office XP Small Business model only (2658-K8U/KCU/LHU)			
802.11b	<i>N5U:</i> Mini PCI 802.11b wireless ⁴ , Cisco® Aironet® Wireless 802.11b with custom chipset, dual antennas (in side of display and in base), Wi-Fi-certified								- Microsoft Office XP Small Business ²⁸ (Word, Excel, Outlook, Publisher, Small Business Tools)			
Wireless upg ³⁶	<i>Some:</i> Dual antennas (in display and in base) for wireless connectivity Mini PCI options								◆ Office XP Small Business CD			
CDC	One Communications Daughter Card (CDC) socket (open or modem) / not accessible								Universal 72 watt AC adapter			
Modem	<i>Some:</i> 56K ⁶ V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset								Asset ID (system-specific info in chip accessed over network)			
Ethernet	10/100 ethernet on motherboard / Intel 82562ET chipset (physical layer)								PC 2001 and PXE 2.0-compliant			
Audio support	Soft audio / ICH AC97 controller / SoundBlaster Pro™-compatible / AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal mic / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack								ACPI 1.0b and 2.0-compliant			
Security	Power-on password / hard disk password / supervisor password / security keyhole								CIM and DMI 2.0-compliant			
	<i>Some:</i> IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant								IBM Rapid Restore PC available to protect software image and data			
Limited warranty ¹²	1 year - EasyServ™.19 onsite pickup and delivery / service upgrades ²² available								International Warranty Service ¹⁷			
									24 hour x 7 day ¹⁸ toll-free hardware support during the warranty ¹²			
128MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028		ThinkPad Port Replicator		02K8667							
256MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030		Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)		19K4480						ServicePac®.22 1yr IOR 9x5 NBD	
512MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032		ThinkPad R32/R40 Li-Ion Battery		02K7052						30L9188	
UltraLight 8X Max DVD Ultrabay 2000	22P9102		Ultrabay 2000 Li-Ion battery		02K6646						ServicePac 3yr P&L P/U Depot	
CD-RW/DVD Combo IV Ultrabay 2000	22P6991		ThinkPad 72W AC Adapter		02K6699						30L9192	
Second HDD Adapter for Ultrabay 2000	08K6068		40GB HS Hard Disk 9.5mm (5400 rpm)		08K9816						Other ServicePac options at	
ThinkPad Removable Diskette Drive	08K9603		IBM 11a/b/g Wireless CardBus Adapter		31P9101						ibm.com/services/its/us/source/wamomxeu.pdf	
Other options at ibm.com/pc/us/accessories												

See footnotes for important warranty information
US models announced September 17, 2002
US models withdrawn effective April, July, or October 2003

Type-model	Processor	Speed GHz	Memory	Screen	Disk GB ⁵	Optical	Mini PCI Comm Bay wireless/modem	CDC modem	Ethernet on planar	Security Chip	Preload	Workhorse (W) Limited or Global (G) warranty	Avail date	
2659-J3U	Pentium® 4-M	1.8	256MB	14.1" XGA	20GB	DVD	Open (wireless upg ³⁶)	Modem	10/100	XP Pro	3 years	W G	Sep2002	
2659-N3U	Pentium 4-M	2.0	256MB	14.1" XGA	30GB	DVD	Open (wireless upg ³⁶)	Modem	10/100	XP Pro	3 years	W G	Sep2002	
2659-N4U	Pentium 4-M	2.0	256MB	14.1" XGA	30GB	DVD	11b Wi-Fi ³² /modem	None	10/100	Yes	XP Pro	3 years	W G	Sep2002
2659-N5U	Pentium 4-M	2.0	256MB	14.1" XGA	30GB	DVD	Cisco® 802.11b	Modem	10/100	Yes	XP Pro	3 years	W	Sep2002

2659 models have a 3 year limited warranty (other 2658 ThinkPad R32 systems have a 1 year limited warranty)

Positioning	Best blend of portability and essential features; two-spindle system											
Processor	Mobile Intel® Pentium® 4 Processor-M 1.8 or 2.0GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz frontside bus											
L2 cache	512KB / on die (at processor speed) / ECC											
Memory	256MB std / 1GB max ⁷ / PC2100 266MHz DDR-SDRAM / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available											
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive											
DVD	DVD-ROM / 8X-3.3X ⁹ speed / bootable / removable from Ultrabay 2000											
Ultrabay 2000	One modular bay for interchangeable devices (right side) / Ultrabay Plus-compatible											
Disk	20GB ⁹ or 30GB / 4200 rpm / upgradable / S.M.A.R.T. / supports 2nd disk with optional HDD Adapter in Ultrabay 2000											
Display	14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits / easy-open cover to unlatch and open with one hand (two latches)											
Graphics controller	ATI® Mobility™ RADEON™ 7000 / AGP 4X / 16MB DDR-SDRAM											
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B											
Keyboard	87-key / ThinkPad Button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)											
TrackPoint™	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass											
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions / no UltraPort™											
Dimensions ³	12.3" x 10.0" x 1.5"; 313mm x 254mm x 38mm											
Approximate weight ²	with optical drive and battery: 6.0 lbs (2.7 kg)											
Case material	Color: Black; All: ABS plastic											
Battery - type	Lithium Ion 8-cell / intelligent / supports unique 2nd battery in Ultrabay 2000											
Battery - life ¹⁰	Wireless N4U/N5U: 3.2 hrs; non-wireless J3U/N3U: 3.3 hrs											
Architecture	Intel 845MP chipset / 82845MP Memory Controller Hub (MCH-M) / 82801CAM ICH3-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB, Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1410A CardBus controller, TSB43AB21 1394 (some), Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared)											
Port Replicator	Optional ThinkPad Port Replicator (no ThinkPad Dock support)											
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door											
Ports	Two USB (Version 1.1) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port											
Video out	S-video out port (TV out) / one industry standard connector											
IEEE 1394	None											
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable											
11b Wi-Fi ³² /mod	N4U: Mini PCI 11b Wi-Fi ³² wireless ⁴ , Intersil® Prism 2.5 chipset, dual antennas (in side of display and in base), Wi-Fi-certified / 56K ⁶ V.90 (V.92-designed ²⁹) modem combo, Agere® chipset											
802.11b	N5U: Mini PCI 802.11b wireless ⁴ , Cisco® Aironet® Wireless 802.11b, Prism 2.0 chipset, dual antennas (in side of display and in base), Wi-Fi-certified											
Wireless upg ³⁶	Some: Dual antennas (in display and in base) for wireless connectivity Mini PCI options											
CDC Modem	One Communications Daughter Card (CDC) socket (open or modem) / not accessible											
Ethernet	Some: 56K ⁶ V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset											
Audio support	10/100 ethernet on motherboard / Intel 82562ET chipset (physical layer) / Soft audio / ICH AC97 controller / SoundBlaster Pro™-compatible / AD1881A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / no internal mic / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack											
Security	All: Power-on password / hard disk password / supervisor password / security keyhole / Some: IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant											
Limited warranty ¹²	3 years/1 year battery - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² available											
128 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028	ThinkPad Port Replicator	02K8667									
256 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030	Portable Drive Bay 2000 (accepts Ultrabay 2000 media and storage devices)	19K4480									
512 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032	ThinkPad R32/R40 Li-Ion Battery	02K7052									
IBM ThinkPad Ultrabay Plus Carrier	22P5737	Ultrabay 2000 Li-Ion battery	02K6646									
IBM ThinkPad Ultrabay Plus c500 Cradle	22P5738	ThinkPad 72W AC Adapter	02K6699									
ThinkPad Ultrabay Plus Numeric Keypad	22P7330	ThinkPad 72W AC/DC Combo Adapter	22P9010									
Travel Bezel for Ultrabay 2000	08K6070	Multiple Li-Ion/NiMH Battery Charger	02K6719									
Zip 250MB Ultrabay 2000 Drive	00N8253	20GB Hard Disk Drive	08K9686									
24X-10X ⁹ CD-ROM Ultrabay 2000 Drive	05K9233	40GB Hard Disk Drive	08K9687									
Ultralight 8X ⁹ Max DVD Ultrabay 2000	22P9102	40GB HS Hard Disk Drive (5400 rpm)	08K9816									
CD-RW/DVD Combo IV Ultrabay 2000	22P6991	Optical 3-Button Travel Wheel Mouse	31P7410									
Second HDD Adapter for Ultrabay 2000	08K6068	IBM 128MB USB 2.0 Memory Key	22P8998									
ThinkPad Removable Diskette Drive	08K9603	TrackPoint Cap Collection	73P2698									
IBM High Rate Wireless LAN PC Card 128	09N9904	IBM USB 2.0 Portable CD-RW Drive	22P5297									
IBM High Rate Wireless LAN Mini PCI	22P7701	ThinkPad USB 2.0 PC CardBus Adpter	33L3245									
Cisco Aironet Wireless 802.11b Mini PCI	31P8301	Other options at ibm.com/pc/us/accessories										
IBM 11a/b/g Wireless CardBus Adapter	31P9101											
<p>SOFTWARE¹⁴</p> <p>Windows XP Pro models</p> <ul style="list-style-type: none"> - Microsoft® Windows® XP Professional²⁰ ◇ Disk-to-Disk Recovery (in Hidden Service Partition) <p>INCLUDED SOFTWARE¹⁴ (all)</p> <p>Preloaded</p> <ul style="list-style-type: none"> • Access ThinkPad - Access Connections - Access Help - Access Support • Adobe Acrobat Reader • InterVideo WinDVD (DVD models) • Norton AntiVirus (OEM edition) • PC-Doctor™ • ThinkPad Utilities • IBM Update Connector™¹⁵ • IBM Rapid Restore™ PC <p>Downloadable</p> <ul style="list-style-type: none"> • IBM Director Agent • Software Delivery Assistant • System Migration Assistant • Client Security Software (models with security chip) <p>License (CD not included)</p> <ul style="list-style-type: none"> - Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client <p>Ultrabay Plus integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series</p> <p>Universal 72 watt AC adapter Asset ID (system-specific info in chip accessed over network) PC 2001-compliant ACPI 1.0b and 2.0-compliant CIM and DMI 2.0-compliant PXE 2.0-compliant IBM ImageUltra™ Services available IBM Rapid Restore PC available to protect software image and data International Warranty Service¹⁷ 24 hour x 7 day¹⁸ toll-free hardware support during the warranty¹²</p> <p>ServicePac®.²² 2yr IOR 9x5 NBD 30L9190</p> <p>ServicePac 3yr IOR 9x5 NBD 30L9197</p> <p>ServicePac 4yr IOR 9x5 NBD 69P9198</p> <p>ServicePac 5yr IOR 9x5 NBD 69P9200</p> <p>ServicePac 4yr P&L P/U Depot 69P9199</p> <p>ServicePac 5yr P&L P/U Depot 69P9201</p>												

See footnotes for important warranty information
US models announced September 17, 2002
US models withdrawn effective July or October 2003

IBM® ThinkPad® R40e (October 2003) - withdrawn

Created by IBM PC Institute
Personal Systems Reference (PSREF)

Type-model	Processor	Speed GHz	Memory	Screen	Disk GB ⁸	Optical	Mini PCI Comm Bay wireless	CDC modem	Ethernet on planar	Security chip	Preload	Workhorse (W) or Global (G) or Entry (E)	Avail date
2684-H6U	Celeron®	2.0	128MB	14.1" XGA	20GB	CD	None	Modem	10/100	No	Windows XP Pro	No	Oct 2003
2684-H8U	Celeron	2.0	128MB	14.1" XGA	20GB	CD	None	Modem	10/100	No	Windows XP Home	Entry	Oct 2003
2684-H4U	Celeron	2.0	128MB	14.1" XGA	30GB	Combo	None	Modem	10/100	No	Windows XP Home	No	Oct 2003

Positioning	<i>Mainstream performance and features; two-spindle system</i>										
Processor	Mobile Intel® Celeron 2.0GHz with 400MHz system bus										
L2 cache	256KB / on die (at processor speed) / ECC										
Memory	128MB std / 1GB max ⁷ / PC2100 266MHz DDR-SDRAM / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available										
Diskette drive	None standard / use optional USB-based diskette drive										
CD	<i>Some:</i> CD-ROM / 24X-10X ⁹ speed / fixed, not removable										
Combo	<i>Some:</i> Combo / 24X/10X/24X/8X ²¹ speed / fixed, not removable										
Ultrabay™ 2000	None										
Disk	20 or 30GB ⁸ , 4200 rpm, 9.5mm, S.M.A.R.T. / removable and upgradable / 9.5mm high bay										
Display	14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits / easy-open cover to unlatch and open with one hand (two latches)										
Graphics controller	ATI® RADEON™ IGP 330M / integrated in northbridge / 16MB DDR-SDRAM										
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B										
Keyboard	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)										
TrackPoint®	TrackPoint pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass / soft dome TrackPoint cap / ships with classic dome and soft rim TrackPoint cap										
Touch pad	No UltraNav™ multi-pointing system										
ThinkLight™	None										
Dimensions ³	12.3 x 10.0 x 1.53" / 313mm x 254mm x 38.9mm										
Approximate weight ²	with optical drive and battery: <i>H6U/H8U:</i> 5.9 lb (2.67kg); <i>H4U:</i> 6.0 lb (2.72kg)										
Case material	<i>Color:</i> black; <i>All:</i> Acrylonitrile-Butadiene-Styrene (ABS) plastic										
Battery - type	Lithium Ion 6-cell / intelligent										
Battery - life ¹⁰	Up to 2.1 hrs										
Architecture	ATI RADEON IGP 330M chipset / IGP 330M northbridge (memory controller, graphics controller, PCI bus) / ALi® M1535+ southbridge (ATA-100 EIDE, Low Pin Count [LPC] interface, USB, parallel, audio) / PCI 2.1, 32-bit 33MHz (TI® PCI1510 CardBus controller) / LPC bus 33MHz (PC87392 Super I/O for parallel)										
Port replicator	No port replicator support										
Docking station	No docking station support										
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door										
Ports	Two USB (Version 1.1) / parallel / external monitor (DB-15) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial or infrared port										
Video out	None										
IEEE 1394	None										
Wireless antenna	None / can upgrade to wireless via optional PC Cards										
Mini PCI	No Mini PCI slot (Communications Bay)										
CDC	One Communications Daughter Card (CDC) socket (used by modem) / not accessible										
Modem	56K ⁶ V.90 (V.92-designed ²³) modem in CDC / Agere® chipset										
Ethernet	10/100 ethernet on planar / Broadcom® BCM5901 (PHY/MAC) / PXE / Wake on LAN®										
Audio support	Soft audio / ICH AC97 controller / DirectSound® support / AD1981B AC97 codec / mono speakers / 1 watt / volume up, down, mute buttons / internal mic / microphone input jack (3.5 mm; mono) / headphone jack (3.5 mm; stereo) / no line-in jack										
Security	Power-on password / hard disk password / supervisor password / security keyhole										
Security chip	None										
Limited warranty ¹²	1 year - EasyServ™ ¹⁹ onsite pickup and delivery courier service										
Service options	Service upgrades ²² provide up to five years of onsite or depot repair service coverage from date of ThinkPad purchase (including warranty period)										
128MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028	ThinkPad R40e Li-Ion Battery (6-cell)	08K8218	ServicePac 2 yr P&L P/U Depot	30L9191						
256MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030	Multiple Multiple Battery Charger II	22P9040	ServicePac 3 yr P&L P/U Depot	30L9192						
512MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032	ThinkPad 72W AC Adapter	02K6699	ServicePac 4 yr P&L P/U Depot	69P9195						
30GB Hard Disk 9.5mm (4200 rpm)	09N4268	ThinkPad 72W AC/DC Combo Adapter	22P9010	ServicePac 5 yr P&L P/U Depot	69P9197						
40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816	IBM USB Keyboard with UltraNav	31P8950	Other ServicePac options at							
IBM 4GB Microdrive™ with PC Card	09N4280	ThinkPad Monitor Stand 2001	22P5265	ibm.com/services/its/us/source/wamomxeu.pdf							
IBM 128MB USB 2.0 Memory Key	22P9229	IBM 11 a/b/g Wireless CardBus Adapter	31P9101	Post-warranty annual maintenance agreements at							
IBM 256MB USB 2.0 Memory Key	22P9025	IBM H Rate Wireless LAN PC Card 128	09N9904	ibm.com/services/its/us/source/maspspleu.pdf							
IBM USB Portable Diskette Drive	05K9276	IBM iLV200 Value Data/Video Projector	0038A03								
IBM USB Portable CD-ROM	33L5151	IBM iLC300 Conference Room Projector	0039A03								
IBM USB 2.0 Portable CD-RW Drive	22P5297	IBM Optical 3-Button Travel Wheel Mouse	31P7410								
IBM USB Serial Parallel Adapter	22P5298	IBM Optical 3-Button ScrollPoint® Mouse	31P7405								
GemPC400 Smart Card Reader/Writer	31P8901	Nylon Carrying Case	10K0207								
IBM Turbo 16/4 Token-Ring PC Card 2	34L1401	Leather Carrying Case	10K0209								
Ericsson® GC82 EDGE PC Card Wireless	58P8782	Other options at ibm.com/pc/us/accessories									

See footnotes for important warranty information
US models announced October 7, 2003
US models withdrawn effective April 2004

(R40E) © IBM Corp. April 2004

Type-model	Processor	Speed GHz	Memory	Screen	Disk GB ⁸	Optical	Mini PCI Comm Bay wireless	CDC modem	Ethernet on planar	Security chip	Preload	Workhorse (W) or Global (G) or Entry (E)	Avail date
2684-KJU	Celeron®	2.2	128MB	14.1" XGA	20GB	CD	None	Modem	10/100	No	Windows XP Home	Entry	Apr 2004
2684-KAU	Celeron	2.2	256MB	14.1" XGA	30GB	Combo	None	Modem	10/100	No	Windows XP Pro	No	Apr 2004
2684-KNU	Celeron	2.2	256MB	14.1" XGA	20GB	CD	None	Modem	10/100	No	Windows XP Pro	No	Apr 2004

Positioning	<i>Mainstream performance and features; two-spindle system</i>										
Processor	Mobile Intel® Celeron 2.2GHz with 400MHz system bus										
L2 cache	256KB / on die (at processor speed) / ECC										
Memory	128MB or 256MB std / 1GB max ⁷ / PC2100 266MHz DDR1 / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket avail										
Diskette drive	None standard / use optional USB-based diskette drive										
CD	Some: CD-ROM / 24X-10X ⁹ speed / fixed, not removable										
Combo	Some: Combo / 24X/10X/24X/8X ²¹ speed / fixed, not removable										
Ultrabay™ 2000	None										
Disk	20 or 30GB ⁸ , 4200 rpm, 9.5mm, S.M.A.R.T. / removable and upgradable / 9.5mm high bay										
Display	14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits / easy-open cover to unlatch and open with one hand (two latches)										
Graphics controller	ATI® RADEON™ IGP 330M / integrated in northbridge / 16MB DDR1 (DDR-SDRAM)										
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B										
Keyboard	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)										
TrackPoint®	TrackPoint pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass / soft dome TrackPoint cap / ships with classic dome and soft rim TrackPoint cap										
Touch pad	No UltraNav™ multi-pointing system										
ThinkLight™	None										
Dimensions ³	12.3 x 10.0 x 1.53" / 313mm x 254mm x 38.9mm										
Approximate weight ²	with optical drive and battery: KJU/KNU: 5.9 lb (2.67kg); KAU: 6.0 lb (2.72kg)										
Case material	Color: black; All: Acrylonitrile-Butadiene-Styrene (ABS) plastic										
Battery - type	Lithium Ion 6-cell / intelligent										
Battery - life ¹⁰	Up to 2.1 hrs										
Architecture	ATI RADEON IGP 330M chipset / IGP 330M northbridge (memory controller, graphics controller, PCI bus) / ALi® M1535+ southbridge (ATA-100 EIDE, Low Pin Count [LPC] interface, USB, parallel, audio) / PCI 2.1, 32-bit 33MHz (TI® PCI1510 CardBus controller) / LPC bus 33MHz (PC87392 Super I/O for parallel)										
Port replicator	No port replicator support										
Docking station	No docking station support										
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door										
Ports	Two USB (Version 1.1) / parallel / external monitor (DB-15) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial or infrared port										
Video out	None										
IEEE 1394	None										
Wireless antenna	None / can upgrade to wireless via optional PC Cards										
Mini PCI	No Mini PCI slot (Communications Bay)										
CDC	One Communications Daughter Card (CDC) socket (used by modem) / not accessible										
Modem	56K ⁶ V.90 (V.92-designed ²³) modem in CDC / Agere® chipset										
Ethernet	10/100 ethernet® Broadcom® BCM5901 (PHY/MAC) / PXE / Wake on LAN®										
Audio support	Soft audio / ICH AC97 controller / DirectSound® support / AD1981B AC97 codec / mono speakers / 1 watt / volume up, down, mute buttons / internal mic / microphone input jack (3.5 mm; mono) / headphone jack (3.5 mm; stereo) / no line-in jack										
Security	Power-on password / hard disk password / supervisor password / security keyhole										
Security chip	None										
Limited warranty ¹²	1 year - EasyServ™.19 onsite pickup and delivery courier service										
Service options	Service upgrades ²² provide up to five years of onsite or depot repair service coverage from date of ThinkPad purchase (including warranty period)										
128 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028	ThinkPad R40e Li-Ion Battery (6-cell)	08K8218	ServicePac 2 yr P&L P/U Depot	30L9188						
256 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030	Multiple Multiple Battery Charger II	22P9040	ServicePac 2 yr IOR 9x5 NBD	30L9189						
512 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032	ThinkPad 72W AC Adapter	02K6699	ServicePac 3 yr IOR 9x5 NBD	30L9195						
30GB Hard Disk 9.5mm (4200 rpm)	09N4268	ThinkPad 72W AC/DC Combo Adapter	22P9010	ServicePac 4 yr IOR 9x5 NBD	30L9194						
40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816	IBM USB Keyboard with UltraNav	31P8950	ServicePac 5 yr IOR 9x5 NBD	30L9196						
IBM 4GB Microdrive™ with PC Card	09N4280	ThinkPad Monitor Stand 2001	22P5265	ServicePac 2 yr P&L P/U Depot	30L9191						
IBM 128MB USB 2.0 Memory Key	22P9229	IBM 11 a/b/g Wireless CardBus Adapter	31P9101	ServicePac 3 yr P&L P/U Depot	30L9192						
IBM 256MB USB 2.0 Memory Key	22P9025	IBM M400 Projector	0037A04	ServicePac 4 yr P&L P/U Depot	69P9195						
IBM USB Portable Diskette Drive	05K9276	IBM E400 Projector	0038A04	ServicePac 5 yr P&L P/U Depot	69P9197						
IBM USB Portable CD-ROM	33L5151	IBM C400 Projector	0039A04	Other ServicePac options at							
IBM USB 2.0 Portable Combo Drive	22P9194	IBM Optical 3-Button Travel Wheel Mouse	31P7410	ibm.com/services/its/us/source/wamomxeu.pdf							
IBM USB Serial Parallel Adapter	22P5298	IBM Optical 3-Button ScrollPoint® Mouse	31P7405	Post-warranty annual maintenance agreements at							
GemPC400 Smart Card Reader/Writer	31P8901	Nylon Carrying Case	10K0207	ibm.com/services/its/us/source/maspspleu.pdf							
Kensington® Microsaver® Security Cable	73P2582	Leather Carrying Case	10K0209								
Ericsson® GC82 EDGE PC Card Wireless	58P8782	Other options at ibm.com/pc/us/accessories									

See footnotes for important warranty information
US models announced April 6, 2004
US models withdrawn effective October 2004

Type-model	Processor	Speed GHz	Memory	Screen	Disk GB ⁸	Optical	Mini PCI Comm Bay wireless	CDC modem	Ethernet on planar	Security chip	Preload	Workhorse (W) or Global (G) or Entry (E)	Avail date
2684-4YU	Celeron®	1.7	128MB	14.1" XGA	20GB	CD	11b Wi-Fi ³²	Modem	10/100	No	Windows XP Pro	No	Mar 2003
2684-HYU	Celeron	2.0	128MB	14.1" XGA	20GB	CD	11b Wi-Fi	Modem	10/100	No	Windows XP Pro	No	Oct 2003

These educational models of the ThinkPad R40e notebook are available only to public or private K-12 (or higher) accredited schools organized and operated exclusively for educational purposes for use by qualified students and/or teachers.

These models for education are for sale direct from IBM or through an Authorized Education Reseller. The models for education are not available for resale to any other organization or individual.

Positioning	<i>Mainstream performance and features; two-spindle system</i>											
Processor	Mobile Intel® Celeron 1.7 or 2.0GHz with 400MHz system bus											
L2 cache	256KB / on die (at processor speed) / ECC											
Memory	128MB std / 1GB max ⁷ / PC2100 266MHz DDR-SDRAM / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available											
Diskette drive	None standard / use optional USB-based diskette drive											
CD	CD-ROM / 24X-10X ⁹ speed / fixed, not removable											
Ultrabay™ 2000	None											
Disk	20GB⁸ , 4200 rpm, 9.5mm, S.M.A.R.T. / removable and upgradable / 9.5mm high bay											
Display	14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits / easy-open cover to unlatch and open with one hand (two latches)											
Graphics controller	ATI® RADEON™ IGP 330M / integrated in northbridge / 16MB DDR-SDRAM											
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B											
Keyboard	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)											
TrackPoint®	TrackPoint pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass / soft dome TrackPoint cap / ships with classic dome and soft rim TrackPoint cap											
Touch pad	No UltraNav™ multi-pointing system											
ThinkLight™	None											
Dimensions ³	12.3 x 10.0 x 1.53" / 313mm x 254mm x 38.9mm											
Approximate weight ²	with optical drive and battery: 5.9 lb (2.7kg)											
Case material	Color: black; All: Acrylonitrile-Butadiene-Styrene (ABS) plastic											
Battery - type	Lithium Ion 6-cell / intelligent											
Battery - life ¹⁰	Up to 2.1 hrs											
Architecture	ATI RADEON IGP 330M chipset / IGP 330M northbridge (memory controller, graphics controller, PCI bus) / ALi® M1535+ southbridge (ATA-100 EIDE, Low Pin Count [LPC] interface, USB, parallel, audio) / PCI 2.1, 32-bit 33MHz (TI® PCI1510 CardBus controller) / LPC bus 33MHz (PC87392 Super I/O for parallel)											
Port replicator	No port replicator support											
Docking station	No docking station support											
PC Card Std slots	One Type II or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door											
Ports	Two USB (Version 1.1) / parallel / external monitor (DB-15) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial or infrared port											
Video out	None											
IEEE 1394	None											
Wireless antenna	UltraConnect™ Antenna built into the display cover for optimal wireless signal reception											
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable											
11b Wi-Fi ³²	11b Wi-Fi ³² wireless ⁴ , Mini PCI, Intersil® Prism 2.5 chipset											
CDC	One Communications Daughter Card (CDC) socket (used by modem) / not accessible											
Modem	56K ⁶ V.90 (V.92-designed ²³) modem in CDC / Agere® chipset											
Ethernet	10/100 ethernet on planar / Broadcom® BCM5901 (PHY/MAC) / PXE / Wake on LAN®											
Audio support	Soft audio / ICH AC97 controller / DirectSound® support / AD1981B AC97 codec / mono speakers / 1 watt / volume up, down, mute buttons / internal mic / microphone input jack (3.5 mm; mono) / headphone jack (3.5 mm; stereo) / no line in jack											
Security	Power-on password / hard disk password / supervisor password / security keyhole											
Security chip	None											
Limited warranty ¹²	1 year - EasyServ™ ¹⁹ onsite pickup and delivery courier service											
Service options	Service upgrades ²² provide up to five years of onsite or depot repair service coverage from date of ThinkPad purchase (including warranty period)											
128MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028	ThinkPad R40e Li-Ion Battery (6-cell)	08K8218									
256MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030	Multiple Multiple Battery Charger II	22P9040									
512MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032	ThinkPad 72W AC Adapter	02K6699									
30GB Hard Disk 9.5mm (4200 rpm)	09N4268	ThinkPad 72W AC/DC Combo Adapter	22P9010									
40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816	IBM USB Keyboard with UltraNav	31P8950									
IBM 4GB Microdrive™ with PC Card	09N4280	ThinkPad Monitor Stand 2001	22P5265									
IBM 128MB USB 2.0 Memory Key	22P9229	IBM 11a/b/g Wireless CardBus Adapter	31P9101									
IBM 256MB USB 2.0 Memory Key	22P9025	IBM H Rate Wireless LAN PC Card 128	09N9904									
IBM USB Portable Diskette Drive	05K9276	IBM iLM300 MicroPortable Projector	0037A03									
IBM USB Portable CD-ROM	33L5151	IBM iLV200 Value Data/Video Projector	0038A03									
IBM USB 2.0 Portable CD-RW Drive	22P5297	IBM iLC300 Conference Room Projector	0039A03									
Portable 40GB USB 2.0 with Rapid Restore	09N4255	IBM Optical 3-Button Travel Wheel Mouse	31P7410									
IBM USB Serial Parallel Adapter	22P5298	IBM Optical 3-Button ScrollPoint® Mouse	31P7405									
GemPC400 Smart Card Reader/Writer	31P8901	Nylon Carrying Case	10K0207									
IBM Turbo 16/4 Token-Ring PC Card 2	34L1401	Leather Carrying Case	10K0209									
Ericsson® GC82 EDGE PC Card Wireless	58P8782	Other options at ibm.com/pc/us/accessories										
SOFTWARE¹⁴												
Windows XP Pro models												
- Microsoft Windows XP Professional ²⁰												
✧ Disk-to-Disk Recovery (in hidden protected area)												
Preloaded												
• Access IBM												
• Access Connections												
• Adobe Acrobat Reader												
• IBM Rapid Restore™ PC												
• Norton® AntiVirus (OEM edition)												
• PC-Doctor™												
• ThinkPad Utilities												
• IBM Update Connector™ ¹⁵												
Downloadable												
• IBM Director Agent												
• Software Delivery Assistant												
• System Migration Assistant												
License (CD not included)												
- Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client												
Universal 72 watt AC adapter												
PC 2001 and PXE 2.0-compliant												
ACPI 1.0b and 2.0-compliant												
CIM and DMI 2.0-compliant												
IBM Rapid Restore PC available to protect software image and data												
International Warranty Service ¹⁷												
24 hour x 7 day ¹⁸ toll-free hardware support during the warranty ¹²												
ServicePac®. ²² 1yr IOR 9x5 NBD												
30L9188												
ServicePac 2 yr IOR 9x5 NBD												
30L9189												
ServicePac 3 yr IOR 9x5 NBD												
30L9195												
ServicePac 4 yr IOR 9x5 NBD												
30L9194												
ServicePac 5 yr IOR 9x5 NBD												
30L9196												
ServicePac 2 yr P&L P/U Depot												
30L9191												
ServicePac 3 yr P&L P/U Depot												
30L9192												
ServicePac 4 yr P&L P/U Depot												
69P9195												
ServicePac 5 yr P&L P/U Depot												
69P9197												
Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf												
Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf												

See footnotes for important warranty information

US model announced October 7, 2003; previous model on March 25, 2003

US models withdrawn effective October 2003 or April 2004

(R40EE) © IBM Corp. April 2004

Type-model	Processor	Speed GHz	Memory	Screen	Graphics memory	Disk GB ⁵	Optical	Mini PCI Comm Bay wireless	CDC modem	Ethernet on planar	IEEE Security 1394 Chip	Workhorse (W) or Global (G) Avail Preload or Entry (E) date
2681-1AU	Celeron®	1.6	128MB	13.3" XGA	16MB	20G	CD	11a/b Wi-Fi ²⁷	Modem	10/100		XP Pro Jan 2003
2681-28U	Celeron	1.6	128MB	14.1" XGA	16MB	20G	Combo	Open; wireless upg ³⁶	Modem	10/100	1394	XP Pro Jan 2003
2681-37U	Celeron	1.6	128MB	15.0" XGA	16MB	20G	CD	Open; wireless upg	Modem	10/100	1394	XP Pro Jan 2003
2681-C8U	Pentium® 4-M	1.9	128MB	14.1" XGA	16MB	20G	CD	Open; wireless upg	Modem	10/100	1394	XP Pro E Jan 2003
2681-DBU	Pentium 4-M	1.9	256MB	15.0" XGA	16MB	20G	DVD	11a/b Wi-Fi	Modem	10/100		XP Pro Jan 2003
2681-DCU	Pentium 4-M	1.9	256MB	15.0" XGA	16MB	20G	DVD	Open; wireless upg	Modem	10/100	1394	XP Pro Jan 2003
2681-F9U	Pentium 4-M	2.0	256MB	14.1" XGA	16MB	20G	DVD	Open; wireless upg	Modem	10/100	Yes	XP Pro W Jan 2003
2681-FFU	Pentium 4-M	2.0	256MB	14.1" XGA	16MB	40G	Combo	Open; wireless upg	Modem	10/100	1394	XP Pro Jan 2003
2681-FCU	Pentium 4-M	2.0	256MB	14.1" XGA	16MB	40G	DVD	11b Wi-Fi ³²	Modem	10/100	Yes	XP Pro Jan 2003
2681-GMU	Pentium 4-M	2.0	256MB	15.0" XGA	32MB	40G	Combo	Open; wireless upg	Modem	10/100	1394	Yes XP Pro Jan 2003
2681-GHU	Pentium 4-M	2.0	256MB	15.0" XGA	32MB	40G	DVD	Open; wireless upg	Modem	10/100	1394	Yes XP Pro W Jan 2003
2681-K3U	Pentium 4-M	2.2	256MB	15.0" XGA	32MB	40G	DVD	Open; wireless upg	Modem	10/100	1394	Yes XP Pro W Jan 2003
2681-L7U	Pentium 4-M	2.2	256MB	15.0" SXGA+	32M	60G	Combo	Open; wireless upg	Modem	10/100	1394	Yes XP Pro Jan 2003
Positioning Processor	Best blend of portability and essential features; two-spindle system Mobile Intel® Celeron 1.6GHz with 400MHz frontside bus or Mobile Intel Pentium 4 Processor-M 1.9, 2.0, or 2.2GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz frontside bus										SOFTWARE¹⁴ Windows XP Pro models - Microsoft® Windows® XP Professional ²⁰ ♦ Disk-to-Disk Recovery (in hidden protected area) Preloaded • Access IBM • Adobe Acrobat Reader • IBM Rapid Restore™ PC • IBM RecordNOW and DLA by Veritas (combo models) • InterVideo WinDVD (DVD models) • Norton AntiVirus (OEM edition) • PC-Doctor™ • ThinkPad Utilities • IBM Update Connector™ ¹⁵ Downloadable • IBM Director Agent • Software Delivery Assistant • System Migration Assistant • Client Security Software (models with security chip) License (CD not included) - Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client Universal 72 watt AC adapter Asset ID (system-specific info in chip accessed over network) PC 2001 and PXE 2.0-compliant ACPI 1.0b and 2.0-compliant CIM and DMI 2.0-compliant IBM Rapid Restore PC available to protect software image and data International Warranty Service ¹⁷ 24 hour x 7 day ¹⁸ toll-free hardware support during the warranty ¹² ServicePac®. ²² 1yr IOR 9x5 NBD 30L9188 ServicePac 3 yr IOR 9x5 NBD 30L9195 ServicePac 3yr P&L P/U Depot 30L9192 ServicePac 5yr P&L P/U Depot 69P9197 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf IBM 1GB Microdrive™ 07N5574 Cisco Aironet Wireless 802.11b Mini PCI 31P8301 IBM 11a/b/g Wireless Mini PCI Adapter 31P9701 IBM 11a/b/g Wireless CardBus Adapter 31P9101 ThinkPad Travel 72W AC Adapter 02K6699 ThinkPad Port Replicator II 74P6733 ThinkPad Mini Dock 287810U Optical 3-Button Travel Wheel Mouse 31P7410 Other options at ibm.com/pc/us/accessories	
L2 cache	Mobile Intel® Celeron 1.6GHz with 400MHz frontside bus or Mobile Intel Pentium 4 Processor-M 1.9, 2.0, or 2.2GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz frontside bus											
Memory	Celeron: 256KB ; Pentium 4-M: 512KB ; All: on die (at processor speed) / ECC 128 or 256MB std / 1GB max ⁷ / PC2100 266MHz DDR-SDRAM / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available											
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive											
CD	Some: CD-ROM / 24X-10X ⁹ speed / bootable / removable from Ultrabay 2000											
DVD	Some: DVD-ROM / 8X-3.3X ⁹ speed / bootable / removable from Ultrabay 2000											
Combo	Some: DVD-ROM/CD-RW / 24X/10X/24X/8X ²¹ speed / removable from Ultrabay 2000											
Ultrabay 2000	One modular bay for interchangeable devices / Ultrabay Plus -compatible / 12.7 mm high 20GB⁸, 40GB⁸, or 60GB⁸ , 4200 rpm, 9.5mm, S.M.A.R.T. / removable and upgradable / 9.5mm high bay / supports 2nd disk with optional HDD Adapter in Ultrabay 2000											
Disk												
Display	Some: 13.3" (337.8mm) XGA (1024x768) TFT color / Active Matrix / 150 nits / Some: 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits / Some: 15.0" (381mm) XGA (1024x768) TFT color / Active Matrix / 150 nits / Some: 15.0" (381mm) SXGA+ (1400x1050) TFT color / Active Matrix / 150 nits / All: Easy-open cover to unlatch and open with one hand (two latches)											
Graphics controller	Some: ATI® Mobility™ RADEON™ / AGP 4X / 16MB DDR-SDRAM Some: ATI Mobility RADEON 7500 / AGP 4X / 32MB DDR-SDRAM											
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B											
Keyboard	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)											
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass											
Touch pad	UltraNav™ multi-pointing system / touch pad below keyboard / Tap Zones											
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions											
Dimensions ³	13.3/14.1" models: 12.3" x 10" x 1.5"; 15.0" models: 13" x 10.5" x 1.6"											
Approximate weight ²	with optical drive and battery: 13.3" models: 6.2 lb; 14.1" models: 6.0 lb; 15.0": 6.7 lb											
Case material	Color: Black; All: ABS plastic											
Battery - type	Lithium Ion 8-cell / intelligent / supports unique 2nd battery in Ultrabay 2000											
Battery - life ¹⁰	13.3" models: 3.8 hrs; 14.1" models: 3.8 to 4.0 hrs; 15.0" models: 3.4 to 3.6 hrs											
Architecture	Intel 845MP chipset / 82845MP Memory Controller Hub (MCH-M) / 82801DBM ICH4-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB, Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1510 CardBus controller, TSB43AB21 1394 (some), Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared)											
PC Card Std slots	One Type I, one Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door											
Ports	Two USB (Version 2.0) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port											
Video out	S-video out port (TV out) / one industry standard connector											
IEEE 1394	Some: IEEE 1394 (FireWire) port / 4-pin connector											
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable											
11a/b Wi-Fi ²⁷	Some: 11a/b Wi-Fi ²⁷ wireless ⁴ , Mini PCI, Atheros™ AR5001X chipset, UltraConnect™ antenna built in both sides of display, Wi-Fi-certified											
Wireless upg ³⁶	Some: UltraConnect™ antenna built in both sides of display for wireless Mini PCI options											
11b Wi-Fi ³²	Some: 11b Wi-Fi ³² wireless ⁴ , Mini PCI, Intersil® Prism 2.5 chipset, UltraConnect™ antenna built in both sides of display, Wi-Fi-certified											
CDC	One Communications Daughter Card (CDC) socket (used by modem) / not accessible											
Modem	All: 56K ⁶ V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset											
Ethernet	10/100 ethernet on motherboard / Intel 82562EZ chip (physical layer)											
Audio support	Soft audio / ICH AC97 controller / DirectSound® support / AD1891A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal mic / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack											
Security	Power-on password / hard disk password / supervisor password / security keyhole Some: IBM Embedded Security Subsystem 2.0³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant											
Limited warranty ¹²	1 year - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² available											
128MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816									
256MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030	Optical 3-Button Travel Wheel Mouse	31P7410									
512MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032	ThinkPad R32/R40 Series Li-Ion Battery	02K7052									
UltraLight 8X Max DVD Ultrabay 2000	22P9102	Ultrabay 2000 Li-Ion battery	02K6646									
CD-RW/DVD Combo IV Ultrabay 2000	22P6991	ThinkPad Multiple Battery Charger II	22P9040									
Second HDD Adapter for Ultrabay 2000	08K6068	IBM USB Keyboard with UltraNav	31P8950									
ThinkPad Removable Diskette Drive	08K9603	IBM USB 2.0 Portable CD-RW Drive	22P5297									
IBM USB Portable Diskette Drive	05K9276	ThinkPad 72W AC Adapter	02K6699									

See footnotes for important warranty information

Type-model	Processor	Speed GHz	Memory	Screen	Graphics memory	Disk GB ⁵	Optical	Mini PCI Comm Bay wireless	CDC modem	Ethernet on planar	IEEE Security 1394 Chip	Workhorse (W) or Global (G) Avail Preload or Entry (E) date
2681-J7U	Pentium® 4-M	2.2	128MB	14.1" XGA	16MB	30G	CD	Open; wireless upg ³⁶	Modem	10/100	1394	XP Pro E May 2003
2681-J8U	Pentium 4-M	2.2	256MB	14.1" XGA	16MB	40G	Combo	Open; wireless upg	Modem	10/100	1394	XP Pro No May 2003
2681-JCU	Pentium 4-M	2.2	256MB	14.1" XGA	16MB	30G	DVD	Open; wireless upg	Modem	10/100	Yes	XP Pro No May 2003
2681-J9U	Pentium 4-M	2.2	256MB	14.1" XGA	16MB	30G	DVD	Cisco® 802.11b	Modem	10/100	Yes	XP Pro No May 2003
2681-JQU	Pentium 4-M	2.2	256MB	14.1" XGA	16MB	40G	DVD	11b Wi-Fi ³²	Modem	10/100	Yes	XP Pro No May 2003
2681-JDU	Pentium 4-M	2.2	256MB	14.1" XGA	16MB	40G	Combo	11a/b Wi-Fi ²⁷	Modem	10/100	Yes	XP Pro No May 2003
2681-JEU	Pentium 4-M	2.2	256MB	14.1" XGA	16MB	40G	DVD	11a/b Wi-Fi	Modem	10/100	Yes	XP Pro No May 2003
2681-KAU	Pentium 4-M	2.2	256MB	15.0" XGA	32MB	40G	Combo	11a/b Wi-Fi	Modem	10/100	1394 Yes	XP Pro No May 2003
2681-KMU	Pentium 4-M	2.2	256MB	15.0" XGA	32MB	40G	DVD	Cisco 802.11b	Modem	10/100	1394 Yes	XP Pro No May 2003
2681-JHU	Pentium 4-M	2.2	256MB	14.1" XGA	32MB	60G	Combo	Open; wireless upg	Modem	10/100	1394 Yes	XP Pro No May 2003
2681-QCU	Pentium 4-M	2.4	256MB	15.0" SXGA+	32M	60G	Combo	Open; wireless upg	Modem	10/100	1394 Yes	XP Pro No May 2003
2681-KLU	Pentium 4-M	2.2	256MB	15.0" XGA	32MB	40G	Combo	Open; wireless upg	Modem	10/100	1394 Yes	XP Pro No May 2003
2681-KPU	Pentium 4-M	2.2	256MB	15.0" XGA	16MB	20G	DVD	Open; wireless upg	Modem	10/100	1394	XP Pro No May 2003
2681-KQU	Pentium 4-M	2.2	256MB	15.0" XGA	16MB	30G	DVD	11a/b Wi-Fi	Modem	10/100	Yes	XP Pro No May 2003
2681-Q5U	Pentium 4-M	2.4	256MB	15.0" SXGA+	32M	40G	DVD	Open; wireless upg	Modem	10/100	1394 Yes	XP Pro No May 2003
2681-Q6U	Pentium 4-M	2.4	256MB	15.0" SXGA+	32M	60G	Combo	11a/b Wi-Fi	Modem	10/100	1394 Yes	XP Pro No May 2003
Processor	Best blend of portability and essential features; two-spindle system											
L2 cache	Mobile Intel® Pentium 4 Processor-M 2.2 or 2.4GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz frontside bus											
Memory	512KB; All: on die (at processor speed) / ECC											
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive											
CD	Some: CD-ROM / 24X-10X ⁹ speed / bootable / removable from Ultrabay 2000											
DVD	Some: DVD-ROM / 8X-3.3X ⁹ speed / bootable / removable from Ultrabay 2000											
Combo	Some: DVD-ROM/CD-RW / 24X/10X/24X/8X ²¹ speed / removable from Ultrabay 2000											
Ultrabay 2000	One modular bay for interchangeable devices / Ultrabay Plus -compatible / 12.7 mm high											
Disk	20, 30, 40, or 60GB ⁸ , 4200 rpm, 9.5mm, S.M.A.R.T. / removable and upgradable / 9.5mm high bay / supports 2nd disk with optional HDD Adapter in Ultrabay 2000											
Display	Some: 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits											
	Some: 15.0" (381mm) XGA (1024x768) TFT color / Active Matrix / 150 nits											
	Some: 15.0" (381mm) SXGA+ (1400x1050) TFT color / Active Matrix / 150 nits											
	All: Easy-open cover to unlatch and open with one hand (two latches)											
Graphics controller	Some: ATI® Mobility™ RADEON™ / AGP 4X / 16MB DDR-SDRAM											
	Some: ATI Mobility RADEON 7500 / AGP 4X / 32MB DDR-SDRAM											
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B											
Keyboard	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)											
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass											
Touch pad	UltraNav™ multi-pointing system / touch pad below keyboard / Tap Zones											
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions											
Dimensions ³	14.1" models: 12.3" x 10" x 1.5"; 15.0" models: 13" x 10.5" x 1.6"											
Approximate weight ²	with optical drive and battery: 14.1" models: 6.0 lb; 15.0": 6.7 lb											
Case material	Color: Black; All: Acrylonitrile-Butadiene-Styrene (ABS) plastic											
Battery - type	Lithium Ion 8-cell / intelligent / supports unique 2nd battery in Ultrabay 2000											
Battery - life ¹⁰	14.1" models: 3.8 to 4.0 hrs; 15.0" models: 3.4 to 3.6 hrs											
Architecture	Intel 845MP chipset / 82845MP Memory Controller Hub (MCH-M) / 82801DBM ICH4-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB, Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1510 CardBus controller, TSB43AB21 1394 (some), Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared)											
PC Card Std slots	One Type I, one Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door											
Ports	Two USB (Version 2.0) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port											
Video out	S-video out port (TV out) / one industry standard connector											
IEEE 1394	Some: IEEE 1394 (FireWire) port / 4-pin connector											
Wireless antenna	UltraConnect™ Antenna built into the display cover for optimal wireless signal reception											
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable											
Wireless upg ³⁶	Some: Wireless upgradable with wireless Mini PCI options											
11a/b Wi-Fi ²⁷	Some: 11a/b Wi-Fi ²⁷ wireless ⁴ , Mini PCI, Atheros™ AR5001X chipset, UltraConnect™ antenna built in both sides of display, Wi-Fi-certified											
11b Wi-Fi ³²	Some: 11b Wi-Fi ³² wireless ⁴ , Mini PCI, Intel® PrISM 2.5 chipset, UltraConnect™ antenna built in both sides of display, Wi-Fi-certified											
Cisco 802.11b	Some: 802.11b wireless ⁴ , Mini PCI, Cisco® Aironet® Wireless 802.11b, Prism 2.0 chipset, UltraConnect™ antenna built in both sides of display, Wi-Fi-certified											
CDC Modem	One Communications Daughter Card (CDC) socket (used by modem) / not accessible											
Ethernet	All: 56K ⁶ V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset											
Audio support	10/100 ethernet on motherboard / Intel 82562EZ chip (physical layer)											
	Soft audio / ICH AC97 controller / DirectSound® support / AD1891A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal mic / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack											
Security	Power-on password / hard disk password / supervisor password / security keyhole											
	Some: IBM Embedded Security Subsystem 2.0 ³⁵ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant											
Limited warranty ¹²	1 year - EasyServ™.19 onsite pickup and delivery / service upgrades ²² available											
	128MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816								
	256MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030	ThinkPad Multiple Battery Charger II	22P9040								
	512MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032	ThinkPad R32/R40 Series Li-Ion Battery	02K7052								
	CD-RW/DVD Combo IV Ultrabay 2000	22P6991	Ultrabay 2000 Li-Ion battery	02K6646								
												Other options at ibm.com/pc/us/accessories

See footnotes for important warranty information
US models announced May 21, 2003
US models withdrawn effective January 2004

Type-model	Processor	Speed GHz	Memory	Screen	Graphics memory	Disk GB ⁵	Optical	Mini PCI Comm Bay wireless	CDC modem	Ethernet on planar	IEEE 1394 port	Security Chip	Workhorse (W) or Global (G) Avail date
2682-FAU	Pentium® 4-M	2.0	256MB	14.1" XGA	16MB	20G	DVD	Open; wireless upg ³⁶	Modem	10/100			XP Pro W G Jan 2003
2682-F9U	Pentium 4-M	2.0	256MB	14.1" XGA	16MB	20G	DVD	Open; wireless upg	Modem	10/100		Yes	XP Pro W Jan 2003
2682-FEU	Pentium 4-M	2.0	256MB	14.1" XGA	16MB	20G	DVD	Cisco® 802.11b	Modem	10/100		Yes	XP Pro W Jan 2003
2682-K2U	Pentium 4-M	2.2	256MB	15.0" XGA	16MB	40G	DVD	Open; wireless upg	Modem	10/100			XP Pro W G Jan 2003
2682-K4U	Pentium 4-M	2.2	256MB	15.0" XGA	16MB	40G	DVD	Cisco 802.11b	Modem	10/100		Yes	XP Pro W G Jan 2003
2682-GHU	Pentium 4-M	2.0	256MB	15.0" XGA	32MB	40G	DVD	Open; wireless upg	Modem	10/100	1394	Yes	XP Pro W Jan 2003
2682-GLU	Pentium 4-M	2.0	256MB	15.0" XGA	32MB	40G	DVD	Cisco 802.11b	Modem	10/100	1394	Yes	XP Pro W Jan 2003
2682-K3U	Pentium 4-M	2.2	256MB	15.0" XGA	32MB	40G	DVD	Open; wireless upg	Modem	10/100	1394	Yes	XP Pro W Jan 2003
2682-J8U	Pentium 4-M	2.2	256MB	14.1" XGA	16MB	40G	Combo	Open; wireless upg	Modem	10/100	1394		XP Pro May 2003
2682-JAU	Pentium 4-M	2.2	256MB	14.1" XGA	16MB	40G	Combo	Cisco 802.11b	Modem	10/100	1394		XP Pro May 2003

2682 models have a 3 year limited warranty (other 2681 ThinkPad R40 systems have a 1 year limited warranty)

Positioning Processor	Best blend of portability and essential features; two-spindle system Mobile Intel® Pentium 4 Processor-M 2.0, or 2.2GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz frontside bus										SOFTWARE¹⁴		
L2 cache	512KB / on die (at processor speed) / ECC										Windows XP Pro models		
Memory	256MB std / 1GB max ⁷ / PC2100 266MHz DDR-SDRAM / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available										- Microsoft® Windows® XP Professional ²⁰ ♦ Disk-to-Disk Recovery (in hidden protected area)		
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive										Preloaded		
DVD	Some: DVD-ROM / 8X-3.3X ⁹ speed / bootable / removable from Ultrabay 2000										• Access IBM		
Combo	Some: DVD-ROM/CD-RW / 24X/10X/24X/8X ²¹ speed / removable from Ultrabay 2000										- Access Connections		
Ultrabay 2000	One modular bay for interchangeable devices / Ultrabay Plus-compatible / 12.7 mm high										- Access Help		
Disk	20GB ⁹ or 40GB, 4200 rpm, 9.5mm high, S.M.A.R.T. / removable and upgradable / 9.5mm high bay / supports 2nd disk with optional HDD Adapter in Ultrabay 2000										- Access Support		
Display	Some: 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits / Some: 15.0" (381mm) XGA (1024x768) TFT color / Active Matrix / 150 nits / All: Easy-open cover to unlatch and open with one hand (two latches)										• Adobe Acrobat Reader		
Graphics controller	Some: ATI® Mobility™ RADEON™ / AGP 4X / 16MB DDR-SDRAM Some: ATI Mobility RADEON 7500 / AGP 4X / 32MB DDR-SDRAM										• IBM Rapid Restore™ PC		
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B										• IBM RecordNOW and DLA by Veritas (combo models)		
Keyboard	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)										• InterVideo WinDVD (DVD models)		
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass										• Norton AntiVirus (OEM edition)		
Touch pad	UltraNav™ multi-pointing system / touch pad below keyboard / Tap Zones										• PC-Doctor™		
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions										• ThinkPad Utilities		
Dimensions ³	14.1" models: 12.3" x 10" x 1.5"; 15.0" models: 13" x 10.5" x 1.6"										• IBM Update Connector™ ¹⁵		
Approximate weight ²	with optical drive and battery: 14.1" models: 6.0 lb; 15.0" models: 6.7 lb										Downloadable		
Case material	Color: Black; All: Acrylonitrile-Butadiene-Styrene (ABS) plastic										• IBM Director Agent		
Battery - type	Lithium Ion 8-cell / intelligent / supports unique 2nd battery in Ultrabay 2000										• Software Delivery Assistant		
Battery - life ¹⁰	14.1" wireless models: 3.8 hrs; 14.1" non-wireless models: 4.0 hrs; 15" wireless models: 3.4 hrs; 15" non-wireless models: 3.6 hrs										• System Migration Assistant		
Architecture	Intel 845MP chipset / 82845MP Memory Controller Hub (MCH-M) / 82801DBM ICH4-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB, Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1510 CardBus controller, TSB43AB21 1394 (some), Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared)										• Client Security Software (models with security chip)		
PC Card Std slots	One Type I, one Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door										License (CD not included)		
Ports	Two USB (Version 2.0) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port										- Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client		
Video out	S-video out port (TV out) / one industry standard connector										Universal 72 watt AC adapter		
IEEE 1394	Some: IEEE 1394 (FireWire) port / 4-pin connector										Asset ID (system-specific info in chip accessed over network)		
Wireless antenna	UltraConnect™ Antenna built into the display cover for optimal wireless signal reception										PC 2001 and PXE 2.0-compliant		
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable										ACPI 1.0b and 2.0-compliant		
Wireless upg ³⁶	Some: Wireless upgradable with wireless Mini PCI options										CIM and DMI 2.0-compliant		
Cisco 802.11b	Some: 802.11b wireless ⁴ , Mini PCI, Cisco® Aironet® Wireless 802.11b, Prism 2.0 chipset, UltraConnect™ antenna built in both sides of display, Wi-Fi-certified										IBM ImageUltra™ Services available		
CDC	One Communications Daughter Card (CDC) socket (used by modem) / not accessible										IBM Rapid Restore PC available to protect software image and data		
Modem	All: 56K ⁶ V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset										International Warranty Service ¹⁷		
Ethernet	10/100 ethernet on motherboard / Intel 82562EZ chipset (physical layer)										24 hour x 7 day ¹⁸ toll-free hardware support during the warranty ¹²		
Audio support	Soft audio / ICH AC97 controller / DirectSound® support / AD1891A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal mic / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack										ServicePac®. ²² 2 yr IOR 9x5 NBD 30L9190		
Security	Power-on password / hard disk password / supervisor password / security keyhole Some: IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant										ServicePac 3 yr IOR 9x5 NBD 30L9197		
Limited warranty ¹²	3 years/1 year battery - EasyServ™ ¹⁹ onsite pickup and delivery										ServicePac 4 yr IOR 9x5 NBD 69P9198		
128MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028			ThinkPad R32/R40 Series Li-Ion Battery 02K7052							ServicePac 5 yr IOR 9x5 NBD 69P9200		
256MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030			Ultrabay 2000 Li-Ion battery 02K6646							ServicePac 4 yr P&L P/U Depot 69P9199		
512MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032			ThinkPad Multiple Battery Charger II 22P9040							ServicePac 5 yr P&L P/U Depot 69P9201		
CD-RW/DVD Combo IV Ultrabay 2000	22P6991			40GB HS Hard Disk 9.5mm (5400 rpm) 08K9816							Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf		
24X-10X CD-ROM Ultrabay 2000 Drive	05K9233			GemPC400 Smart Card Reader/Writer 31P8901							Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
Second HDD Adapter for Ultrabay 2000	08K6068			Cisco Aironet Wireless 802.11b Mini PCI 31P8301									
ThinkPad Multi-Burner Ultrabay 2000 Drive	22P7015			IBM 11a/b/g Wireless Mini PCI Adapter 31P9701									
ThinkPad Removable Diskette Drive	08K9603			IBM 11a/b/g Wireless CardBus Adapter 31P9101									
IBM USB Portable Diskette Drive	05K9276			ThinkPad 72W AC Adapter 02K6699									
IBM USB 2.0 Portable CD-RW Drive	22P5297			ThinkPad 72W AC/DC Combo Adapter 22P9010									
IBM USB Serial Parallel Adapter	22P5298			ThinkPad Port Replicator II 74P6733									
IBM iLV200 Value Data/Video Projector	0038A03			ThinkPad Mini Dock 287810U									
IBM Optical 3-Button Travel Wheel Mouse	31P7410			Other options at ibm.com/pc/us/accessories									

See footnotes for important warranty information
US models announced on January 28 or May 21, 2003
US models withdrawn effective January 2004

Type-model	Processor	Speed GHz	Memory	Screen	Graphics memory	Disk GB ³	Optical	Mini PCI Comm Bay wireless	CDC modem	Ethernet on planar	IEEE Security 1394 Chip	Small and medium business	Avail date		
2896-4WU	Celeron®	1.8	256MB	14.1" XGA	16MB	20GB	DVD	Open; wireless upg ³⁶	Modem	10/100	Yes	XP Pro	Yes	May 2003	
2896-5WU	Celeron	1.8	256MB	15.0" XGA	16MB	20GB	DVD	Open; wireless upg	Modem	10/100	Yes	XP Pro	Yes	May 2003	
2896-FZU	Pentium® 4-M	2.0	256MB	14.1" XGA	16MB	20GB	DVD	Open; wireless upg	Modem	10/100	Yes	XP Pro	Yes	May 2003	
2896-GZU	Pentium 4-M	2.0	256MB	15.0" XGA	32MB	20GB	DVD	Open; wireless upg	Modem	10/100	1394	Yes	XP Pro	Yes	May 2003

These small and medium business (SMB) models are part of the IBM US ThinkPad Express Program

Positioning Processor	Best blend of portability and essential features; two-spindle system Mobile Intel® Celeron 1.8GHz with 400MHz frontside bus or Mobile Intel Pentium 4 Processor-M 2.0GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz frontside bus										SOFTWARE¹⁴		
L2 cache Memory	Celeron: 256KB ; Pentium 4-M: 512KB ; All: on die (at processor speed) / ECC 256MB std / 1GB max ⁷ / PC2100 266MHz DDR-SDRAM / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available										Windows XP Pro models - Microsoft® Windows® XP Professional ²⁰ ♦ Disk-to-Disk Recovery (in hidden protected area)		
Diskette drive DVD Ultrabay 2000 Disk	None standard / use optional Ultrabay™-based or USB-based diskette drive DVD-ROM / 8X-3.3X ⁹ speed / bootable / removable from Ultrabay 2000 One modular bay for interchangeable devices / Ultrabay Plus -compatible / 12.7 mm high 20GB⁸ , 4200 rpm, 9.5mm, S.M.A.R.T. / removable and upgradable / 9.5mm high bay / supports 2nd disk with optional HDD Adapter in Ultrabay 2000										Preloaded • Access IBM • Adobe Acrobat Reader • IBM Rapid Restore™ PC • InterVideo WinDVD (DVD models) • Norton AntiVirus (OEM edition) • PC-Doctor™ • ThinkPad Utilities • IBM Update Connector™ ¹⁵		
Display	Some: 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits Some: 15.0" (381mm) XGA (1024x768) TFT color / Active Matrix / 150 nits All: Easy-open cover to unlatch and open with one hand (two latches)										Downloadable • IBM Director Agent • Software Delivery Assistant • System Migration Assistant • Client Security Software (for security chip)		
Graphics controller	Some: ATI® Mobility™ RADEON™ / AGP 4X / 16MB DDR-SDRAM Some: ATI Mobility RADEON 7500 / AGP 4X / 32MB DDR-SDRAM										License (CD not included) - Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client		
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B										Universal 72 watt AC adapter Asset ID (system-specific info in chip accessed over network) PC 2001 and PXE 2.0-compliant ACPI 1.0b and 2.0-compliant CIM and DMI 2.0-compliant IBM Rapid Restore PC available to protect software image and data International Warranty Service ¹⁷ 24 hour x 7 day ¹⁸ toll-free hardware support during the warranty ¹²		
Keyboard TrackPoint® Touch pad ThinkLight™	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys) TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass UltraNav™ multi-pointing system / touch pad below keyboard / Tap Zones Illuminates the keyboard to improve visibility in low-light conditions										ServicePac®. ²² 1yr IOR 9x5 NBD 30L9188		
Dimensions ³	14.1" models (WxDxH): 12.3" x 10" x 1.5"; 313mm x 254mm x 38.9mm 15.0" models (WxDxH): 13" x 10.5" x 1.6"; 329mm x 267.5mm x 40.5mm										ServicePac 2 yr IOR 9x5 NBD 30L9189		
Approximate weight ² Case material	with optical drive and battery: 14.1" models: 6.0 lb (2.8kg); 15.0": 6.7 lb (3.1kg) Color: Black; All: Acrylonitrile-Butadiene-Styrene (ABS) plastic										ServicePac 3 yr IOR 9x5 NBD 30L9195		
Battery - type Battery - life ¹⁰	Lithium Ion 8-cell / intelligent / supports unique 2nd battery in Ultrabay 2000 14.1" models: 3.8 to 4.0 hrs; 15.0" models: 3.4 to 3.6 hrs										ServicePac 4 yr IOR 9x5 NBD 30L9194		
Architecture	Intel 845MP chipset / 82845MP Memory Controller Hub (MCH-M) / 82801DBM ICH4-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB, Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1510 CardBus controller, TSB43AB21 1394 (some), Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared)										ServicePac 5 yr IOR 9x5 NBD 30L9196		
PC Card Std slots Ports	One Type I, one Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door Two USB (Version 2.0) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port										ServicePac 2 yr P&L P/U Depot 30L9191		
Video out IEEE 1394 Wireless antenna Mini PCI Wireless upg ³⁶ CDC Modem Ethernet Audio support	S-video out port (TV out) / one industry standard connector Some: IEEE 1394 (FireWire) port / 4-pin connector UltraConnect™ Antenna built into the display cover for optimal wireless signal reception One Mini PCI type III slot (Communications Bay) / customer upgradable Wireless upgradable with wireless Mini PCI options One Communications Daughter Card (CDC) socket (used by modem) / not accessible 56K ⁶ V.90 (V.92-designed ²⁵) modem in CDC / Agere® chipset 10/100 ethernet on motherboard / Intel 82562EZ chip (physical layer) Soft audio / ICH AC97 controller / DirectSound® support / AD1891A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal mic / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack										ServicePac 3 yr P&L P/U Depot 30L9192		
Security	Power-on password / hard disk password / supervisor password / security keyhole IBM Embedded Security Subsystem 2.0³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant										ServicePac 4 yr P&L P/U Depot 69P9195		
Limited warranty ¹²	1 year - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² available										ServicePac 5 yr P&L P/U Depot 69P9197		
128MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028	ThinkPad R32/R40 Series Li-Ion Battery								02K7052	Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
256MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030	Ultrabay 2000 Li-Ion battery								02K6646			
512MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032	ThinkPad Multiple Battery Charger II								22P9040			
UltraLight 8X Max DVD Ultrabay 2000	22P9102	IBM USB Keyboard with UltraNav								31P8950			
CD-RW/DVD Combo IV Ultrabay 2000	22P6991	40GB HS Hard Disk 9.5mm (5400 rpm)								08K9816			
24X-10X CD-ROM Ultrabay 2000 Drive	05K9233	GemPC400 Smart Card Reader/Writer								31P8901			
Second HDD Adapter for Ultrabay 2000	08K6068	ThinkPad Monitor Stand 2001								22P5265			
ThinkPad Multi-Burner Ultrabay 2000 Drive	22P7015	Cisco Aironet Wireless 802.11b Mini PCI								31P8301			
ThinkPad Removable Diskette Drive	08K9603	IBM 11a/b/g Wireless Mini PCI Adapter								31P9701			
IBM USB Portable Diskette Drive	05K9276	IBM 11a/b/g Wireless CardBus Adapter								31P9101			
IBM USB 2.0 Portable CD-RW Drive	22P5297	ThinkPad 72W AC Adapter								02K6699			
IBM USB Serial Parallel Adapter	22P5298	ThinkPad 72W AC/DC Combo Adapter								22P9010			
Optical 3-Button Travel Wheel Mouse	31P7410	ThinkPad Port Replicator II								74P6733			
IBM iLV200 Value Data/Video Projector	0038A03	ThinkPad Mini Dock								287810U			
IBM ThinkPad Ultrabay Plus Carrier	22P5737	IBM 1GB Microdrive™ with PC Card								07N5574			
IBM ThinkPad Ultrabay Plus c500 Cradle	22P5738	IBM Optical 3-Button Travel Wheel Mouse								31P7410			
ThinkPad Ultrabay Plus Numeric Keypad	22P7330	Other options at ibm.com/pc/us/accessories											

See footnotes for important warranty information
US models announced April 22, 2003
US models withdrawn effective October 2003

IBM® ThinkPad® R40 (2896) - Express (October 2003) - withdrawn

Created by IBM PC Institute
Personal Systems Reference (PSREF)

Type-model	Processor	Speed GHz	Memory	Screen	Graphics memory	Disk GB ²	Optical	Mini PCI Comm Bay wireless	CDC modem	Ethernet on planar	IEEE 1394 port	Security chip	Preload	Avail date
2896-72U	Celeron®	2.0	256MB	15.0" XGA	16MB	30GB	Combo	Open; wireless upg ³⁶	Modem	10/100	1394	Yes	XP Pro	Oct 2003
2896-J2U	Pentium® 4-M	2.2	256MB	14.1" XGA	32MB	30GB	CD	Open; wireless upg	Modem	10/100	1394	Yes	XP Pro	Oct 2003
2896-J3U	Pentium 4-M	2.2	256MB	14.1" XGA	32MB	40GB	Combo	Open; wireless upg	Modem	10/100	1394	Yes	XP Pro	Oct 2003
2896-J4U	Pentium 4-M	2.2	256MB	14.1" XGA	32MB	60GB	Combo	11a/b Wi-Fi ²⁷	Modem	10/100	1394	Yes	XP Pro	Oct 2003
2896-N2U	Pentium 4-M	2.4	256MB	14.1" XGA	32MB	30GB	CD	Open; wireless upg	Modem	10/100	1394	Yes	XP Pro	Oct 2003
2896-N3U	Pentium 4-M	2.4	256MB	14.1" XGA	32MB	40GB	Combo	Open; wireless upg	Modem	10/100	1394	Yes	XP Pro	Oct 2003
2896-N4U	Pentium 4-M	2.4	256MB	14.1" XGA	32MB	60GB	Combo	11a/b Wi-Fi ²⁷	Modem	10/100	1394	Yes	XP Pro	Oct 2003
2896-Q3U	Pentium 4-M	2.4	256MB	15.0" SXGA+	32MB	40GB	Combo	Open; wireless upg	Modem	10/100	1394	Yes	XP Pro	Oct 2003
2896-Q4U	Pentium 4-M	2.4	256MB	15.0" SXGA+	32MB	60GB	Combo	11a/b Wi-Fi ²⁷	Modem	10/100	1394	Yes	XP Pro	Oct 2003
2896-P2U	Pentium 4-M	2.4	256MB	15.0" XGA	32MB	30GB	CD	Open; wireless upg	Modem	10/100	1394	Yes	XP Pro	Oct 2003
2896-P3U	Pentium 4-M	2.4	256MB	15.0" XGA	32MB	40GB	Combo	Open; wireless upg	Modem	10/100	1394	Yes	XP Pro	Oct 2003
These small and medium business (SMB) models are part of the IBM US Think Express Program														
Positioning	Mainstream performance and features; two-spindle system										SOFTWARE¹⁴			
Processor	Mobile Intel® Celeron 2.0GHz with 400MHz system bus or Mobile Intel Pentium 4 Processor-M 2.2 or 2.4GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz system bus										Windows XP Pro models - Microsoft® Windows® XP Professional ²⁰ ♦ Disk-to-Disk Recovery (in hidden protected area)			
L2 cache	Celeron: 256KB; Pentium 4-M: 512KB; All: on die (at processor speed) / ECC													
Memory	256MB std / 1GB max ⁷ / PC2100 266MHz DDR1 (DDR-SDRAM) / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available										Preloaded • Access IBM • Access Connections • Adobe Acrobat Reader • IBM Rapid Restore™ PC • InterVideo WinDVD (combo models) • IBM RecordNow and DLA by Veritas (combo models) • Norton AntiVirus (OEM edition) • PC-Doctor™ • ThinkPad Utilities • IBM Update Connector™ ¹⁵			
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive													
CD	Some: CD-ROM / 24X-10X ⁹ speed / bootable / removable from Ultrabay 2000										Downloadable • IBM Director Agent • Software Delivery Assistant • System Migration Assistant • Client Security Software (for security chip)			
Combo	Some: DVD-ROM/CD-RW / 24X/10X/24X/8X ²¹ speed / removable from Ultrabay 2000													
Ultrabay 2000	One modular bay for interchangeable devices / Ultrabay Plus-compatible / 12.7 mm high										License (CD not included) - Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client			
Disk	30GB ⁸ , 40GB, or 60GB / 4200 rpm, 9.5mm, S.M.A.R.T. / removable and upgradable / 9.5mm high bay / supports 2nd disk with optional HDD Adapter in Ultrabay 2000													
Display	Some: 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits Some: 15.0" (381.0mm) XGA (1024x768) TFT color / Active Matrix / 150 nits Some: 15.0" (381.0mm) SXGA+ (1450x1050) TFT color / Active Matrix / 150 nits										Universal 72 watt AC adapter Asset ID (system-specific info in chip accessed over network) PC 2001 and PXE 2.0-compliant ACPI 1.0b and 2.0-compliant CIM and DMI 2.0-compliant IBM Rapid Restore PC available to protect software image and data International Warranty Service ¹⁷ 24 hour x 7 day ¹⁸ toll-free warranty support during the warranty ¹² via 800-IBM-SERV (426-7378)			
Graphics controller	Some: ATI® Mobility™ RADEON™ / AGP 4X / 16MB DDR1 (DDR-SDRAM) Some: ATI Mobility RADEON 7500 / AGP 4X / 32MB DDR1 (DDR-SDRAM)													
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B										ServicePac®. ²² 1yr IOR 9x5 NBD 30L9188 ServicePac 2 yr IOR 9x5 NBD 30L9189 ServicePac 3 yr IOR 9x5 NBD 30L9195 ServicePac 4 yr IOR 9x5 NBD 30L9194 ServicePac 5 yr IOR 9x5 NBD 30L9196 ServicePac 2 yr P&L P/U Depot 30L9191 ServicePac 3 yr P&L P/U Depot 30L9192 ServicePac 4 yr P&L P/U Depot 69P9195 ServicePac 5 yr P&L P/U Depot 69P9197			
Keyboard	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)													
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass										Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf			
Touch pad	UltraNav™ multi-pointing system / touch pad below keyboard / Tap Zones													
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions										Limited warranty ¹² 1 year - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² available			
Dimensions ³	14.1" models (WxDxH): 12.3" x 10" x 1.5"; 313mm x 254mm x 38.9mm 15.0" models (WxDxH): 13" x 10.5" x 1.6"; 329mm x 267.5mm x 40.5mm													
Approximate weight ²	with optical drive and batt: 14.1" models: 6.0 to 6.1 lb (2.7kg); 15.0": 6.6 to 6.7 lb (3.0kg)										See footnotes for important warranty information US models announced October 7, 2003 US models withdrawn effective April 2004 or October 2004			
Case material	Color: black; All: Acrylonitrile-Butadiene-Styrene (ABS) plastic													
Battery - type	Lithium Ion 8-cell / intelligent / supports unique 2nd battery in Ultrabay 2000										128MB PC2100 DDR-SDRAM CL2.5 SOD 10K0028 ThinkPad R32/R40 Series Li-Ion Battery 02K7052 256MB PC2100 DDR-SDRAM CL2.5 SOD 10K0030 Ultrabay 2000 Li-Ion battery 02K6646 512MB PC2100 DDR-SDRAM CL2.5 SOD 10K0032 ThinkPad Multiple Battery Charger II 22P9040 CD-RW/DVD Combo IV Ultrabay 2000 22P6991 40GB HS Hard Disk 9.5mm (5400 rpm) 08K9816 Ultralight 8X Max DVD Ultrabay 2000 22P9102 80GB HS Hard Disk 9.5mm (5400 rpm) 09N4273 Second HDD Adapter for Ultrabay 2000 08K6068 Cisco Aironet Wireless 802.11b Mini PCI 31P8301 Multi-Burner Plus Ultrabay Enhanced Drive 73P3312 IBM 11a/b/g Wireless Mini PCI Adapter 31P9701 ThinkPad Slim Drive Adpr for Ultrabay 2000 62P4557 IBM 11a/b/g Wireless CardBus Adapter 31P9101 ThinkPad Removable Diskette Drive 08K9603 ThinkPad 72W AC/DC Combo Adapter 22P9010 IBM USB Portable Diskette Drive 05K9276 ThinkPad Port Replicator II 74P6733 IBM USB 2.0 Portable Multi-Burner Drive 22P9163 ThinkPad Mini Dock 287810U ThinkPad 72W AC Adapter 02K6699 Other options at ibm.com/pc/us/accessories			
Battery - life ¹⁰	14.1" and 15" XGA models: 3.8 to 4.0 hrs; 15.0" SXGA+ models: 3.4 to 3.6 hrs													
Architecture	Intel 845MP chipset / 82845MP Memory Controller Hub (MCH-M) / 82801DBM ICH4-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB, Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1510 CardBus controller, TSB43AB21 1394 (some), Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared)										PC Card Std slots One Type I, one Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door			
PC Card Std slots	One Type I, one Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door													
Ports	Two USB (Version 2.0) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port										Video out S-video out port (TV out) / one 4-pin industry standard connector IEEE 1394 IEEE 1394 (FireWire) port / 4-pin connector Wireless antenna UltraConnect™ Antenna built into the display cover for optimal wireless signal reception Mini PCI One Mini PCI type III slot (Communications Bay) / customer upgradable Wireless upg ³⁶ Some: wireless upgradable with wireless Mini PCI options 11a/b Wi-Fi ²⁷ Some: 11a/b Wi-Fi ²⁷ wireless ⁴ , Mini PCI, Atheros™ AR5001X chipset CDC One Communications Daughter Card (CDC) socket (used by modem) / not accessible Modem 56K ⁶ V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset Ethernet 10/100 ethernet on motherboard / Intel 82562EZ chip (physical layer) Audio support Soft audio / ICH AC97 controller / DirectSound® support / AD1891A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal mic / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack Security Power-on password / hard disk password / supervisor password / security keyhole Some: IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant			
Video out	S-video out port (TV out) / one 4-pin industry standard connector													
IEEE 1394	IEEE 1394 (FireWire) port / 4-pin connector										ServicePac 2 yr P&L P/U Depot 30L9192 ServicePac 4 yr P&L P/U Depot 69P9195 ServicePac 5 yr P&L P/U Depot 69P9197			
Wireless antenna	UltraConnect™ Antenna built into the display cover for optimal wireless signal reception													
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable										Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf			
Wireless upg ³⁶	Some: wireless upgradable with wireless Mini PCI options													
11a/b Wi-Fi ²⁷	Some: 11a/b Wi-Fi ²⁷ wireless ⁴ , Mini PCI, Atheros™ AR5001X chipset										Limited warranty ¹² 1 year - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² available			
CDC	One Communications Daughter Card (CDC) socket (used by modem) / not accessible													
Modem	56K ⁶ V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset										See footnotes for important warranty information US models announced October 7, 2003 US models withdrawn effective April 2004 or October 2004			
Ethernet	10/100 ethernet on motherboard / Intel 82562EZ chip (physical layer)													
Audio support	Soft audio / ICH AC97 controller / DirectSound® support / AD1891A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal mic / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack										Limited warranty ¹² 1 year - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² available			
Security	Power-on password / hard disk password / supervisor password / security keyhole Some: IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant													
Limited warranty ¹²	1 year - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² available										See footnotes for important warranty information US models announced October 7, 2003 US models withdrawn effective April 2004 or October 2004			
128MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028 ThinkPad R32/R40 Series Li-Ion Battery 02K7052													
256MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030 Ultrabay 2000 Li-Ion battery 02K6646										Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf			
512MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032 ThinkPad Multiple Battery Charger II 22P9040													
CD-RW/DVD Combo IV Ultrabay 2000	22P6991 40GB HS Hard Disk 9.5mm (5400 rpm) 08K9816										Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf			
Ultralight 8X Max DVD Ultrabay 2000	22P9102 80GB HS Hard Disk 9.5mm (5400 rpm) 09N4273													
Second HDD Adapter for Ultrabay 2000	08K6068 Cisco Aironet Wireless 802.11b Mini PCI 31P8301										Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf			
Multi-Burner Plus Ultrabay Enhanced Drive	73P3312 IBM 11a/b/g Wireless Mini PCI Adapter 31P9701													
ThinkPad Slim Drive Adpr for Ultrabay 2000	62P4557 IBM 11a/b/g Wireless CardBus Adapter 31P9101										Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf			
ThinkPad Removable Diskette Drive	08K9603 ThinkPad 72W AC/DC Combo Adapter 22P9010													
IBM USB Portable Diskette Drive	05K9276 ThinkPad Port Replicator II 74P6733										Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf			
IBM USB 2.0 Portable Multi-Burner Drive	22P9163 ThinkPad Mini Dock 287810U													
ThinkPad 72W AC Adapter	02K6699 Other options at ibm.com/pc/us/accessories										See footnotes for important warranty information US models announced October 7, 2003 US models withdrawn effective April 2004 or October 2004			

See footnotes for important warranty information
US models announced October 7, 2003
US models withdrawn effective April 2004 or October 2004

IBM® ThinkPad® R40 (2897) - Express - withdrawn

Created by IBM PC Institute
Personal Systems Reference (PSREF)

Type-model	Processor	Speed GHz	Memory	Screen	Graphics memory GB ⁸	Disk GB ⁹	Optical	Mini PCI Comm Bay wireless	CDC modem/ Bluetooth™	Ethernet on planar	IEEE Security 1394 Chip	Small and medium business	Avail date
2897-22U	Pentium® M1.3	256MB	14.1" XGA	16MB 20G DVD	Open; wireless upg ³⁶	Modem	10/100	1394	Yes	XP Pro	Yes	May 2003	
2897-23U	Pentium M 1.3	256MB	14.1" XGA	16MB 20G Combo	*Intel 11b Wi-Fi ³²	Modem	10/100	1394	Yes	XP Pro	Yes	May 2003	
2897-34U	Pentium M 1.3	256MB	14.1" XGA	32MB 40G Combo	*Intel 11b Wi-Fi	Modem	10/100	1394	Yes	XP Pro	Yes	May 2003	
2897-55U	Pentium M 1.3	256MB	15.0" XGA	32MB 40G Combo	Open; wireless upg	Modem	10/100	1394	Yes	XP Pro	Yes	May 2003	
2897-54U	Pentium M 1.3	256MB	15.0" XGA	32MB 40G Combo	*Intel 11b Wi-Fi	Modem	10/100	1394	Yes	XP Pro	Yes	May 2003	
2897-GWU	Pentium M 1.5	256MB	15.0" SXGA+	32MB 60G Combo	11a/b Wi-Fi ²⁷	Modem	10/100	1394	Yes	XP Pro	Yes	May 2003	
2897-93U	Pentium M 1.4	256MB	14.1" XGA	16MB 20G Combo	*Intel 11b Wi-Fi	Modem	10/100	1394	Yes	XP Pro	Yes	Oct 2003	
2897-B4U	Pentium M 1.4	256MB	15.0" XGA	32MB 40G Combo	*Intel 11b Wi-Fi	Modem	10/100	1394	Yes	XP Pro	Yes	Oct 2003	
2897-GAU	Pentium M 1.5	256MB	15.0" SXGA+	32MB 60G Combo	*Intel 11b Wi-Fi	Modem	10/100	1394	Yes	XP Pro	Yes	Oct 2003	
2897-83U	Pentium M 1.4	256MB	15.0" XGA	16MB 20G Combo	*Intel 11b Wi-Fi	Modem	10/100	1394	Yes	XP Pro	Yes	Nov 2003	

These small and medium business (SMB) models are part of the IBM US Think Express Program

Positioning	Mainstream performance and features; two-spindle system										SOFTWARE¹⁴		
Processor	Intel® Pentium® M Processor 1.3, 1.4, or 1.5GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz system bus										Windows XP Pro models		
L2 cache	1MB / on die (at processor speed) / ECC										- Microsoft® Windows® XP Professional ²⁰		
Memory	256MB std / 2GB max ⁷ / PC2100 266MHz DDR1 (DDR-SDRAM) / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available										◆ Disk-to-Disk Recovery (in hidden protected area)		
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive										Preloaded		
DVD	Some: DVD-ROM / 8X-3.3X ⁹ speed / bootable / removable from Ultrabay 2000										• Access IBM		
Combo	Some: DVD-ROM/CD-RW / 24X/10X/24X/8X ²¹ speed / removable from Ultrabay 2000										- Access Connections		
Ultrabay 2000	One modular bay for interchangeable devices / Ultrabay Plus-compatible / 12.7 mm high										• Adobe Acrobat Reader		
Disk	20GB ⁸ , 40GB, or 60GB, 4200 rpm, 9.5mm / removable and upgradable / 9.5mm high bay / supports 2nd disk with optional HDD Adapter in Ultrabay 2000										• IBM Rapid Restore™ PC		
Display	Some: 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits										• IBM RecordNOW and DLA by Veritas (combo models)		
	Some: 15.0" (381.0mm) XGA (1024x768) TFT color / Active Matrix / 150 nits										• InterVideo WinDVD (Combo, DVD)		
	Some: 15.0" (381.0mm) SXGA+ (1400x1050) TFT color / Active Matrix / 150 nits										• Norton AntiVirus (OEM edition)		
Graphics controller	Some: ATI® Mobility™ RADEON™ / AGP 4X / 16MB DDR1 (DDR-SDRAM)										• PC-Doctor™		
	Some: ATI Mobility RADEON 7500 / AGP 4X / 32MB DDR1 (DDR-SDRAM)										• ThinkPad Utilities		
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B										• IBM Update Connector™ ¹⁵		
Keyboard	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)										Downloadable		
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass										• IBM Director Agent		
Touch pad	UltraNav™ multi-pointing system / touch pad below keyboard / Tap Zones										• Software Delivery Assistant		
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions										• System Migration Assistant		
Dimensions ³	14.1" models: 12.3" x 10.0" x 1.53"; 15.0" models: 13.0" x 10.5" x 1.59"										• Client Security Software (for security chip)		
Approximate weight ²	with optical drive and battery: 14.1" models: 6.1 to 6.7 lb; 15.0": 6.6 to 6.7 lb (3.0 to 3.4kg)										License (CD not included)		
Case material	Color: Black; All: Acrylonitrile-Butadiene-Styrene (ABS) plastic										- Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client		
Battery - type	Lithium Ion 8-cell / intelligent / supports unique 2nd battery in Ultrabay 2000												
Battery - life ¹⁰	6.1 to 6.2 hr												
Architecture	Intel 855PM chipset / 82855PM Memory Controller Hub (MCH-M) / 82801DBM ICH4-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB, Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1510 CardBus controller, TSB43AB21 1394 (some), Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared)										Universal 72 watt AC adapter		
PC Card Std slots	One Type I, one Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door										Asset ID™ ³⁴ (system-specific info in chip accessed over network)		
Ports	Two USB (Version 2.0) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port										PC 2001 and PXE 2.0-compliant		
Video out	S-video out port (TV out) / one 4-pin industry standard connector										ACPI 1.0b and 2.0-compliant		
IEEE 1394	IEEE 1394 (FireWire) port / 4-pin connector										CIM and DMI 2.0-compliant		
Wireless antenna	UltraConnect™ Antenna built into the display cover for optimal wireless signal reception										IBM Rapid Restore PC available to protect software image and data		
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable										International Warranty Service ¹⁷		
Wireless upg ³⁶	Some: Wireless upgradable with wireless Mini PCI options										24 hour x 7 day ¹⁸ toll-free warranty support during the warranty ¹² via 800-IBM-SERV (426-7378)		
11b Wi-Fi ³²	Some: 11b Wi-Fi ³² wireless ⁴ , Mini PCI, Intel PRO/Wireless 2100 Network Connection 802.11b, Intel 82531 chipset										ServicePac®. ²² 1yr IOR 9x5 NBD 30L9188		
11a/b Wi-Fi ²⁷	Some: 11a/b Wi-Fi ²⁷ wireless ⁴ , Mini PCI, Atheros™ AR5001X chipset										ServicePac 2 yr IOR 9x5 NBD 30L9189		
CDC	One Communications Daughter Card (CDC) socket (used by modem) / not accessible										ServicePac 3 yr IOR 9x5 NBD 30L9195		
Modem	56K ⁶ V.90 (V.92-designed ²⁵) modem in CDC / Agere® chipset										ServicePac 4 yr IOR 9x5 NBD 30L9194		
Bluetooth™	None										ServicePac 5 yr IOR 9x5 NBD 30L9196		
Ethernet	10/100 ethernet on motherboard / Intel 82562EZ chip (physical layer) / PXE										ServicePac 2 yr P&L P/U Depot 30L9191		
Audio support	Soft audio / ICH AC97 controller / DirectSound® support / AD1891A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal mic / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack										ServicePac 3 yr P&L P/U Depot 30L9192		
Security	Power-on password / hard disk password / supervisor password / security keyhole										ServicePac 4 yr P&L P/U Depot 69P9195		
Security chip	IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant										ServicePac 5 yr P&L P/U Depot 69P9197		
Limited warranty ¹²	1 year - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² available										Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf		
128 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028	ThinkPad Port Replicator II	74P6733										
256 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030	ThinkPad Mini Dock	287810U										
512 MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816										
1GB PC2100 DDR-SDRAM CL2.5 SOD	10K0034	80GB HS Hard Disk 9.5mm (5400 rpm)	09N4273										
CD-RW/DVD Combo IV Ultrabay 2000	22P6991	ThinkPad R32/R40 Series Li-Ion Battery	02K7052										
Second HDD Adapter for Ultrabay 2000	08K6068	Ultrabay 2000 Li-Ion battery	02K6646										
ThinkPad Removable Diskette Drive	08K9603	ThinkPad Multiple Battery Charger II	22P9040										
IBM USB Portable Diskette Drive	05K9276	IBM 11a/b/g Wireless CardBus Adapter	31P9101										
IBM 4GB Microdrive™ with PC Card	09N4280	IBM 11a/b/g Wireless Mini PCI Adapter	31P9701										
IBM 256MB USB 2.0 Memory Key	22P9025	Cisco Aironet Wireless 802.11b Mini PCI	31P8301										
ThinkPad 72W AC Adapter	02K6699	Ericsson® GC82 EDGE PC Card Wireless	58P8782										
ThinkPad 72W AC/DC Combo Adapter	22P9010	Other options at ibm.com/pc/us/accessories											

See footnotes for important warranty information

* Powered by Intel Centrino™ mobile technology

(R40MB) © IBM Corp. October 2004

US models announced April 22, October 21, or November 11, 2003

US models withdrawn effective October 2003 or January 2004 or October 2004

IBM® ThinkPad® R40 (2723) - Education - withdrawn

Created by IBM PC Institute
Personal Systems Reference (PSREF)

Type-model	Processor	Speed GHz	Memory	Screen	Graphics memory	Disk GB ⁵	Optical	Mini PCI Comm Bay wireless	Ethernet on planar	CDC modem	IEEE 1394 port	Security Chip	Workhorse (W) Global (G) Avail date
2723-3XU	Pentium® M	1.3	256MB	14.1" XGA	32MB	40GB	Combo	*Intel 11b Wi-Fi ³²	Modem	10/100	1394	Yes	XP Pro W Mar 2003
2723-3PU	Pentium M	1.3	256MB	14.1" XGA	32MB	40GB	Combo	11a/b Wi-Fi ²⁷	Modem	10/100	1394	Yes	XP Pro W Mar 2003
2723-6XU	Pentium M	1.3	256MB	15.0" SXGA+	32MB	40GB	Combo	*Intel 11b Wi-Fi	Modem	10/100	1394	Yes	XP Pro W Mar 2003
2723-6PU	Pentium M	1.3	256MB	15.0" SXGA+	32MB	40GB	Combo	11a/b Wi-Fi	Modem	10/100	1394	Yes	XP Pro W Mar 2003
2723-BDU	Pentium M	1.4	256MB	15.0" XGA	32MB	40GB	Combo	*Intel 11b Wi-Fi	Modem	10/100	1394	Yes	XP Pro Nov2003

These educational models of the ThinkPad R40 notebook are available only to public or private K-12 (or higher) accredited schools organized and operated exclusively for educational purposes for use by qualified students and/or teachers.

This model for education is for sale direct from IBM or through an Authorized Education Reseller. The model or models for education are not available for resale to any other organization or individual.
2723 models have a 3 year limited warranty (other 2722 ThinkPad R40 systems have a 1 year limited warranty)

Positioning Processor	<i>Mainstream performance and features; two-spindle system</i> Mobile Intel® Pentium® M Processor 1.3 or 1.4GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz frontside bus	SOFTWARE¹⁴ Windows XP Pro models - Microsoft® Windows® XP Professional ²⁰ ♦ Disk-to-Disk Recovery (in hidden protected area) Preloaded • Access IBM - Access Connections • Adobe Acrobat Reader • IBM Rapid Restore™ PC • IBM RecordNow and DLA • InterVideo WinDVD • Norton AntiVirus (OEM edition) • PC-Doctor™ • ThinkPad Utilities • IBM Update Connector™ ¹⁵ Downloadable • IBM Director Agent • Software Delivery Assistant • System Migration Assistant • Client Security Software (for security chip) License (CD not included) - Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client Universal 72 watt AC adapter Asset ID™ ³⁴ (system-specific info in chip accessed over network) PC 2001 and PXE 2.0-compliant ACPI 1.0b and 2.0-compliant CIM and DMI 2.0-compliant IBM ImageUltra™ Services available IBM Rapid Restore PC available to protect software image and data International Warranty Service ¹⁷ 24 hour x 7 day ¹⁸ toll-free warranty support during the warranty ¹² Ultrabay Plus integrated modular bay supports most Ultrabay 2000 devices including CD-RW/DVD Combo drive, diskette drive, or Zip drive; the optional Ultrabay Plus Device Carrier adds potential functionality by supporting the Ultrabay Plus Numeric Keypad and Cradle for the WorkPad® c500 Series ServicePac® ²² 2 yr IOR 9x5 NBD 30L9190 ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf
L2 cache	1MB / on die (at processor speed) / ECC	
Memory	256MB std / 2GB max ⁷ / PC2100 266MHz DDR1 (DDR-SDRAM) / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available	
Diskette drive	None standard / use optional Ultrabay™-based or USB-based diskette drive	
Combo	DVD-ROM/CD-RW / 24X/10X/24X/8X ²¹ speed / removable from Ultrabay 2000	
Ultrabay 2000	One modular bay for interchangeable devices / Ultrabay Plus -compatible / 12.7 mm high	
Disk	40GB⁸ , 4200 rpm, 9.5mm high / removable and upgradable / 9.5mm high bay / supports 2nd disk with optional HDD Adapter in Ultrabay 2000	
Display	<i>Some:</i> 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits <i>Some:</i> 15.0" (381mm) XGA (1024x768) TFT color / Active Matrix / 150 nits <i>Some:</i> 15.0" (381mm) SXGA+ (1400x1050) TFT color / Active Matrix / 150 nits <i>All:</i> Easy-open cover to unlatch and open with one hand (two latches)	
Graphics controller	ATI® Mobility RADEON® 7500 / AGP 4X / 32MB DDR1 (DDR-SDRAM)	
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B	
Keyboard	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)	
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass	
Touch pad	UltraNav™ multi-pointing system / touch pad below keyboard / Tap Zones	
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions	
Dimensions ³	<i>14.1" models:</i> 12.3" x 10.0" x 1.53"; <i>15.0" models:</i> 13.0" x 10.5" x 1.59"	
Approximate weight ²	with optical drive and battery: <i>14.1" models:</i> 6.0 to 6.1 lb; <i>15.0":</i> 6.6 to 6.7 lb (3.0 to 3.4kg)	
Case material	<i>Color:</i> Black; <i>All:</i> Acrylonitrile-Butadiene-Styrene (ABS) plastic	
Battery - type	Lithium Ion 8-cell / intelligent / supports unique 2nd battery in Ultrabay 2000	
Battery - life ¹⁰	6.2 hr; <i>BDU:</i> 6.1 hr	
Architecture	Intel 855PM chipset / 82855PM Memory Controller Hub (MCH-M) / 82801DBM ICH4-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count (LPC) interface, USB, Firmware Hub) / PCI bus 2.2 32-bit, 33MHz (TI® PCI1510 CardBus controller, TSB43AB21 1394 (some), Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared)	
PC Card Std slots	One Type I, one Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door	
Ports	Two USB (Version 2.0) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port	
Video out	S-video out port (TV out) / one 4-pin industry standard connector	
IEEE 1394	IEEE 1394 (FireWire) port / 4-pin connector	
Wireless antenna	UltraConnect™ Antenna built into the display cover for optimal wireless signal reception	
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable	
11b Wi-Fi ³²	<i>Some:</i> 11b Wi-Fi ³² wireless ⁴ , Mini PCI, Intel PRO/Wireless 2100, Intel 82531 chipset	
11a/b Wi-Fi ²⁷	<i>Some:</i> 11a/b Wi-Fi ²⁷ wireless ⁴ , Mini PCI, Atheros™ AR5001X chipset	
CDC	One Communications Daughter Card (CDC) socket (used by modem) / not accessible	
Modem	56K ⁶ V.90 (V.92-designed ²³) modem in CDC / Agere® chipset	
Bluetooth	None	
Ethernet	10/100 ethernet on motherboard / Intel 82562EZ chipset (physical layer) / PXE	
Audio support	Soft audio / ICH AC97 controller / DirectSound® support / AD1891A AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal mic / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack	
Security	Power-on password / hard disk password / supervisor password / security keyhole	
Security chip	IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant	
Limited warranty ¹²	3 years /1 year battery - EasyServ™ ¹⁹ onsite pickup and delivery / serv upgrades ²² avail	

128MB PC2100 DDR-SDRAM CL2.5 SOD	10K0028	ThinkPad Port Replicator II	74P6733
256MB PC2100 DDR-SDRAM CL2.5 SOD	10K0030	ThinkPad Mini Dock	287810U
512MB PC2100 DDR-SDRAM CL2.5 SOD	10K0032	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816
1GB PC2100 DDR-SDRAM CL2.5 SOD	10K0034	80GB HS Hard Disk 9.5mm (5400 rpm)	09N4273
CD-RW/DVD Combo IV Ultrabay 2000	22P6991	GemPC400 Smart Card Reader/Writer	31P8901
Second HDD Adapter for Ultrabay 2000	08K6068	ThinkPad R32/R40 Series Li-Ion Battery	02K7052
ThinkPad Removable Diskette Drive	08K9603	Ultrabay 2000 Li-Ion battery	02K6646
IBM USB Portable Diskette Drive	05K9276	ThinkPad Multiple Battery Charger II	22P9040
IBM Portable USB 2.0 Multi-Burner Drive	22P9163	IBM 11a/b/g Wireless CardBus Adapter	31P9101
Optical 3-Button Travel Wheel Mouse	31P7410	IBM 11a/b/g Wireless Mini PCI Adapter	31P9701
IBM 4GB Microdrive™ with PC Card	09N4280	Cisco Aironet Wireless 802.11b Mini PCI	31P8301
IBM 128MB USB 2.0 Memory Key	22P9229	IBM M400 Projector	0037A04
IBM 256MB USB 2.0 Memory Key	22P9025	IBM E400 Projector	0038A04
ThinkPad 72W AC Adapter	02K6699	ThinkPad Monitor Stand 2001	22P5265
ThinkPad 72W AC/DC Combo Adapter	22P9010	Other options at ibm.com/pc/us/accessories	

See footnotes for important warranty information * Powered by the Intel Centrino™ mobile technology (R403ME) © IBM Corp. October 2004

US models announced March 25 or November 20, 2003

US models withdrawn effective January 2004 or October 2004

Type-model	Processor	Speed GHz	Memory	Screen	Disk GB ^a	Optical	Mini PCI Comm Bay wireless	CDC modem	Ethernet on planar	IEEE 1394 port	Security chip	Preload	Limited Workhorse (W) warranty ¹²	Global (G) Entry (E)	Avail date
1834-4EU	Celeron® M	1.3	128MB	14.1" XGA	20GB	CD	None	Modem	10/100	No	No	XP Home	1 yr	E	Apr 2004
1834-5BU	Celeron M	1.3	128MB	15.0" XGA	20GB	CD	None	Modem	10/100	No	No	XP Home	1 yr	E	Apr 2004
1834-4AU	Celeron M	1.3	256MB	14.1" XGA	30GB	Combo	None	Modem	10/100	No	No	XP Pro	1 yr		Apr 2004
1834-56U	Celeron M	1.3	256MB	15.0" XGA	30GB	Combo	None	Modem	10/100	No	No	XP Pro	1 yr		Apr 2004
1834-NEU	Pentium® M 705	1.5	128MB	14.1" XGA	30GB	CD	* Intel 11b/g ³²	Modem	10/100	No	No	XP Home	1 yr	E	July 2004
1834-C4U	Pentium M 715	1.5	128MB	14.1" XGA	30GB	CD	* Intel 11b/g	Modem	10/100	No	No	XP Home	1 yr	E	July 2004
1834-AAU	Pentium M 715	1.5	256MB	14.1" XGA	30GB	CD	* Intel 11b/g	Modem	10/100	No	No	XP Pro	1 yr		July 2004
Positioning Processor	Mainstream performance and features; two-spindle system Intel® Celeron M Processor 1.3GHz with 400MHz system bus or Intel Pentium M Processor 705 (1.5GHz with 1MB L2 cache) or 715 (1.5GHz with 2MB L2 cache) with enhanced Intel SpeedStep™ technology ¹ and 400MHz system bus Celeron M: 512KB; Pentium M 705: 1MB; Pentium M 715: 2 MB; All: ECC 128MB or 256MB std / 2GB max ⁷ / PC2700 333MHz DDR 1 (memory controller limits speed to 266MHz) / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available												SOFTWARE¹⁴		
L2 cache													Windows XP Home models		
Memory													- Microsoft® Windows® XP Home Edition ²⁰ ♦ Disk-to-Disk Recovery (in hidden protected area)		
Diskette drive	None standard / use optional USB-based diskette drive <i>Some:</i> CD-ROM / 24X-10X ⁹ speed / fixed, not removable / 12.7 mm high <i>Some:</i> DVD-ROM/CD-RW / 24X/24X/8X ²¹ speed / fixed, not removable / 12.7 mm												Windows XP Pro models		
CD													- Microsoft Windows XP Professional ²⁰ ♦ Disk-to-Disk Recovery (in hidden protected area)		
Combo													Preloaded (all)		
Ultrabay Enhanced Disk	None / no support for removable Ultrabay™ options 20GB⁸ or 30GB (4200 rpm), 9.5mm high / removable and upgradable / 9.5mm high bay / IBM Hard Disk Drive Shock Absorber												• Access IBM • Access Connections • IBM Rescue and Recovery™ • IBM RecordNOW and Drive Letter Access powered by Sonic products (combo models) • InterVideo WinDVD (combo models) • Norton AntiVirus (OEM edition) • PC-Doctor™ • ThinkPad Utilities • Adobe Reader • IBM Update Connector™. ¹⁵		
Display	<i>Some:</i> 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits <i>Some:</i> 15.0" (381.0mm) XGA (1024x768) TFT color / Active Matrix / 200 nits <i>All:</i> one latch to unlatch and open with one hand												• IBM Director Agent • Software Delivery Assistant • System Migration Assistant		
Graphics	Integrated Intel Extreme™ Graphics 2 / in 855GM GMCH / uses main memory (up to 64MB) / 200MHz												License (CD not included) - Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client		
Graphics external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B												ThinkPad notebooks implement IBM ThinkVantage™ technologies and design; visit ibm.com/thinkvantage		
Keyboard	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys) TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass												Universal 72 watt AC adapter Asset ID™. ³⁴ (system-specific info in chip accessed over network) PC 2001 and PXE 2.0-compliant ACPI 1.0b and 2.0-compliant CIM and DMI 2.0-compliant ENERGY STAR®-compliant IBM ImageUltra™ Services available International Warranty Service ¹⁷ 24 hour x 7 day ¹⁸ toll-free warranty support during the warranty ¹²		
TrackPoint®	No UltraNav™ multi-pointing system												ServicePac®. ²² 1yr IOR 9x5 NBD 30L9188		
Touch pad	Illuminates the keyboard to improve visibility in low-light conditions												ServicePac 2 yr IOR 9x5 NBD 30L9189		
ThinkLight™													ServicePac 3 yr IOR 9x5 NBD 30L9195		
Dimensions ³	14.1" models (WxDxH): 12.4" x 10.2" x 1.35-1.46"; 314mm x 260mm x 34-37mm 15.0" models (WxDxH): 13.1" x 10.6" x 1.47-1.58"; 332mm x 269mm x 37-40mm with optical drive and battery: 14.1" models: 6.0 lb (2.7kg); 15.0" models: 6.6 lb (3.0kg)												ServicePac 4 yr IOR 9x5 NBD 30L9194		
Weight ²													ServicePac 5 yr IOR 9x5 NBD 30L9196		
Case material	<i>Color:</i> black; <i>All:</i> Acrylonitrile-Butadiene-Styrene (ABS) plastic												ServicePac 2 yr P&L P/U Depot 22P9040 30L9191		
Battery - type	Lithium Ion 6-cell / intelligent / supports optional 9-cell battery												ServicePac 3 yr P&L P/U Depot 30L9192		
Battery - life ¹⁰	<i>Celeron M models:</i> up to 4.0 hr; <i>Pentium M models:</i> up to 4.7 hr; <i>Optional High Capacity 9-cell:</i> up to 6.0 hr												ServicePac 4 yr P&L P/U Depot 69P9195		
Architecture	Intel 855GM chipset / 82855GM Memory Controller Hub (MCH-M) / 82801DBM ICH4-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count [LPC] interface, USB) / PCI bus 2.2 32-bit, 33MHz (TI ⁹ PCI1510 CardBus controller, Mini PCI) / LPC bus 33MHz (PC87392 Super I/O for parallel)												ServicePac 5 yr P&L P/U Depot 69P9197		
Port replicator	No port replicator support												Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
Docking station	No docking station support														
PC Card Std slots	One Type I, one Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door														
Ports	Two USB (Version 2.0) / parallel / external monitor (DB-15) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial or infrared port														
Video out	None														
IEEE 1394	None														
Wireless antenna	<i>Some (Celeron models):</i> none / can upgrade to wireless via optional PC Cards <i>Some (Pentium models):</i> UltraConnect™ Antenna built into the display cover <i>Some (Celeron models):</i> no Mini PCI slot (Communications Bay) <i>Some (Pentium):</i> one Mini PCI slot (Communications Bay) / not customer upgradable														
Mini PCI	<i>Some:</i> 11b/g wireless ⁴ , Mini PCI, Intel PRO/Wireless 2200BG, Intel 82532 chipset One Communications Daughter Card (CDC) socket (used by modem) / not accessible														
Intel 11b/g ³²	56K ⁵ V.90 (V.92-designed ²⁹) modem in CDC / Conexant® chipset														
CDC	10/100 ethernet on planar / Intel 82562EZ chipset (physical layer) / Wake on LAN®														
Modem	Soft audio / ICH AC97 controller / DirectSound® support / AD1981B AC97 codec / mono speaker / 1 watt / volume up, down, mute buttons / no internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack														
Ethernet	Power-on password / hard disk password / supervisor password / security keyhole														
Audio support	None														
Security															
Security chip															
Limited warranty ¹²	1 year - EasyServ™. ¹⁹ onsite pickup and delivery courier service														
128 MB PC2700 DDR-SDRAM CL2.5 SOD	31P9828	T40/R50 Series Li-Ion Battery 6-cell	08K8214												
256 MB PC2700 DDR-SDRAM CL2.5 SOD	31P9830	T40/R50 High Capacity Li-Ion Batt 9-cell	08K8197												
512 MB PC2700 DDR-SDRAM CL2.5 SOD	31P9832	ThinkPad Multiple Battery Charger II	22P9040												
1 GB PC2700 DDR-SDRAM CL2.5 SOD	31P9834	TrackPoint Cap Collection	73P2698												
IBM 4GB Microdrive™ with PC Card	09N4280	Kensington® MicroSaver® Security Cable	73P2582												
IBM USB Portable Diskette Drive	05K9276	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816												
IBM USB 2.0 Combo Drive	73P4515	60GB HS Hard Disk 9.5mm (5400 rpm)	73P3357												
IBM USB 2.0 Portable Multi-Burner Drive	22P9163	80GB HS Hard Disk 9.5mm (5400 rpm)	09N4273												
IBM USB 2.0 Portable 40GB Hard Disk	22P7196	IBM 11a/b/g Wireless CardBus Adapter	31P9101												
IBM USB 2.0 Memory Key 256MB	22P9228	ThinkPad Carrying Case - Leather	73P3600												
IBM USB 2.0 Memory Key 512MB	22P9230	ThinkPad 72W AC/DC Combo Adapter	22P9010												
IBM C400 Projector	0039A04	IBM USB Travel Keyboard with UltraNav	31P9490												
ThinkPad Monitor Stand 2001	22P5265	Other options at ibm.com/pc/us/accessories													

See footnotes for important warranty information
US models announced April 6 or July 13, 2004
US models withdrawn effective January or March 2005

* Powered by Intel Centrino™ mobile technology

Type-model	Processor	Speed GHz Memory	Screen	Graphics controller	Disk GB ⁸	Optical	Mini PCI Comm Bay wireless	Ethernet on planar	IEEE 1394 port	Security chip	Workhorse (W) Global (G) Entry (E)	Avail date	
1830-46U	Pentium® M	1.4 256MB	14.1" XGA	7500	30G	CD	Open; wireless upg ³⁶	Modem	10/100	Yes	XP Pro W	Oct 2003	
1830-48U	Pentium M	1.4 256MB	14.1" XGA	7500	30G	DVD	Open; wireless upg	Modem	10/100	Yes	XP Pro W G	Oct 2003	
1830-56U	Pentium M	1.4 256MB	14.1" XGA	7500	30G	Combo	*Intel 11b Wi-Fi ³²	Modem	Gigabit	1394	Yes	XP Pro W G	Oct 2003
1830-6FU	Pentium M	1.5 256MB	15.0" XGA	7500	40G	Combo	*Intel 11b Wi-Fi	Modem	Gigabit	1394	Yes	XP Pro W G	Oct 2003
1830-7DU	Pentium M	1.4 256MB	15.0" SXGA+	9000	40G	Combo	11a/b/g Wi-Fi ³²	Modem	Gigabit	1394	Yes	XP Pro	Oct 2003
1830 models have a 3 year limited warranty (other 1829/1836 ThinkPad R50 systems have a 1 year limited warranty)													
Positioning	Mainstream performance and features; two-spindle system										SOFTWARE¹⁴		
Processor	Intel® Pentium® M Processor 1.4 or 1.5GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz system bus												
L2 cache	1MB / on die (at processor speed) / ECC										Windows XP Pro models - Microsoft® Windows® XP Professional ²⁰ ♦ Disk-to-Disk Recovery (in hidden protected area)		
Memory	256MB std / 2GB max ⁷ / PC2700 333MHz DDR-SDRAM / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available												
Diskette drive	None standard / use optional USB-based diskette drive										Preloaded • Access IBM • Access Connections • Adobe Acrobat Reader • IBM Rapid Restore™ Ultra • IBM RecordNow and IBM Drive Letter Access (combo models) • InterVideo WinDVD (combo, DVD) • Norton AntiVirus (OEM edition) • PC-Doctor™ • ThinkPad Utilities • IBM Update Connector™ ¹⁵		
CD	Some: CD-ROM / 24X-10X ⁹ speed / bootable / removable from Ultrabay Enhanced												
DVD	Some: DVD-ROM / 8X-3.3X ⁹ speed / bootable / removable from Ultrabay Enhanced										Downloadable • IBM Director Agent • Software Delivery Assistant • System Migration Assistant • Client Security Software (for security chip)		
Combo	Some: DVD-ROM/CD-RW / 24X/24X/24X/8X ²¹ speed / removable from Ultrabay Enhanced												
Ultrabay Enhanced Disk	One modular bay for interchangeable devices / Ultrabay Slim-compatible / 12.7 mm high 30GB ⁸ (4200 rpm) or 40GB (4200 rpm), 9.5mm high / removable and upgradable / 9.5mm high bay / supports 2nd disk with optional Second HDD Adapter for Ultrabay Slim / IBM Hard Disk Drive Shock Absorber / IBM Active Protection System										License (CD not included) - Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client		
Display	Some: 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits Some: 15.0" (381.0mm) XGA (1024x768) TFT color / Active Matrix / 200 nits Some: 15.0" (381.0mm) SXGA+ (1400x1050) TFT color / Active Matrix / 200 nits / FlexView display with wide viewing angle and high density using in plane switching (IPS) technology												
Graphics controller	Some: ATI® Mobility™ RADEON™ 7500 / AGP 4X / 32MB DDR-SDRAM Some: ATI Mobility RADEON 9000 / AGP 4X / 32MB DDR-SDRAM										ServicePac® , ²² 2 yr IOR 9x5 NBD 30L9190 ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B												
Keyboard	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)										Universal 72 watt AC adapter Asset ID™ ³⁴ (system-specific info in chip accessed over network) PC 2001 and PXE 2.0-compliant ACPI 1.0b and 2.0-compliant CIM and DMI 2.0-compliant IBM ImageUltra™ Services available IBM Rapid Restore Ultra available to protect software image and data International Warranty Service ¹⁷ 24 hour x 7 day ¹⁸ toll-free warranty support during the warranty ¹² via 800-IBM-SERV (426-7378)		
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass												
Touch pad	UltraNav™ multi-pointing system / touch pad below keyboard / Tap Zones										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions												
Dimensions ³	14.1" models (WxDxH): 12.4" x 10.2" x 1.35-1.46"; 314mm x 260mm x 34-37mm 15.0" models (WxDxH): 13.1" x 10.6" x 1.47-1.58"; 332mm x 269mm x 37-40mm										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
Approximate weight ²	with optical drive and battery: 46U/48U: 5.7 lb (2.6kg); 56U: 6.0 lb; 6FU/7DU: 6.6 lb (3.0kg)												
Case material	Color: black; All: Acrylonitrile-Butadiene-Styrene (ABS) plastic										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
Battery - type	Lithium Ion 6-cell / intelligent / supports unique 2nd battery in Ultrabay Enhanced												
Battery - life ¹⁰	Model 7DU with SXGA+: up to 4.0 hr; Others: up to 4.7 hr; Optional 9-cell: up to 6.9 hr										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
Architecture	Intel 855PM chipset / 82855PM Memory Controller Hub (MCH-M) / 82801DBM ICH4-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count [LPC] interface, USB, [Bluetooth]) / PCI bus 2.2 32-bit, 33MHz (TI® PCI4520A CardBus and 1394 controller, Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared, [docking-based ports])												
PC Card Std slots	One Type I, one Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
Ports	Two USB (Version 2.0) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port												
Video out	S-video out port (TV out) / one 4-pin industry standard connector										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
IEEE 1394	Some: IEEE 1394 (FireWire) port / 4-pin connector / 1394a-2000 standard												
Wireless antenna	UltraConnect™ Antenna built into the display cover for optimal wireless signal reception										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable												
Wireless upg ³⁶	Some: wireless upgradable with wireless Mini PCI options										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
11b Wi-Fi ³²	Some: 11b Wi-Fi ³² wireless ⁴ , Mini PCI, Intel PRO/Wireless 2100, Intel 82531 chipset												
11a/b/g Wi-Fi ³²	Some: 11a/b/g Wi-Fi ³² wireless ⁴ , Mini PCI, Atheros™ AR5001X+ chipset										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
CDC	One Communications Daughter Card (CDC) socket (used by modem) / not accessible												
Modem	56K V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
Bluetooth	None												
Ethernet	Some: 10/100 ethernet on planar / Intel 82562EZ chipset (physical layer) / Wake on LAN® Some: Gigabit Ethernet on planar / Intel 82540EP chipset (MAC/PHY) / Wake on LAN										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
Audio support	Soft audio / ICH AC97 controller / DirectSound® support / AD1981B AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack												
Security	Power-on password / hard disk password / supervisor password / security keyhole										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
Security chip	IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant												
Limited warranty ¹²	3 years/1 yr battery - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² avail										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf		
128MB PC2700 DDR-SDRAM CL2.5 SOD	31P9828	T40/R50 Series Li-Ion Battery 6-cell	08K8214										
256MB PC2700 DDR-SDRAM CL2.5 SOD	31P9830	T40/R50 High Capacity Li-Ion Batt 9-cell	08K8197										
512MB PC2700 DDR-SDRAM CL2.5 SOD	31P9832	Ultrabay Slim Li-Polymer Battery 3-cell	08K8190										
1GB PC2700 DDR-SDRAM CL2.5 SOD	31P9834	30GB Hard Disk 9.5mm (4200 rpm)	09N4268										
Second HDD Adapter for Ultrabay Slim	62P4554	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816										
ThinkPad DVD-ROM Ultrabay Slim Drive	73P3270	80GB HS Hard Disk 9.5mm (5400 rpm)	09N4273										
CD-RW/DVD Combo Ultrabay Enhanced	73P3275	Intel PRO/Wireless 2200BG Mini PCI	73P2801										
Multi-Burner Ultrabay Enhanced Drive	73P3282	IBM 11a/b/g Wireless Mini PCI Adapter	31P9701										
IBM USB Portable Diskette Drive	05K9276	IBM 11a/b/g Wireless CardBus Adapter	31P9101										
IBM USB 2.0 Portable Multi-Burner Drive	22P9163	ThinkPad Port Replicator II	74P6733										
ThinkPad 72W AC/DC Combo Adapter	22P9010	ThinkPad Mini Dock	287810U										
Other options at ibm.com/pc/us/accessories			ThinkPad Dock II	287710U									

See footnotes for important warranty information
US models announced October 7, 2003
US models withdrawn effective July 2004

* Powered by Intel Centrino™ mobile technology

Type-model	Processor	Speed GHz Memory	Screen	Graphics controller	Disk	Optical	Mini PCI Comm Bay wireless	CDC modem/ Bluetooth™	Ethernet on planar	IEEE 1394 port	Battery Sec cells Limited warranty	Workhorse Global Entry Avail date
1829-6YU	Pentium® M 1.6	512MB 15.0"	XGA	7500	40GB ⁸	Combo	Open; wireless upg ³⁶	Modem	Gigabit	1394	Yes	6 1 year No Jan 2004
1829-7ZU	Pentium M 1.7	512MB 15.0"	SXGA+	9000	60GB	Combo	Open; wireless upg	Mod/Blue	Gigabit	1394	Yes	9 1 year No Jan 2004
<p>1829 models have a 1 year limited warranty (other 1830 ThinkPad R50 systems have a 3 year limited warranty)</p>												
Positioning	Mainstream performance and features; two-spindle system											
Processor	Intel® Pentium® M Processor 1.6 or 1.7GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz system bus											
L2 cache	1MB / on die (at processor speed) / ECC											
Memory	512MB std / 2GB max ⁷ / PC2700 333MHz DDR1 (DDR-SDRAM) / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available											
Diskette drive	None standard / use optional USB-based diskette drive											
Combo	DVD-ROM/CD-RW / 24X/24X/24X/8X ²¹ speed / removable from Ultrabay Enhanced											
Ultrabay Enhanced	One modular bay for interchangeable devices / Ultrabay Slim-compatible / 12.7 mm high											
Disk	40GB ⁸ (4200 rpm) or 60GB (4200 rpm), 9.5mm high / removable and upgradable / 9.5mm high bay / supports 2nd disk with optional Second HDD Adapter for Ultrabay Slim ⁷ / IBM Hard Disk Drive Shock Absorber / IBM Active Protection System											
Display	Some: 15.0" (381.0mm) XGA (1024x768) TFT color / Active Matrix / 200 nits Some: 15.0" (381.0mm) SXGA+ (1400x1050) TFT color / Active Matrix / 200 nits / FlexView display with wide viewing angle and high density using in plane switching (IPS) technology											
Graphics controller	Some: ATI® Mobility™ RADEON™ 7500 / AGP 4X / 32MB DDR1 (DDR-SDRAM) Some: ATI Mobility RADEON 9000 / AGP 4X / 32MB DDR1 (DDR-SDRAM)											
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B											
Keyboard	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)											
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass											
Touch pad	UltraNav™ multi-pointing system / touch pad below keyboard / Tap Zones											
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions											
Dimensions ³	(WxDxH): 13.1" x 10.6" x 1.47-1.58"; 332mm x 269mm x 37-40mm											
Approximate weight ²	with optical drive and battery: 6YU: 6.6 lb (3.0kg); 7ZU: 6.8 lb (3.1kg)											
Case material	Color: black; All: Acrylonitrile-Butadiene-Styrene (ABS) plastic											
Battery - type	Lithium Ion 6- or 9-cell / intelligent / supports unique 2nd battery in Ultrabay Enhanced											
Battery - life ¹⁰	Model 6YU with 6-cell: up to 4.7 hr; 7ZU with 9-cell: up to 6.0 hr											
Architecture	Intel 855PM chipset / 82855PM Memory Controller Hub (MCH-M) / 82801DBM ICH4-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count [LPC] interface, USB, [Bluetooth]) / PCI bus 2.2 32-bit, 33MHz (TI® PCI4520A CardBus and 1394 controller, Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared, [docking-based ports])											
PC Card Std slots	One Type I, one Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door											
Ports	Two USB (Version 2.0) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port											
Video out	S-video out port (TV out) / one 4-pin industry standard connector											
IEEE 1394	IEEE 1394 (FireWire) port / 4-pin connector / 1394a-2000 standard											
Wireless antenna	UltraConnect™ Antenna built into the display cover for optimal wireless signal reception											
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable											
Wireless upg ³⁶	Wireless upgradable with wireless Mini PCI options											
CDC	One Communications Daughter Card (CDC) socket (used by modem) / not accessible											
Modem	56K ⁹ V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset											
Bluetooth	Some: Bluetooth wireless technology / in CDC (with modem)											
Ethernet	Intel PRO/1000 Gigabit Ethernet / on planar / Intel 82540EP chipset (MAC/PHY) / Wake on LAN®											
Audio support	Soft audio / ICH AC97 controller / DirectSound® support / AD1981B AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack											
Security	Power-on password / hard disk password / supervisor password / security keyhole											
Security chip	IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant											
Limited warranty ¹²	1 year - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² avail											
128 MB PC2700 DDR-SDRAM CL2.5 SOD	31P9828	T40/R50 Series Li-Ion Battery 6-cell	08K8214									
256 MB PC2700 DDR-SDRAM CL2.5 SOD	31P9830	T40/R50 High Capacity Li-Ion Batt 9-cell	08K8197									
512 MB PC2700 DDR-SDRAM CL2.5 SOD	31P9832	Ultrabay Slim Li-Polymer Battery 3-cell	08K8190									
1GB PC2700 DDR-SDRAM CL2.5 SOD	31P9834	ThinkPad Multiple Battery Charger II	22P9040									
Second HDD Adapter for Ultrabay Slim	62P4554	IBM USB Travel Keyboard with UltraNav	31P9490									
ThinkPad DVD-ROM Ultrabay Slim Drive	73P3270	TrackPoint Cap Collection	73P2698									
CD-RW/DVD Combo Ultrabay Enhanced	73P3275	30GB Hard Disk 9.5mm (4200 rpm)	09N4268									
Multi-Burner Plus Ultrabay Enhanced Drive	73P3312	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816									
IBM 128MB USB 2.0 Memory Key	22P9229	80GB HS Hard Disk 9.5mm (5400 rpm)	09N4273									
IBM 256MB USB 2.0 Memory Key	22P9025	Intel PRO/Wireless 2200BG Mini PCI	73P2801									
IBM 4GB Microdrive™ with PC Card	09N4280	IBM 11a/b/g Wireless Mini PCI Adapter	31P9701									
IBM USB Portable Diskette Drive	05K9276	IBM 11a/b/g Wireless CardBus Adapter	31P9101									
IBM USB 2.0 Portable Combo Drive	22P9194	Ericsson® GC82 EDGE PC Card Wireless	58P8782									
IBM USB 2.0 Portable Multi-Burner	22P9163	ThinkPad 72W AC Adapter	02K6699									
IBM USB Serial Parallel Adapter	22P5298	ThinkPad 72W AC/DC Combo Adapter	22P9010									
IBM M400 Projector	0037A04	ThinkPad Port Replicator II	74P6733									
IBM E400 Projector	0038A04	ThinkPad Mini Dock	287810U									
IBM C400 Projector	0039A04	ThinkPad Dock II	287710U									
IBM Optical 3-Button Travel Wheel Mouse	31P7410	Other options at ibm.com/pc/us/accessories										
<p>SOFTWARE¹⁴</p> <p>Windows XP Pro models</p> <ul style="list-style-type: none"> Microsoft® Windows® XP Professional²⁰ ◆ Disk-to-Disk Recovery (in hidden protected area) <p>Preloaded</p> <ul style="list-style-type: none"> Access IBM Access Connections Adobe Acrobat Reader IBM Rapid Restore™ Ultra IBM RecordNOW and IBM Drive Letter Access InterVideo WinDVD Norton AntiVirus (OEM edition) PC-Doctor™ ThinkPad Utilities IBM Update Connector™¹⁵ <p>Downloadable</p> <ul style="list-style-type: none"> IBM Director Agent Software Delivery Assistant System Migration Assistant Client Security Software (for security chip) <p>License (CD not included)</p> <ul style="list-style-type: none"> Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client 												
<p>Universal 72 watt AC adapter Asset ID™³⁴ (system-specific info in chip accessed over network) PC 2001 and PXE 2.0-compliant ACPI 1.0b and 2.0-compliant CIM and DMI 2.0-compliant IBM ImageUltra™ Services available IBM Rapid Restore Ultra available to protect software image and data International Warranty Service¹⁷ 24 hour x 7 day¹⁸ toll-free warranty support during the warranty¹² via 800-IBM-SERV (426-7378)</p>												
<p>ServicePac®²² 1yr IOR 9x5 NBD 30L9188</p> <p>ServicePac 2 yr IOR 9x5 NBD 30L9189</p> <p>ServicePac 3 yr IOR 9x5 NBD 30L9195</p> <p>ServicePac 4 yr IOR 9x5 NBD 30L9194</p> <p>ServicePac 5 yr IOR 9x5 NBD 30L9196</p> <p>ServicePac 2 yr P&L P/U Depot 30L9191</p> <p>ServicePac 3 yr P&L P/U Depot 30L9192</p> <p>ServicePac 4 yr P&L P/U Depot 69P9195</p> <p>ServicePac 5 yr P&L P/U Depot 69P9197</p> <p>Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf</p>												

See footnotes for important warranty information
US models announced January 13, 2004
US models withdrawn effective October 2004

Type-model	Processor	Speed GHz	Memory	Screen	Graphics controller	Disk GB ⁸	Optical	Mini PCI Comm Bay wireless	CDC modem	Ethernet on planar	IEEE 1394 port	Security chip	Workhorse (W) Global (G) Entry (E)	Avail date	
1830-5AU	Pentium® M	1.4	256MB	14.1" XGA	7500	40G	Combo	*Intel 11b Wi-Fi ³²	Modem	Gigabit	1394	Yes	XP Pro	No	Oct 2003
1830-5CU	Pentium M	1.4	256MB	14.1" XGA	7500	40G	Combo	11a/b/g Wi-Fi ³²	Modem	Gigabit	1394	Yes	XP Pro	No	Oct 2003
1830-7CU	Pentium M	1.4	256MB	15.0" SXGA+	9000	40G	Combo	*Intel 11b Wi-Fi	Modem	Gigabit	1394	Yes	XP Pro	No	Oct 2003

These educational models of the ThinkPad notebook are available only to public or private K-12 (or higher) accredited schools organized and operated exclusively for educational purposes for use by qualified students and teachers.

This model for education is for sale direct from IBM or through an Authorized Education Reseller.

The model or models for education are not available for resale to any other organization or individual.

1830 models have a 3 year limited warranty (other 1829/1836 ThinkPad R50 systems have a 1 year limited warranty)

Positioning Processor	Mainstream performance and features; two-spindle system Intel® Pentium® M Processor 1.4GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz system bus										SOFTWARE¹⁴							
L2 cache	1MB / on die (at processor speed) / ECC										Windows XP Pro models							
Memory	256MB std / 2GB max ⁷ / PC2700 333MHz DDR-SDRAM / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available										- Microsoft® Windows® XP Professional ²⁰ ◆ Disk-to-Disk Recovery (in hidden protected area)							
Diskette drive	None standard / use optional USB-based diskette drive										Preloaded							
Combo	DVD-ROM/CD-RW / 24X/24X/24X/8X ²¹ speed / removable from Ultrabay Enhanced										• Access IBM							
Ultrabay Enhanced Disk	One modular bay for interchangeable devices / Ultrabay Slim-compatible / 12.7 mm high 40GB (4200 rpm), 9.5mm high / removable and upgradable / 9.5mm high bay / supports 2nd disk with optional 'Second HDD Adapter for Ultrabay Slim' / IBM Hard Disk Drive Shock Absorber / IBM Active Protection System (impact protection)										• Access Connections • Adobe Acrobat Reader • IBM Rapid Restore™ Ultra • IBM RecordNOW and IBM Drive Letter Access • InterVideo WinDVD • Norton AntiVirus (OEM edition) • PC-Doctor™ • ThinkPad Utilities • IBM Update Connector™. ¹⁵							
Display	Some: 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits Some: 15.0" (381.0mm) SXGA+ (1400x1050) TFT color / Active Matrix / 200 nits / FlexView display with wide viewing angle and high density using in plane switching (IPS) technology All: one latch to unlatch and open with one hand										Downloadable							
Graphics controller	Some: ATI® Mobility™ RADEON™ 7500 / AGP 4X / 32MB DDR-SDRAM Some: ATI Mobility RADEON 9000 / AGP 4X / 32MB DDR-SDRAM										• IBM Director Agent • Software Delivery Assistant • System Migration Assistant • Client Security Software (for security chip)							
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B										License (CD not included) - Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client							
Keyboard	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)										Universal 72 watt AC adapter Asset ID™. ³⁴ (system-specific info in chip accessed over network) PC 2001 and PXE 2.0-compliant ACPI 1.0b and 2.0-compliant CIM and DMI 2.0-compliant IBM ImageUltra™ Services available IBM Rapid Restore PC available to protect software image and data International Warranty Service ¹⁷ 24 hour x 7 day ¹⁸ toll-free warranty support during the warranty ¹² via 800-IBM-SERV (426-7378)							
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass																	
Touch pad	UltraNav™ multi-pointing system / touch pad below keyboard / Tap Zones																	
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions																	
Dimensions ³	14.1" models (WxDxH): 12.4" x 10.2" x 1.35-1.46"; 314mm x 260mm x 34-37mm 15.0" models (WxDxH): 13.1" x 10.6" x 1.47-1.58"; 332mm x 269mm x 37-40mm																	
Approximate weight ²	with optical drive and battery: 5AU/5CU: 6.0 lb (2.7kg); 7CU: 6.6 lb (3.0kg)										ServicePac®. ²² 2 yr IOR 9x5 NBD 30L9190 ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf							
Case material	Color: black; All: Acrylonitrile-Butadiene-Styrene (ABS) plastic																	
Battery - type	Lithium Ion 6-cell / intelligent / supports unique 2nd battery in Ultrabay Enhanced																	
Battery - life ¹⁰	Model 7CU with SXGA+: up to 4.0 hr; Others: up to 4.7 hr; Optional 9-cell: up to 6.9 hr																	
Architecture	Intel 855PM chipset / 82855PM Memory Controller Hub (MCH-M) / 82801DBM ICH4-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count [LPC] interface, USB, [Bluetooth]) / PCI bus 2.2 32-bit, 33MHz (TI® PCI4520A CardBus and 1394 controller, Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared, [docking-based ports])																	
PC Card Std slots	One Type I, one Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf							
Ports	Two USB (Version 2.0) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port																	
Video out	S-video out port (TV out) / one 4-pin industry standard connector																	
IEEE 1394	IEEE 1394 (FireWire) port / 4-pin connector / 1394a-2000 standard																	
Wireless antenna	UltraConnect™ Antenna built into the display cover for optimal wireless signal reception																	
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf							
11b Wi-Fi ³²	Some: 11b Wi-Fi ³² wireless ⁴ , Mini PCI, Intel PRO/Wireless 2100, Intel 82531 chipset																	
11a/b/g Wi-Fi ³²	Some: 11a/b/g Wi-Fi ³² wireless ⁴ , Mini PCI, Atheros™ AR5001X+ chipset																	
CDC	One Communications Daughter Card (CDC) socket (used by modem) / not accessible																	
Modem	56K ⁶ V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset																	
Bluetooth	None										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf							
Ethernet	Gigabit Ethernet on planar / Intel 82540EP chipset (MAC/PHY) / Wake on LAN®																	
Audio support	Soft audio / ICH AC97 controller / DirectSound® support / AD1981B AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack																	
Security	Power-on password / hard disk password / supervisor password / security keyhole																	
Security chip	IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant																	
Limited warranty ¹²	3 years/1 yr battery - EasyServ™. ¹⁹ onsite pickup and delivery / service upgrades ²² avail										ServicePac 3 yr IOR 9x5 NBD 30L9197 ServicePac 4 yr IOR 9x5 NBD 69P9198 ServicePac 5 yr IOR 9x5 NBD 69P9200 ServicePac 4 yr P&L P/U Depot 69P9199 ServicePac 5 yr P&L P/U Depot 69P9201 Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf							
128MB PC2700 DDR-SDRAM CL2.5 SOD	31P9828	T40/R50 Series Li-Ion Battery 6-cell	08K8214															
256MB PC2700 DDR-SDRAM CL2.5 SOD	31P9830	T40/R50 High Capacity Li-Ion Batt 9-cell	08K8197															
512MB PC2700 DDR-SDRAM CL2.5 SOD	31P9832	Ultrabay Slim Li-Polymer Battery 3-cell	08K8190															
1GB PC2700 DDR-SDRAM CL2.5 SOD	31P9834	ThinkPad Multiple Battery Charger II	22P9040															
Second HDD Adapter for Ultrabay Slim	62P4554	30GB Hard Disk 9.5mm (4200 rpm)	09N4268															
ThinkPad DVD-ROM Ultrabay Slim Drive	73P3270	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816															
CD-RW/DVD Combo Ultrabay Enhanced	73P3275	80GB HS Hard Disk 9.5mm (5400 rpm)	09N4273															
Multi-Burner Ultrabay Enhanced Drive	73P3282	Intel PRO/Wireless 2200BG Mini PCI	73P2801															
Portable 40GB USB 2.0 with Rapid Restore	09N4255	IBM 11a/b/g Wireless Mini PCI Adapter	31P9701															
IBM USB Portable Diskette Drive	05K9276	IBM 11a/b/g Wireless CardBus Adapter	31P9101															
IBM USB 2.0 Portable Multi-Burner Drive	22P9163	ThinkPad Port Replicator II	74P6733															
ThinkPad 72W AC/DC Combo Adapter	22P9010	ThinkPad Mini Dock	287810U															
Other options at ibm.com/pc/us/accessories											ThinkPad Dock II	287710U						

See footnotes for important warranty information
US models announced October 7, 2003
US models withdrawn effective July 2004

* Powered by Intel Centrino™ mobile technology

(R50E) © IBM Corp. July 2004

IBM® ThinkPad® R50 (1836) - Express - withdrawn

Created by IBM PC Institute
Personal Systems Reference (PSREF)

Type-model	Processor	Speed GHz	Memory GB	Screen	Graphics controller	Disk GB ³	Optical	Mini PCI Comm Bay wireless	CDC modem/ Bluetooth™	Ethernet on planar	IEEE 1394 port	Security chip	Battery Preload	Workhorse (W) Global (G) Entry (E)	Avail date	
1836-2NU	Pentium® M 1.4	256MB	14.1"	XGA	7500	40G	DVD	*Intel 11b Wi-Fi ³²	Modem	10/100	Yes	6	XP Pro	No	Oct 2003	
1836-2PU	Pentium M 1.4	256MB	14.1"	XGA	7500	40G	Combo	Open; wireless upg ³⁶	Modem	Gigabit	1394	Yes	6	XP Pro	No	Oct 2003
1836-2QU	Pentium M 1.4	256MB	14.1"	XGA	7500	40G	Combo	*Intel 11b Wi-Fi	Modem	Gigabit	1394	Yes	6	XP Pro	No	Oct 2003
1836-2RU	Pentium M 1.4	256MB	14.1"	XGA	7500	60G	Combo	11a/b/g Wi-Fi ³²	Modem	Gigabit	1394	Yes	9	XP Pro	No	Oct 2003
1836-2SU	Pentium M 1.5	256MB	14.1"	XGA	7500	40G	Combo	Open; wireless upg	Modem	Gigabit	1394	Yes	6	XP Pro	No	Oct 2003
1836-2TU	Pentium M 1.5	256MB	14.1"	XGA	7500	40G	Combo	*Intel 11b Wi-Fi	Modem	Gigabit	1394	Yes	6	XP Pro	No	Oct 2003
1836-2UU	Pentium M 1.5	256MB	14.1"	XGA	7500	60G	Combo	11a/b/g Wi-Fi	Modem	Gigabit	1394	Yes	9	XP Pro	No	Oct 2003
1836-3NU	Pentium M 1.4	256MB	15.0"	XGA	7500	40G	DVD	Open; wireless upg	Modem	10/100	Yes	6	XP Pro	No	Oct 2003	
1836-3PU	Pentium M 1.4	256MB	15.0"	XGA	7500	40G	DVD	*Intel 11b Wi-Fi	Modem	10/100	Yes	6	XP Pro	No	Oct 2003	
1836-3QU	Pentium M 1.5	256MB	15.0"	XGA	7500	40G	DVD	Open; wireless upg	Modem	10/100	Yes	6	XP Pro	No	Oct 2003	
1836-3RU	Pentium M 1.5	256MB	15.0"	XGA	7500	40G	DVD	*Intel 11b Wi-Fi	Modem	10/100	Yes	6	XP Pro	No	Oct 2003	
1836-3SU	Pentium M 1.6	256MB	15.0"	SXGA+	9000	60G	Combo	11a/b/g Wi-Fi	Mod/Blue	Gigabit	1394	Yes	9	XP Pro	No	Oct 2003
1836-3TU	Pentium M 1.6	256MB	15.0"	SXGA+	9000	40G	Combo	Open; wireless upg	Modem	Gigabit	1394	Yes	6	XP Pro	No	Oct 2003
1836-3UU	Pentium M 1.6	256MB	15.0"	SXGA+	9000	40G	Combo	*Intel 11b Wi-Fi	Modem	Gigabit	1394	Yes	6	XP Pro	No	Oct 2003

These small and medium business (SMB) models are part of the IBM US Think Express Program

Positioning	Mainstream performance and features; two-spindle system										SOFTWARE¹⁴				
Processor	Intel® Pentium® M Processor 1.4, 1.5, or 1.6GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz system bus										Windows XP Pro models				
L2 cache	1MB / on die (at processor speed) / ECC										- Microsoft® Windows® XP Professional ²⁰				
Memory	256MB std / 2GB max ⁷ / PC2700 333MHz DDR-SDRAM / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available										- Disk-to-Disk Recovery (in hidden protected area)				
Diskette drive	None standard / use optional USB-based diskette drive										Preloaded				
DVD	<i>Some:</i> DVD-ROM / 8X-3.3X ⁹ speed / bootable / removable from Ultrabay Enhanced										• Access IBM				
Combo	<i>Some:</i> DVD-ROM/CD-RW / 24X/24X/24X/8X ²¹ speed / removable from Ultrabay Enhance										• Access Connections				
Ultrabay Enhanced	One modular bay for interchangeable devices / Ultrabay Slim-compatible / 12.7 mm high										• Adobe Acrobat Reader				
Disk	40GB⁸ (4200 rpm) or 60GB (4200 rpm), 9.5mm high / removable and upgradable / 9.5mm high bay / supports 2nd disk with optional 'Second HDD Adapter for Ultrabay Slim' / IBM Hard Disk Drive Shock Absorber / IBM Active Protection System										• IBM Rapid Restore™ Ultra				
Display	<i>Some:</i> 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits <i>Some:</i> 15.0" (381.0mm) XGA (1024x768) TFT color / Active Matrix / 200 nits <i>Some:</i> 15.0" (381.0mm) SXGA+ (1400x1050) TFT color / Active Matrix / 200 nits / FlexView display with wide viewing angle and high density using IPS technology										• IBM RecordNOW and IBM Drive Letter Access (combo models)				
Graphics controller	<i>Some:</i> ATI® Mobility™ RADEON™ 7500 / AGP 4X / 32MB DDR-SDRAM <i>Some:</i> ATI Mobility RADEON 9000 / AGP 4X / 32MB DDR-SDRAM										• Norton AntiVirus (OEM edition)				
Graphics - external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B										• PC-Doctor™				
Keyboard	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)										• ThinkPad Utilities				
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass										• IBM Update Connector™ ¹⁵				
Touch pad	UltraNav™ multi-pointing system / touch pad below keyboard / Tap Zones										Downloadable				
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions										• IBM Director Agent				
Dimensions ³	14.1" models (WxDxH): 12.4" x 10.2" x 1.35-1.46"; 314mm x 260mm x 34-37mm 15.0" models (WxDxH): 13.1" x 10.6" x 1.47-1.58"; 332mm x 269mm x 37-40mm										• Software Delivery Assistant				
Approximate weight ²	with optical drive and battery: 14.1" models: 5.7 to 6.2 lb; 15.0" models: 6.6 to 6.8 lb										• System Migration Assistant				
Case material	<i>Color:</i> black; <i>All:</i> Acrylonitrile-Butadiene-Styrene (ABS) plastic										• Client Security Software (for security chip)				
Battery - type	Lithium Ion 6- or 9-cell / intelligent / supports unique 2nd battery in Ultrabay Enhanced										License (CD not included)				
Battery - life ¹⁰	6-cell models: 4.0 to 4.7 hr; 9-cell models: 6.0 to 6.9 hr; optional 9-cell available for all										- Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client				
Architecture	Intel 855PM chipset / 82855PM Memory Controller Hub (MCH-M) / 82801DBM ICH4-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count [LPC] interface, USB, [Bluetooth]) / PCI bus 2.2 32-bit, 33MHz (TI® PCI4520A CardBus and 1394 controller, Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared, [docking-based ports])										Universal 72 watt AC adapter				
PC Card Std slots	One Type I, one Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door										Asset ID™ ³⁴ (system-specific info in chip accessed over network)				
Ports	Two USB (Version 2.0) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port										PC 2001 and PXE 2.0-compliant				
Video out	S-video out port (TV out) / one 4-pin industry standard connector										ACPI 1.0b and 2.0-compliant				
IEEE 1394	<i>Some:</i> IEEE 1394 (FireWire) port / 4-pin connector / 1394a-2000 standard										CIM and DMI 2.0-compliant				
Wireless antenna	UltraConnect™ Antenna built into the display cover for optimal wireless signal reception										IBM ImageUltra™ Services available				
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable										IBM Rapid Restore Ultra available to protect software image and data				
Wireless upg ³⁶	<i>Some:</i> wireless upgradable with wireless Mini PCI options										International Warranty Service ¹⁷				
11b Wi-Fi ³²	<i>Some:</i> 11b Wi-Fi ³² wireless ⁴ , Mini PCI, Intel PRO/Wireless 2100, Intel 82531 chipset										24 hour x 7 day ¹⁸ toll-free warranty support during the warranty ¹²				
11a/b/g Wi-Fi ³²	<i>Some:</i> 11a/b/g Wi-Fi ³² wireless ⁴ , Mini PCI, Atheros™ AR5001X+ chipset										ServicePac ²² 1yr IOR 9x5 NBD 30L9188				
CDC	One Communications Daughter Card (CDC) socket (used by modem) / not accessible										ServicePac 2 yr IOR 9x5 NBD 30L9189				
Modem	56K ⁵ V.90 (V.92-designed ²⁹) modem in CDC / Agere® chipset										ServicePac 3 yr IOR 9x5 NBD 30L9195				
Bluetooth	<i>Some:</i> Bluetooth wireless technology / in CDC (with modem)										ServicePac 4 yr IOR 9x5 NBD 30L9194				
Ethernet	<i>Some:</i> 10/100 ethernet on planar / Intel 82562EZ chipset (physical layer) / Wake on LAN®										ServicePac 5 yr IOR 9x5 NBD 30L9196				
Audio support	<i>Some:</i> Gigabit Ethernet on planar / Intel 82540EP chipset (MAC/PHY) / Wake on LAN										ServicePac 2 yr P&L P/U Depot 30L9191				
Security	Soft audio / ICH AC97 controller / DirectSound® support / AD1981B AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack										ServicePac 3 yr P&L P/U Depot 30L9192				
Security chip	Power-on password / hard disk password / supervisor password / security keyhole										ServicePac 4 yr P&L P/U Depot 69P9195				
Limited warranty ¹²	1 year - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² available										ServicePac 5 yr P&L P/U Depot 69P9197				
128MB PC2700 DDR-SDRAM CL2.5 SOD	31P9828			T40/R50 Series Li-Ion Battery 6-cell			08K8214			Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf					
256MB PC2700 DDR-SDRAM CL2.5 SOD	31P9830			T40/R50 High Capacity Li-Ion Batt 9-cell			08K8197								
512MB PC2700 DDR-SDRAM CL2.5 SOD	31P9832			ThinkPad Dock II			287710U								
1GB PC2700 DDR-SDRAM CL2.5 SOD	31P9834			Other options at ibm.com/pc/us/accessories											

See footnotes for important warranty information
US models announced October 7, 2003
US models withdrawn effective July 2004

* Powered by Intel Centrino™ mobile technology

(R50B) © IBM Corp. July 2004

Type-model	Processor	Speed	GHz	Memory	Screen	Graphics controller	Disk memory	Disk GB ⁸	Optical	Mini PCI Comm Bay wireless	CDC modem/Bluetooth™	Ethernet on planar	IEEE 1394 port	Security chip	Workhorse (W) Global (G) Avail date
1832-22U	Pentium® M	1.7	512MB	15.0"	UXGA	128MB	60G	DVD-RW	11a/b/g Wi-Fi ³²	Mod/Blue	Gigabit	No	Yes	XP Pro	W Nov 2003
1832-23U	Pentium M	1.7	512MB	15.0"	UXGA	128MB	60G	DVD-RW	* Intel 11b Wi-Fi ³²	Mod/Blue	Gigabit	No	Yes	XP Pro	W G Nov 2003
Positioning Processor	Mainstream performance and features; two-spindle system														
L2 cache	Intel® Pentium® M Processor 1.7GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz system bus														
Memory	1MB / on die (at processor speed) / ECC 512MB std / 2GB max ⁷ / PC2700 333MHz DDR1 (DDR-SDRAM) / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available														
Diskette drive	None standard / use optional USB-based diskette drive														
DVD-RW	CD-RW/DVD-RW Multi-Burner / writes to CD-R, CD-RW, DVD-RAM, DVD-R, DVD-RW / reads CD-ROM, CD-R, CD-RW, CD-Audio, DVD-ROM, DVD-R, DVD+R, DVD+RW, DVD-RW, DVD-Video, DVD-RAM / same as optional ThinkPad Multi-Burner Ultrabay Enhanced Drive Option / removable from Ultrabay Enhanced														
Ultrabay Enhanced Disk	One modular bay for interchangeable devices / Ultrabay Slim-compatible / 12.7 mm high 60GB⁸ Ultra HS (7200 rpm), 9.5mm high / removable and upgradable / 9.5mm high bay / supports 2nd disk with optional 'Second HDD Adapter for Ultrabay Slim' / IBM Hard Disk Drive Shock Absorber / IBM Active Protection System														
Display	15.0" (381mm) UXGA-IPS (1600x1200) TFT color / Active Matrix / 200 nits / 400:1 contrast ratio / 170-degree horizontal and vertical viewing angle / display uses in plane switching (IPS) technology / one latch to unlatch and open with one hand														
Graphics	ATI® Mobility™ FireGL™ T2 / AGP 4X / 128MB DDR1 / OpenGL® support														
Graphics external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B														
Keyboard	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)														
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass														
Touch pad	UltraNav™ multi-pointing system / touch pad below keyboard / Tap Zones														
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions														
Dimensions ³	(WxDxH): 13.1" x 10.6" x 1.47-1.58"; 332mm x 269mm x 37-40mm														
Weight ²	with optical drive and battery: 7.1 lb (3.2kg)														
Case material	Color: black; All: Acrylonitrile-Butadiene-Styrene (ABS) plastic														
Battery - type	Lithium Ion 9-cell / intelligent / supports unique 2nd battery in Ultrabay Enhanced														
Battery - life ¹⁰	5.9 hr; with optional Ultrabay Slim Li-Polymer Battery: 8.0 hr														
Architecture	Intel 855PM chipset / 82855PM Memory Controller Hub (MCH-M) / 82801DBM ICH4-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count [LPC] interface, USB, [Bluetooth]) / PCI bus 2.2 32-bit, 33MHz (TI® PCI4520A CardBus and 1394 controller, Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for diskette, parallel, infrared, [docking-based ports])														
PC Card Std slots	Two Type I, two Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door														
Ports	Two USB (Version 2.0) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port														
Video out	S-video out port (TV out) / one 4-pin industry standard connector														
IEEE 1394	None														
Wireless antenna	UltraConnect™ Antenna built into the display cover for optimal wireless signal reception														
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable <i>Some:</i> 11b Wi-Fi ³² wireless ⁴ , Mini PCI, Intel PRO/Wireless 2100, Intel 82531 chipset <i>Some:</i> 11a/b/g Wi-Fi ³² wireless ⁴ , Mini PCI, Atheros™ AR5001X+ chipset														
CDC	One Communications Daughter Card (CDC) socket (used by modem) / not accessible														
Modem	56K ⁵ V.90 (V.92-designed ²⁵) modem in CDC / Agere® chipset														
Bluetooth	Bluetooth wireless technology / in CDC (with modem)														
Ethernet	Gigabit Ethernet on planar / Intel 82540EP chipset (MAC/PHY) / Wake on LAN®														
Audio support	Soft audio / ICH AC97 controller / DirectSound® support / AD1981B AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack														
Security	Power-on password / hard disk password / supervisor password / security keyhole														
Security chip	IBM Embedded Security Subsystem 2.0³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant														
Limited warranty ¹²	3 years /1 yr battery - EasyServ™ ¹⁹ onsite pickup and delivery courier service														
Service options	Service upgrades ²² provide up to five years of onsite or depot repair service coverage from date of ThinkPad purchase (including warranty period)														
128 MB PC2700 DDR-SDRAM CL2.5 SOD	31P9828	T40/R50 Series Li-Ion Battery 6-cell	08K8214												
256 MB PC2700 DDR-SDRAM CL2.5 SOD	31P9830	T40/R50 High Capacity Li-Ion Batt 9-cell	08K8197												
512 MB PC2700 DDR-SDRAM CL2.5 SOD	31P9832	Ultrabay Slim Li-Polymer Battery 3-cell	08K8190												
1 GB PC2700 DDR-SDRAM CL2.5 SOD	31P9834	ThinkPad Multiple Battery Charger II	22P9040												
Second HDD Adapter for Ultrabay Slim	62P4554	IBM USB Travel Keyboard with UltraNav	31P9490												
ThinkPad DVD-ROM Ultrabay Slim Drive	73P3270	30GB Hard Disk 9.5mm (4200 rpm)	09N4268												
CD-RW/DVD Combo Ultrabay Enhanced	73P3275	40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816												
Multi-Burner Plus Ultrabay Enhanced Drive	73P3312	80GB HS Hard Disk 9.5mm (5400 rpm)	09N4273												
IBM 4GB Microdrive™ with PC Card	09N4280	Intel PRO/Wireless 2200BG Mini PCI	73P2801												
IBM USB Portable Diskette Drive	05K9276	IBM 11a/b/g Wireless Mini PCI Adptr II	73P4301												
IBM USB Serial Parallel Adapter	22P5298	IBM 11a/b/g Wireless CardBus Adapter	31P9101												
IBM USB 2.0 Portable Multi-Burner Drive	22P9163	ThinkPad 72W AC Adapter	02K6699												
IBM USB 2.0 Portable 40GB Hard Disk	22P7196	ThinkPad 72W AC/DC Combo Adapter	22P9010												
IBM USB 2.0 Memory Key 256MB	22P9228	ThinkPad Port Replicator II	74P6733												
IBM USB 2.0 Memory Key 512MB	22P9230	ThinkPad Mini Dock	287810U												
IBM M400 Projector	0037A04	ThinkPad Dock II	287710U												
IBM Enh Perf Wireless Keyboard and Mouse	73P4067	IBM Optical 3-Button Travel Wheel Mouse	31P7410												
ThinkPad Premiere Leather Carrying Case	10K0209	Other options at ibm.com/pc/us/accessories													
SOFTWARE¹⁴															
Windows XP Professional															
- Microsoft® Windows® XP Professional ²⁰															
◆ Disk-to-Disk Recovery (in hidden protected area)															
Preloaded															
• Access IBM															
• Access Connections															
• Adobe Reader															
• IBM Rapid Restore™ Ultra															
• IBM RecordNOW and IBM Drive Letter Access by Sonic															
• InterVideo WinDVD															
• InterVideo WinDVD Creator															
• Norton AntiVirus (OEM edition)															
• PC-Doctor™															
• ThinkPad Utilities															
• IBM Update Connector™ ¹⁵															
Downloadable															
• IBM Director Agent															
• Software Delivery Assistant															
• System Migration Assistant															
• Client Security Software (for security chip)															
License (CD not included)															
- Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client															
ThinkPad notebooks implement IBM ThinkVantage™ technologies and design; visit ibm.com/thinkvantage															
Universal 72 watt AC adapter Asset ID™ ³⁴ (system-specific info in chip accessed over network)															
PC 2001 and PXE 2.0-compliant ACPI 1.0b and 2.0-compliant CIM and DMI 2.0-compliant ENERGY STAR®-compliant IBM ImageUltra™ Services available IBM Rapid Restore Ultra available to protect software image and data International Warranty Service ¹⁷ 24 hour x 7 day ¹⁸ toll-free warranty support during the warranty ¹² via 800-IBM-SERV (426-7378)															
ServicePac®. ²² 2 yr IOR 9x5 NBD 30L9190															
ServicePac 3 yr IOR 9x5 NBD 30L9197															
ServicePac 4 yr IOR 9x5 NBD 69P9198															
ServicePac 5 yr IOR 9x5 NBD 69P9200															
ServicePac 4 yr P&L P/U Depot 69P9199															
ServicePac 5 yr P&L P/U Depot 69P9201															
Other ServicePac options at ibm.com/services/its/us/source/wamomxeu.pdf															
Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf															

See footnotes for important warranty information
US models announced October 28, 2003
US models withdrawn effective January 2005

* Powered by Intel Centrino™ mobile technology

Type-model	Processor	Speed GHz	Memory GB	Screen	Graphics controller	Disk GB ³	Optical	Mini PCI Comm Bay wireless	CDC modem/ Bluetooth™	Ethernet on planar	IEEE1394 port	Security chip	Workhorse (W) Global (G) Preload Entry (E)	Avail date	
1836-A4U	Pentium® M	1.5	256MB	14.1" XGA	7500	40GB	Combo	*Intel 11b/g Wi-Fi ³²	Modem	10/100		Yes	XP Pro	No	Apr 2004
1836-A5U	Pentium M	1.5	256MB	14.1" XGA	9000	60GB	DVD-RW	11a/b/g Wi-Fi ³²	Modem	Gigabit	1394	Yes	XP Pro	No	Apr 2004
1836-BAU	Pentium M	1.5	256MB	15.0" XGA	7500	40GB	Combo	*Intel 11b/g Wi-Fi	Modem	10/100		Yes	XP Pro	No	Apr 2004
1836-BBU	Pentium M	1.6	256MB	15.0" SXGA+	9000	60GB	Combo	*Intel 11b/g Wi-Fi	Modem	Gigabit	1394	Yes	XP Pro	No	Apr 2004
1836-BCU	Pentium M	1.6	256MB	15.0" SXGA+	9000	80GB	DVD-RW	11a/b/g Wi-Fi	Mod/Blue	Gigabit	1394	Yes	XP Pro	No	Apr 2004
1836-BDU	Pentium M	1.5	256MB	15.0" SXGA+	7500	40GB	Combo	*Intel 11b/g Wi-Fi	Modem	10/100		Yes	XP Pro	No	Apr 2004

These small and medium business (SMB) models are part of the IBM US Think Express Program

Positioning Processor	Mainstream performance and features; two-spindle system Intel® Pentium® M Processor 1.5 or 1.6GHz with enhanced Intel SpeedStep™ technology ¹ and 400MHz system bus											SOFTWARE¹⁴	
L2 cache	1MB / on die (at processor speed) / ECC											Windows XP Professional	
Memory	256MB std / 2GB max ⁷ / PC2700 333MHz DDR1 (DDR-SDRAM) / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available											- Microsoft® Windows® XP Professional ²⁰ ♦ Disk-to-Disk Recovery (in hidden protected area)	
Diskette drive	None standard / use optional USB-based diskette drive											Preloaded	
Combo DVD-RW	Some: DVD-ROM/CD-RW / 24X/24X/24X/8X ²¹ speed / removable from Ultrabay Enhance Some: CD-RW/DVD-RW Multi-Burner / removable from Ultrabay Enhanced											• Access IBM	
Ultrabay Enhanced Disk	One modular bay for interchangeable devices / Ultrabay Slim-compatible / 12.7 mm high 40GB⁸ (4200 rpm), 60GB (4200 rpm), or 80GB (4200 rpm) / 9.5mm high / removable and upgradable / 9.5mm high bay / supports 2nd disk with optional 'Second HDD Adapter for Ultrabay Slim' / IBM Hard Disk Drive Shock Absorber / IBM Active Protection System											• Access Connections	
Display	Some: 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits Some: 15.0" (381.0mm) XGA (1024x768) TFT color / Active Matrix / 200 nits Some: 15.0" (381.0mm) SXGA+ (1400x1050) TFT color / Active Matrix / 200 nits / FlexView display with wide viewing angle and high density using IPS technology											• IBM Rescue and Recovery™	
Graphics	Some: ATI® Mobility™ RADEON™ 7500 / AGP 4X / 32MB DDR1 (DDR-SDRAM) Some: ATI Mobility RADEON 9000 / AGP 4X / 32MB DDR1 (DDR-SDRAM)											• IBM RecordNOW and Drive Letter Access powered by Sonic products (combo, DVD-RW)	
Graphics external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B											• InterVideo WinDVD (combo, DVD-RW)	
Keyboard	87-key / Acss IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)											• InterVideo WinDVD Creator (DVD-RW)	
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass											• Norton AntiVirus (OEM edition)	
Touch pad	UltraNav™ multi-pointing system / touch pad below keyboard / Tap Zones											• PC-Doctor™	
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions											• ThinkPad Utilities	
Dimensions ³	14.1" models (WxDxH): 12.4" x 10.2" x 1.35-1.46"; 314mm x 260mm x 34-37mm 15.0" models (WxDxH): 13.1" x 10.6" x 1.47-1.58"; 332mm x 269mm x 37-40mm											• Adobe Reader	
Weight ²	with optical drive and battery: 14.1" models: 6.0 lb (2.7kg); 15.0" models: 6.6 lb (3.0kg)											• IBM Update Connector™ ¹⁵	
Case material	Color: black; All: Acrylonitrile-Butadiene-Styrene (ABS) plastic											Downloadable	
Battery - type	Lithium Ion 6-cell / intelligent / supports unique 2nd battery in Ultrabay Enhanced											• IBM Director Agent	
Battery - life ¹⁰	Model BBU/BCU/BDU with SXGA+: 4.0 hr; Others: 4.7 hr; Optional 9-cell: up to 6.9 hr											• Software Delivery Assistant	
Architecture	Intel 855PM chipset / 82855PM Memory Controller Hub (MCH-M) / 82801DBM ICH4-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count [LPC] interface, USB, [Bluetooth]) / PCI bus 2.2 32-bit, 33MHz (TI® PCI4520A CardBus and 1394 controller, Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for parallel, infrared, [docking-based ports]) One Type I, one Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door											• System Migration Assistant	
PC Card Std slots	Two USB (Version 2.0) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port											• Client Security Software (for security chip)	
Ports	S-video out port (TV out) / one 4-pin industry standard connector Some: IEEE 1394 (FireWire) port / 4-pin connector / 1394a-2000 standard UltraConnect™ Antenna built into the display cover for optimal wireless signal reception One Mini PCI type III slot (Communications Bay) / customer upgradable											License (CD not included) - Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client	
Video out	Some: 11b/g Wi-Fi ³² wireless ⁴ , Mini PCI, Intel PRO/Wireless 2200BG, Intel 82532 chipset Some: 11a/b/g Wi-Fi ³² wireless ⁴ , Mini PCI, Atheros™ AR5001X+ chipset											ThinkPad notebooks implement IBM ThinkVantage™ technologies and design; visit ibm.com/thinkvantage	
IEEE 1394	One Communications Daughter Card (CDC) socket (used by modem) / not accessible											Universal 72 watt AC adapter Asset ID™ ³⁴ (system-specific info in chip accessed over network)	
Wireless antenna	Some: Bluetooth wireless technology / in CDC (with modem) Some: 10/100 ethernet on planar / Intel 82562EZ chipset (physical layer) / Wake on LAN® Some: Gigabit Ethernet on planar / Intel 82540EP chipset (MAC/PHY) / Wake on LAN											PC 2001 and PXE 2.0-compliant ACPI 1.0b and 2.0-compliant CIM and DMI 2.0-compliant ENERGY STAR®-compliant IBM ImageUltra™ Services available International Warranty Service ¹⁷ 24 hour x 7 day ¹⁸ toll-free warranty support during the warranty ¹²	
Mini PCI	Some: Bluetooth wireless technology / in CDC (with modem) Some: 10/100 ethernet on planar / Intel 82562EZ chipset (physical layer) / Wake on LAN® Some: Gigabit Ethernet on planar / Intel 82540EP chipset (MAC/PHY) / Wake on LAN											ServicePac®, ²² 1yr IOR 9x5 NBD 30L9188	
Intel 11b/g ³²	Soft audio / ICH AC97 controller / DirectSound® support / AD1981B AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack											ServicePac 2 yr IOR 9x5 NBD 30L9189	
11a/b/g Wi-Fi ³²	Power-on password / hard disk password / supervisor password / security keyhole											ServicePac 3 yr IOR 9x5 NBD 30L9195	
CDC	IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant											ServicePac 4 yr IOR 9x5 NBD 30L9194	
Modem	Limited warranty ¹² 1 year - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² available											ServicePac 5 yr IOR 9x5 NBD 30L9196	
Bluetooth	128MB PC2700 DDR-SDRAM CL2.5 SOD 31P9828											ServicePac 2 yr P&L P/U Depot 30L9191	
Ethernet	256MB PC2700 DDR-SDRAM CL2.5 SOD 31P9830											ServicePac 3 yr P&L P/U Depot 30L9192	
Audio support	512MB PC2700 DDR-SDRAM CL2.5 SOD 31P9832											ServicePac 4 yr P&L P/U Depot 69P9195	
Security	1GB PC2700 DDR-SDRAM CL2.5 SOD 31P9834											ServicePac 5 yr P&L P/U Depot 69P9197	
Security chip	Second HDD Adapter for Ultrabay Slim 62P4554											Post-warranty annual maintenance agreements at ibm.com/services/its/us/source/maspspleu.pdf	
Limited warranty ¹²	CD-RW/DVD Combo Ultrabay Enhanced 73P3275												
	Multi-Burner Plus Ultrabay Enhanced Drive 73P3312												
	IBM USB Portable Diskette Drive 05K9276												
	IBM USB 2.0 Combo Drive 73P4515												
	IBM USB 2.0 Portable Multi-Burner Drive 22P9163												
	40GB HS Hard Disk 9.5mm (5400 rpm) 08K9816												
	80GB HS Hard Disk 9.5mm (5400 rpm) 09N4273												
	T40/R50 Series Li-Ion Battery 6-cell 08K8214												
	T40/R50 High Capacity Li-Ion Batt 9-cell 08K8197												
	Ultrabay Slim Li-Polymer Battery 3-cell 08K8190												
	Intel PRO/Wireless 2200BG Mini PCI 73P2801												
	IBM 11a/b/g Wireless Mini PCI Adapter II 73P4301												
	IBM 11a/b/g Wireless CardBus Adapter 31P9101												
	ThinkPad 72W AC/DC Combo Adapter 22P9010												
	ThinkPad Port Replicator II 74P6733												
	ThinkPad Mini Dock 287810U												
	ThinkPad Dock II 287710U												
	ThinkPad Carrying Case - Leather 73P3600												
	Other options at ibm.com/pc/us/accessories												

See footnotes for important warranty information
US models announced April 6, 2004
US models withdrawn effective January 2005

* Powered by Intel Centrino™ mobile technology

Type-model	Processor	Speed GHz	Memory	Screen	Graphics controller	Disk GB ⁸	Optical	Mini PCI Comm Bay wireless	CDC modem/Bluetooth™	Ethernet on planar	IEEE 1394 port	Security chip	Workhorse (W) Global (G) Entry (E)	Avail date
1836-GCU	Pentium® M 715	1.5	256MB	14.1" XGA	7500	40GB	Combo	* Intel 11b/g Wi-Fi ³²	Modem	10/100		Yes	No	Jul 2004
1836-GDU	Pentium M 715	1.5	256MB	14.1" XGA	9000	60GB	DVD-RW	11a/b/g Wi-Fi ³²	Modem	Gigabit	1394	Yes	No	Jul 2004
1836-H7U	Pentium M 715	1.5	256MB	15.0" XGA	7500	40GB	Combo	* Intel 11b/g Wi-Fi	Modem	10/100		Yes	No	Jul 2004
1836-H8U	Pentium M 715	1.5	256MB	15.0" SXGA+	7500	40GB	Combo	* Intel 11b/g Wi-Fi	Modem	10/100		Yes	No	Jul 2004
1836-H9U	Pentium M 725	1.6	256MB	15.0" SXGA+	9000	60GB	Combo	* Intel 11b/g Wi-Fi	Modem	Gigabit	1394	Yes	No	Jul 2004
1836-HAU	Pentium M 725	1.6	256MB	15.0" SXGA+	9000	80GB	DVD-RW	11a/b/g Wi-Fi	Mod/Blue	Gigabit	1394	Yes	No	Jul 2004

These small and medium business (SMB) models are part of the IBM US Think Express Program

Positioning Processor	Mainstream performance and features; two-spindle system Intel® Pentium® M Processor 715 (1.5GHz) or 725 (1.6GHz) with enhanced Intel SpeedStep™ technology ¹ and 400MHz system bus												
L2 cache	2MB / on die (at processor speed) / ECC												
Memory	256MB std / 2GB max ⁷ / PC2700 333MHz DDR1 (DDR-SDRAM) / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available												
Diskette drive	None standard / use optional USB-based diskette drive												
Combo DVD-RW	Some: DVD-ROM/CD-RW / 24X/24X/24X/8X ²¹ speed / removable from Ultrabay Enhance Some: CD-RW/DVD-RW Multi-Burner / removable from Ultrabay Enhanced												
Ultrabay Enhanced Disk	One modular bay for interchangeable devices / Ultrabay Slim-compatible / 12.7 mm high 40GB⁸ (4200 rpm), 60GB (4200 rpm), or 80GB (4200 rpm) / 9.5mm high / removable and upgradable / 9.5mm high bay / supports 2nd disk with optional 'Second HDD Adapter for Ultrabay Slim' / IBM Hard Disk Drive Shock Absorber / IBM Active Protection System												
Display	Some: 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits Some: 15.0" (381.0mm) XGA (1024x768) TFT color / Active Matrix / 200 nits Some: 15.0" (381.0mm) SXGA+ (1400x1050) TFT color / Active Matrix / 200 nits / FlexView display with wide viewing angle and high density using IPS technology												
Graphics	Some: ATI® Mobility™ RADEON™ 7500 / AGP 4X / 32MB DDR1 (DDR-SDRAM) Some: ATI Mobility RADEON 9000 / AGP 4X / 32MB DDR1 (DDR-SDRAM)												
Graphics external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B												
Keyboard	87-key / Accs IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)												
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass												
Touch pad	UltraNav™ multi-pointing system / touch pad below keyboard / Tap Zones												
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions												
Dimensions ³	14.1" models (WxDxH): 12.4" x 10.2" x 1.35-1.46"; 314mm x 260mm x 34-37mm 15.0" models (WxDxH): 13.1" x 10.6" x 1.47-1.58"; 332mm x 269mm x 37-40mm												
Weight ²	with optical drive and battery: 14.1" models: 6.0 lb (2.7kg); 15.0" models: 6.6 lb (3.0kg)												
Case material	Color: black; All: Acrylonitrile-Butadiene-Styrene (ABS) plastic												
Battery - type	Lithium Ion 6-cell / intelligent / supports unique 2nd battery in Ultrabay Enhanced												
Battery - life ¹⁰	Up to 4.7 hr; <i>Optional High Capacity 9-cell:</i> up to 6.9 hr												
Architecture	Intel 855PM chipset / 82855PM Memory Controller Hub (MCH-M) / 82801DBM ICH4-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count [LPC] interface, USB, [Bluetooth]) / PCI bus 2.2 32-bit, 33MHz (TI® PCI4520A CardBus and 1394 controller, Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for parallel, infrared, [docking-based ports]) One Type I, one Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door												
PC Card Std slots	Two USB (Version 2.0) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port												
Ports	S-video out port (TV out) / one 4-pin industry standard connector Some: IEEE 1394 (FireWire) port / 4-pin connector / 1394a-2000 standard UltraConnect™ Antenna built into the display cover for optimal wireless signal reception One Mini PCI type III slot (Communications Bay) / customer upgradable												
Video out	Some: 11b/g Wi-Fi ³² wireless ⁴ , Mini PCI, Intel PRO/Wireless 2200BG, Intel 82532 chipset												
IEEE 1394	Some: 11a/b/g Wi-Fi ³² wireless ⁴ , Mini PCI, Atheros™ AR5001X+ chipset												
Wireless antenna	One Communications Daughter Card (CDC) socket (used by modem) / not accessible												
Mini PCI	Some: 56K ⁶ V.90 (V.92-designed ²⁹) modem in CDC / Conexant® chipset												
Intel 11b/g ³²	Some: Bluetooth wireless technology / in CDC (with modem)												
11a/b/g Wi-Fi ³²	Some: 10/100 ethernet on planar / Intel 82562EZ chipset (physical layer) / Wake on LAN®												
CDC	Some: Gigabit Ethernet on planar / Intel 82540EP chipset (MAC/PHY) / Wake on LAN												
Modem	Soft audio / ICH AC97 controller / DirectSound® support / AD1981B AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack												
Bluetooth	Power-on password / hard disk password / supervisor password / security keyhole												
Ethernet	IBM Embedded Security Subsystem 2.0³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant												
Audio support	IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant												
Security	IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant												
Security chip	IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant												
Limited warranty ¹²	1 year - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² available												
128MB PC2700 DDR-SDRAM CL2.5 SOD	31P9828	T40/R50 Series Li-Ion Battery 6-cell	08K8214	ServicePac 2 yr P&L P/U Depot	30L9188								
256MB PC2700 DDR-SDRAM CL2.5 SOD	31P9830	T40/R50 High Capacity Li-Ion Batt 9-cell	08K8197	ServicePac 3 yr P&L P/U Depot	30L9191								
512MB PC2700 DDR-SDRAM CL2.5 SOD	31P9832	Ultrabay Slim Li-Polymer Battery 3-cell	08K8190	ServicePac 4 yr P&L P/U Depot	69P9195								
1GB PC2700 DDR-SDRAM CL2.5 SOD	31P9834	Intel PRO/Wireless 2200BG Mini PCI	73P2801	ServicePac 5 yr P&L P/U Depot	69P9197								
Second HDD Adapter for Ultrabay Slim	62P4554	IBM 11a/b/g Wireless Mini PCI Adapter II	73P4301	Post-warranty annual maintenance agreements at									
CD-RW/DVD Combo Ultrabay Enhanced	73P3275	IBM 11a/b/g Wireless CardBus Adapter	31P9101	ibm.com/services/its/us/source/maspspleu.pdf									
Multi-Burner Plus Ultrabay Enhanced Drive	73P3312	ThinkPad 72W AC/DC Combo Adapter	22P9010										
IBM USB Portable Diskette Drive	05K9276	ThinkPad Port Replicator II	74P6733										
IBM USB 2.0 Combo Drive	73P4515	ThinkPad Mini Dock	287810U										
IBM USB 2.0 Portable Multi-Burner Drive	22P9163	ThinkPad Dock II	287710U										
40GB HS Hard Disk 9.5mm (5400 rpm)	08K9816	ThinkPad Carrying Case - Backpack	73P3599										
80GB HS Hard Disk 9.5mm (5400 rpm)	09N4273	Other options at ibm.com/pc/us/accessories											

See footnotes for important warranty information
US models announced July 13, 2004
US models withdrawn effective January 2005

* Powered by Intel Centrino™ mobile technology

IBM® ThinkPad® R51 (2883) - Express - withdrawn

Created by IBM PC Institute
Personal Systems Reference (PSREF)

Type-model	Processor	Speed GHz	Memory	Screen	Disk GB ^a	Optical	Mini PCI Comm Bay wireless	CDC modem	Integrated graphics	Secu- rity warranty ¹²	Limited warranty ¹²	Workhorse (W) Global (G) Avail date
2883-2ZU	Celeron® M	1.3	256MB	15.0" XGA	30GB	Combo	Open; wireless upg ³⁶	Modem	Extreme™	2	Yes	1 yr XP Pro No Apr 2004
2883-2NU	Pentium® M	1.5	256MB	14.1" XGA	30GB	Combo *	Intel 11b/g Wi-Fi ³²	Modem	Extreme 2	2	Yes	1 yr XP Pro No Apr 2004
2883-2XU	Pentium M	1.5	256MB	14.1" XGA	20GB	Combo *	Intel 11b/g Wi-Fi	Modem	Extreme 2	2	Yes	1 yr XP Pro No Apr 2004
2883-2QU	Pentium M	1.5	256MB	15.0" XGA	30GB	Combo *	Intel 11b/g Wi-Fi	Modem	Extreme 2	2	Yes	1 yr XP Pro No Apr 2004
2883-2YU	Pentium M	1.5	256MB	15.0" XGA	20GB	Combo *	Intel 11b/g Wi-Fi	Modem	Extreme 2	2	Yes	1 yr XP Pro No Apr 2004
2883-8QU	Pentium M 715	1.5	256MB	14.1" XGA	30GB	Combo *	Intel 11b/g Wi-Fi	Modem	Extreme 2	2	Yes	1 yr XP Pro No July 2004
2883-ARU	Pentium M 715	1.5	256MB	15.0" XGA	30GB	Combo *	Intel 11b/g Wi-Fi	Modem	Extreme 2	2	Yes	1 yr XP Pro No July 2004
<p>• These small and medium business (SMB) models are part of the IBM US Think Express Program • The 2883 has a 1 year limited warranty</p>												
Positioning	Mainstream performance and features; two-spindle system										SOFTWARE¹⁴	
Processor	Intel® Celeron M Processor 1.3GHz with 400MHz system bus or Intel Pentium M Processor 1.5GHz or Intel Pentium M Processor 715 (1.5GHz) with enhanced Intel SpeedStep™ technology ¹ and 400MHz system bus										Windows XP Professional	
L2 cache	Celeron M: 512KB; Pentium M: 1MB; Pentium M 715: 2 MB; All: ECC										- Microsoft® Windows® XP Professional ²⁰	
Memory	256MB std / 2GB max ⁷ / PC2700 333MHz DDR1 (DDR-SDRAM) / non-parity / CL2.5 / two 200-pin SO-DIMM sockets / std memory in one socket / one socket available										✦ Disk-to-Disk Recovery (in hidden protected area)	
Diskette drive	None standard / use optional USB-based diskette drive										Preloaded	
Combo	DVD-ROM/CD-RW / 24X/24X/24X/8X ²¹ speed / removable from Ultrabay Enhance										• Access IBM	
Ultrabay Enhanced	One modular bay for interchangeable devices / Ultrabay Slim-compatible / 12.7 mm high										• Access Connections	
Disk	20GB ⁸ or 30GB (4200 rpm), 9.5mm high / removable and upgradable / 9.5mm high bay / supports 2nd disk with optional 'Second HDD Adapter for Ultrabay Slim' / IBM Hard Disk Drive Shock Absorber / IBM Active Protection System										• IBM Rescue and Recovery™	
Display	Some: 14.1" (358.1mm) XGA (1024x768) TFT color / Active Matrix / 150 nits										• IBM RecordNOW and Drive Letter Access powered by Sonic products (combo models)	
Graphics	Integrated Intel Extreme™ Graphics 2 / in 855GME GMCH / uses main memory (up to 64MB) / 250MHz										• InterVideo WinDVD (combo models)	
Graphics external	External monitor support via analog DB-15 connector / up to 1600x1200 at 85Hz / DDC2B										• Norton AntiVirus (OEM edition)	
Keyboard	87-key / Access IBM button / palm rest / pitch: 19mm; stroke: 2.7mm (std-size keys)										• PC-Doctor™	
TrackPoint®	TrackPoint® pointing device, "Press-to-Select," Internet Scroll Bar ¹³ , magnifying glass										• ThinkPad Utilities	
Touch pad	UltraNav™ multi-pointing system / touch pad below keyboard / Tap Zones										• Adobe Reader	
ThinkLight™	Illuminates the keyboard to improve visibility in low-light conditions										• IBM Update Connector™ ¹⁵	
Dimensions ³	14.1" models (WxDxH): 12.4" x 10.2" x 1.35-1.46"; 314mm x 260mm x 34-37mm										Downloadable	
Weight ²	15.0" models (WxDxH): 13.1" x 10.6" x 1.47-1.58"; 332mm x 269mm x 37-40mm										• IBM Director Agent	
Case material	Color: black; All: Acrylonitrile-Butadiene-Styrene (ABS) plastic										• Software Delivery Assistant	
Battery - type	Lithium Ion 6-cell / intelligent / supports unique 2nd battery in Ultrabay Enhanced										• System Migration Assistant	
Battery - life ¹⁰	Celeron M model: up to 3.5 hr; Pentium M models: up to 4.7 hr; Optional High Capacity 9-cell: up to 6.9 hr										• Client Security Software (for security chip)	
Architecture	Intel 855GME chipset / 82855GME Memory Controller Hub (MCH-M) / 82801DBM ICH4-M I/O Controller Hub (ATA-100 EIDE, PCI bus, ethernet MAC, Low Pin Count [LPC] interface, USB / PCI bus 2.2 32-bit, 33MHz (TI® PCI4510 CardBus and 1394 controller, Mini PCI, external expansion) / LPC bus 33MHz (security chip; PC87392 Super I/O for parallel, infrared, [docking-based ports])										License (CD not included)	
PC Card Std slots	One Type I, one Type II, or one Type III / CardBus 32-bit / PCMCIA 2.1 / integrated door										- Lotus® SmartSuite® Millennium and Lotus Notes® Stand-alone Client	
Ports	Two USB (Version 2.0) / parallel / external monitor (DB-15) / infrared (4Mbps) / RJ-11 (modem) / RJ-45 (ethernet) / no keyboard or mouse or serial port										ThinkPad notebooks implement IBM ThinkVantage technologies and design; visit ibm.com/thinkvantage	
Video out	S-video out port (TV out) / one 4-pin industry standard connector										Universal 72 watt AC adapter	
IEEE 1394	None										Asset ID™ ³⁴ (system-specific info in chip accessed over network)	
Wireless antenna	UltraConnect™ Antenna built into the display cover for optimal wireless signal reception										PC 2001 and PXE 2.0-compliant	
Mini PCI	One Mini PCI type III slot (Communications Bay) / customer upgradable										ACPI 1.0b and 2.0-compliant	
Wireless upg ³⁶	Some: wireless upgradable with wireless Mini PCI options										CIM and DMI 2.0-compliant	
Intel 11b/g ³²	Some: 11b/g Wi-Fi ³² wireless ⁴ , Mini PCI, Intel PRO/Wireless 2200BG, Intel 82532 chipset										ENERGY STAR™-compliant	
CDC	One Communications Daughter Card (CDC) socket (used by modem) / not accessible										IBM ImageUltra™ Services available	
Modem	56K ⁹ V.90 (V.92-designed ²⁹) modem in CDC / Conexant® chipset										International Warranty Service ¹⁷	
Bluetooth	None										24 hour x 7 day ¹⁸ toll-free warranty support during the warranty ¹²	
Ethernet	10/100 ethernet on planar / Intel 82562EZ chipset (physical layer) / Wake on LAN®										ServicePac®. ²² 1yr IOR 9x5 NBD	
Audio support	Soft audio / ICH AC97 controller / DirectSound® support / AD1981B AC97 codec / stereo speakers / 1 watt / volume up, down, mute buttons / internal microphone / microphone input jack (3.5 mm) / headphone jack (3.5 mm) / no line in jack										30L9188	
Security	Power-on password / hard disk password / supervisor password / security keyhole										ServicePac 2 yr IOR 9x5 NBD	
Security chip	IBM Embedded Security Subsystem 2.0 ³³ / hardware key storage / multi-factor authentication / local file encryption / enhances VPN security ¹⁶ / TCG-compliant										30L9189	
Limited warranty ¹²	1 year - EasyServ™ ¹⁹ onsite pickup and delivery / service upgrades ²² available										ServicePac 3 yr IOR 9x5 NBD	
128 MB PC2700 DDR-SDRAM CL2.5 SOD	31P9828			T40/R50 Series Li-Ion Battery 6-cell			08K8214			ServicePac 4 yr IOR 9x5 NBD		
256 MB PC2700 DDR-SDRAM CL2.5 SOD	31P9830			T40/R50 High Capacity Li-Ion Batt 9-cell			08K8197			30L9194		
512 MB PC2700 DDR-SDRAM CL2.5 SOD	31P9832			Ultrabay Slim Li-Polymer Battery 3-cell			08K8190			30L9196		
1GB PC2700 DDR-SDRAM CL2.5 SOD	31P9834			ThinkPad Multiple Battery Charger II			22P9040			ServicePac 2 yr P&L P/U Depot		
Second HDD Adapter for Ultrabay Slim	62P4554			40GB HS Hard Disk 9.5mm (5400 rpm)			08K9816			30L9191		
ThinkPad DVD-ROM Ultrabay Slim Drive	73P3270			80GB HS Hard Disk 9.5mm (5400 rpm)			09N4273			ServicePac 3 yr P&L P/U Depot		
CD-RW/DVD Combo Ultrabay Enhanced	73P3275			Intel PRO/Wireless 2200BG Mini PCI			73P2801			30L9192		
Multi-Burner Plus Ultrabay Enhanced Drive	73P3312			IBM 11a/b/g Wireless Mini PCI Adapter II			73P4301			ServicePac 4 yr P&L P/U Depot		
IBM 4GB Microdrive™ with PC Card	09N4280			IBM 11a/b/g Wireless CardBus Adapter			31P9101			69P9195		
IBM USB Portable Diskette Drive	05K9276			SonyEricsson® GC83 EDGE PC Card			26K3393			ServicePac 5 yr P&L P/U Depot		
IBM USB 2.0 Portable Multi-Burner Drive	22P9163			ThinkPad 72W AC/DC Combo Adapter			22P9010			69P9197		
IBM USB 2.0 Memory Key 512MB	22P9230			ThinkPad Port Replicator II			74P6733			Post-warranty annual maintenance agreements at		
TrackPoint Cap Collection	73P2698			ThinkPad Mini Dock			287810U			ibm.com/services/its/us/source/maspspleu.pdf		
Kensington® MicroSaver® Security Cable	73P2582			ThinkPad Dock II			287710U					
ThinkPad Carrying Case - Leather	73P3600			Other options at ibm.com/pc/us/accessories								

See footnotes for important warranty information
US models announced July 13, 2004; previous models on April 6, 2004
US models withdrawn effective January 2005

* Powered by Intel Centrino™ mobile technology

Availability: All offers subject to availability. IBM reserves the right to alter product offerings and specifications at any time, without notice. IBM is not responsible for photographic or typographic errors.

Warranty: For a copy of applicable product warranties, write to: Warranty Information, P.O. Box 12195, RTP, NC, 27709, Attn: Dept JDJA/B203. IBM makes no representation or warranty regarding third party products or services.

Footnotes:

- ¹ With Intel SpeedStep, processor speed may be reduced to conserve battery power.
- ² **Travel weight** includes battery and optional travel bezel instead of standard optical drive in Ultrabay bay, if applicable; weight may vary due to vendor components, manufacturing process and options.
- ³ **Thinness** may vary at certain points on the system.
- ⁴ **Wireless capability:** Requires compatible wireless-enabled options sold separately.
- ⁵ **TAA:** ThinkPad notebook is compliant with the U.S. Federal Government's country-of-origin requirements prescribed in 48 C.F.R. Subpart 25.4; Trade Act Agreement (TAA) model.
- ⁶ **Public network download speeds** are limited to 53Kbps. Upload speeds are limited to 31.2Kbps. Compatible phone line and server equipment required. Actual speeds depend on many factors and are often less than the maximum possible.
- ⁷ **Maximum memory and hard disk drive capacity** may require the replacement of standard component with largest supported component available.
- ⁸ **Hard drive:** GB = billion bytes, TB = trillion bytes. Accessible capacity may be less; up to 4GB is used in service partition.
- ⁹ **CD/DVD drive speeds** list maximum rates; rates are variable and are often less than the maximum.
- ¹⁰ **Battery:** These model numbers achieved the Ziff Davis Media Inc.'s Business Winstone 2002 BatteryMark™ Version 1.0, Battery Rundown Time of at least the times shown. This test was performed without independent verification by the VeriTest testing division of Lionbridge Technologies, Inc. ("VeriTest") nor Ziff Davis Media Inc.; neither Ziff Davis Media Inc. nor VeriTest makes any representations or warranties as to these test results. Winstone is a registered trademark and BatteryMark is a trademark of Ziff Davis Publishing Holdings Inc., in the US and other countries. A description of the environment under which the test was performed is available at ibm.com/pc/ww/thinkpad/batterylife. Battery life (and recharge times) will vary based on many factors including screen brightness, applications, features, power management, battery conditioning and other customer preferences. Refer to ibm.com/pc/support and enter machine type and model number for more information.
- ¹¹ **Memory:** For ThinkPad models without a separate video card, memory supports both system and video. Accessible system memory may be up to 64MB less than the amount stated, depending on video mode.
- ¹² **Limited warranty:** Support unrelated to a warranty issue may be subject to additional charges.
- ¹³ **Internet access not included.**
- ¹⁴ **Included software** may differ from its retail version (if available), and may not include user manuals or all program functionality. Software license agreements may apply.
- ¹⁵ **Update Connector** is available to registered ThinkPad customers during the limited warranty period at no charge. Line charges may apply.
- ¹⁶ **IBM Embedded Security Subsystem** works with optional VPN software.
- ¹⁷ **International Warranty Service** is available in any country in which this product is sold and serviced. Service delivery methods and parts availability vary by country, may be different from that in the country of purchase, and are subject to change without notice. Fees and restrictions may apply in some countries.
- ¹⁸ **Telephone support** may be subject to additional charges, even during the limited warranty period. If a machine is listed as having "On-site service for select repairs", this means that onsite service is available only for the replacement of select parts. For all other warranty repairs, IBM will provide the customer a replacement part for customer installation. The parts for which onsite service is available varies by machine, but may include the processor, power supply, heat sink, system board, or base cover. For IBM machines with EasyServ or Courier service, IBM will attempt to diagnose and resolve the problem remotely before sending a courier.
- ¹⁹ **Depot repair:** The customer may be asked certain diagnostic questions before a courier is sent. Your ThinkPad purchase includes this depot repair service, available in the U.S. during the warranty period.
- ²⁰ **Delivered with** Windows 2000, Windows XP Professional, or Windows XP Home Edition preloaded and a recovery partition on the hard disk drive.
- ²¹ **For combination drives**, maximum possible speeds only are given in the following order: CD write, CD rewrite, CD read, DVD read.
- ²² **These services** are available for machines normally used for business, professional, or trade purposes, rather than personal, family, or household purposes. Not all machine types and models are covered. Service period begins with the equipment date of purchase. Service must be purchased during the original limited product warranty period. If the machine problem turns out to be a Customer Replaceable Unit (CRU), IBM will express ship the part to you for quick replacement. Onsite 24x7x2-hour service is not available in all locations. For ThinkPad notebooks requiring LCD or other component replacement, IBM may choose to perform service at the depot repair center.

²³ **For ThinkPad X Series**, the 32GB, 48GB, and 60GB HDD only supports ThinkPad Dock, UltraBase X2, or X3 UltraBase media slice and requires the ThinkPad Second HDD Adapter for Ultra-bay 2000.

²⁴ **Systems with limited onsite service** are designed to be repaired during the applicable warranty period primarily with customer-replaceable parts provided by IBM. IBM will only send a technician onsite to perform a repair if (a) remote telephone diagnosis and/or customer part replacement are unable to resolve the problem, or (b) the part is one of the few designated by IBM for onsite replacement. For a list of onsite replaceable parts, contact IBM. Support unrelated to a warranty issue may be subject to additional charges. IBM onsite repair (IOR), 8 am to 5 pm, Monday through Friday coverage excluding holidays, next business day response time.

²⁵ **Linux preloaded systems** do not support UltraPort connector solutions and S-video-out port that may be included on this machine.

²⁶ **As defined by ISO/IEC 15412.**

²⁷ **Based on IEEE 802.11a and 802.11b.** A customer can not upgrade to a different wireless Mini PCI adapter due to FCC regulations. Security screws prevent removal of this adapter. This wireless LAN product has been designed to permit legal operation world-wide in regions which it is approved. This product has been tested and certified to be interoperable by the Wireless Ethernet Compatibility Alliance and is authorized to carry the Wi-Fi logo.

²⁸ **Certain Microsoft software products** included with this computer may use technological measures for copy protection. IN SUCH EVENT, YOU WILL NOT BE ABLE TO USE THE PRODUCT IF YOU DO NOT FULLY COMPLY WITH THE PRODUCT ACTIVATION PROCEDURES. Product activation procedures and Microsoft's privacy policy will be detailed during initial launch of the product, or upon certain reinstallations of the software products or reconfigurations of the computer, and may be completed by Internet or telephone (toll charges may apply).

²⁹ **Public network download speeds** are limited to 53Kbps. Upload speeds are limited to 48Kbps for V.92 modems. Actual speeds depend on many factors and are often less than the maximum possible. V.92 functions and speeds require compatible phone line and server equipment. Check with your telephone and ISP service providers for availability. Requires download of V.92 microcode when available and country approval.

³⁰ **Measures only maximum** data transfer rate, not application performance. Many factors affect application performance.

³¹ **Internet access** account (not included) and profiling at ibm.com/support required.

³² **Wireless:** based on IEEE 802.11a, 802.11b, and 802.11g respectively. An adapter with 11a/b, 11b/g, or 11a/b/g can communicate on either/any of these listed formats respectively, the actual connection will be based on the access point to which it connects.

- ³³ **IBM Embedded Security Subsystem** requires download of client security software from the Web and requires Internet access, not included.
- ³⁴ **Asset ID** allows system-specific information to be stored in a chip inside the system; it does not have any radio frequency support.
- ³⁵ **Operating system:** Level of support varies by operating system. Operating systems not preloaded on the system may not provide full feature functionality. Refer to ibm.com/pc/support and enter your machine type and model number for more information.
- ³⁶ **Wireless upgradable** allows the system to be wireless-enabled with an optional wireless Mini PCI card. These systems are designed to operate only with wireless LAN Mini PCI options sold by IBM.
- ³⁷ **Mobile processors:** Power management features reduce processor speed when in battery mode.

This publication was developed for products and services offered in the United States. IBM may not offer the products, services or features discussed in this document in other countries. IBM may withdraw an offering at any time. Information is subject to change without notice. Consult your local IBM representative for information on offerings available in your area.

IBM reserves the right to change specifications or other product information without notice. IBM is not responsible for photographic or typographical errors. IBM PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.



Trademarks: IBM, the IBM logo HelpCenter, IBM Rescue and Recovery, Rapid Restore, EasyServ, EtherJet, Lotus Notes, Lotus SmartSuite, ScrollPoint, ThinkLight, ThinkPad, ThinkPad Assistant, TrackPoint, ServicePac, UltraNav, Ultrabay, ImageUltra, UltraConnect, and Update Connector are trademarks or registered trademarks of IBM Corporation in the United States and/or other countries. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. Any use of such marks by IBM is under license. Microsoft and Windows are trademarks of Microsoft Corporation. Intel, Intel Inside, the Intel Inside logo, Intel Centrino logo, Pentium, Celeron and Intel SpeedStep are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. Cisco and Aironet are registered trademarks of Cisco Corporation. Linux is a trademark of Linus Torvalds in the United States, other countries, or both. Other company, product and service names may be trademarks or service marks of others.

ENERGY STAR: As an ENERGY STAR Partner, IBM has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR is a U.S. registered mark.

Visit ibm.com/pc/safecomputing periodically for the latest information on safe and effective computing.

© Copyright International Business Machines Corporation, 2005.
All rights reserved

IBM Personal Computing Division
Department WY3A
3039 Cornwallis Road
Research Triangle Park, NC 27709

May 2005
trwbook.pdf